

# Repartição do server da série C UCS que pesquisa defeitos TechNote

## Índice

[Introdução](#)

[Pré-requisitos](#)

[Requisitos](#)

[Componentes Utilizados](#)

[Rendimento esperado para condições diferentes da repartição](#)

[Repartição do OS \(vSphere 5.0\)](#)

[Ciclo da potência CIMC da interface do utilizador](#)

[Sem energia CIMC da interface do utilizador](#)

[Potência sobre CIMC da interface do utilizador](#)

[Botão da potência na parte dianteira do server \(FORA\)](#)

[Botão da potência na parte dianteira do server \(SOBRE\)](#)

## Introdução

Este documento fornece a saída de `/var/log/messages` (igualmente encontrado no log a bordo do registro de falha (OBFL)) para um C210-M2 que descreva o rendimento esperado durante a repartição diferente condicione. Quando você pesquisa defeitos questões de inicialização do server da série C do Cisco Unified Computing System (UCS), um lugar a começar é `/var/log/messages` e logs OBFL. Estes logs são ficados situados nos arquivos do suporte técnico. A ideia é que você pode combinar a saída de uma mensagem particular do suporte técnico com a saída neste documento a fim confirmar o que provocou a repartição.

## Pré-requisitos

### Requisitos

A Cisco recomenda que você tenha conhecimento destes tópicos:

- VSphere 5.0 de VMware
- Controlador do gerenciamento integrado de Cisco (CIMC)

### [Componentes Utilizados](#)

Este documento não se restringe a versões de software e hardware específicas.

As informações neste documento foram criadas a partir de dispositivos em um ambiente de laboratório específico. Todos os dispositivos utilizados neste documento foram iniciados com uma configuração (padrão) inicial. Se a sua rede estiver ativa, certifique-se de que entende o impacto potencial de qualquer comando.

# Rendimento esperado para condições diferentes da repartição

## Repartição do OS (vSphere 5.0)

```
5:2012 May 11 13:49:38:BMC:kernel:--<5>LPC Reset ISR -> ResetState: 1
7:2012 May 11 13:49:38:BMC:kernel:--<7>[peci_init_hardware]:490:peci:
  unregistered IRQ: [13]
7:2012 May 11 13:49:38:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
  1141:block_transfer_deallocate_entire_list
7:2012 May 11 13:49:38:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
  1185:block_transfer_deallocate_entire_list : Dumped: 0x0002 files.
5:2012 May 11 13:49:38:BMC:BIOSReader:391: BIOSReader.c:555:File Close :
  /var/nuova/BIOS/BiosTech_1.txt
5:2012 May 11 13:49:38:BMC:BIOSReader:391: BIOSReader.c:555:File Close :
  /var/nuova/BIOS/BiosTech_4.txt
5:2012 May 11 13:49:38:BMC:kernel:--<5>[block_transfer_fetch_host_request_for_app]:
  2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
  HostBTDescr = 126 : FName = BiosTech_1.txt
5:2012 May 11 13:49:38:BMC:kernel:--<5>[block_transfer_fetch_host_request_for_app]:
  2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
  HostBTDescr = 125 : FName = BiosTech_4.txt
5:2012 May 11 13:49:38:BMC:kernel:--<5>LPC Reset ISR -> ResetState: 0
7:2012 May 11 13:49:38:BMC:kernel:--<7>[peci_init_hardware]:472:peci:
  registered IRQ: [13]
5:2012 May 11 13:49:38:BMC:kernel:--<5>[lpc_reset_handler_Port80_Capture_setup]:
  630:BIOS_POST_CMPLT De-asserted --> BIOS is running
7:2012 May 11 13:49:38:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
  1141:block_transfer_deallocate_entire_list
7:2012 May 11 13:49:38:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
  1185:block_transfer_deallocate_entire_list : Dumped: 0x0000 files.
6:2012 May 11 13:49:38:BMC:avct_server:--: rvas_wait_for_changes failed
4:2012 May 11 13:49:38:BMC:avct_server:--: No Video Source Detected!
5:2012 May 11 13:49:39:BMC:bioscom:--: lv_mode_dimm_support.c:126:
  [lpc_reset_seen]LPC Reset Count is Different [0x28:0x29]
  Asserted LPC Reset Seen
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
  Fn:0x4 Cmd:0x28 Resp:0x0
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1415:audit data&colon; 0x9 0x80
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
  Fn:0x4 Cmd:0x28 Resp:0x0
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1415:audit data&colon; 0xa 0x80
5:2012 May 11 13:49:39:BMC:bioscom:--: lv_mode_dimm_support.c:197:
  [transition_function]Starting Transition to
  [High Voltage Mode] from [Unknown Mode]
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
  Fn:0x4 Cmd:0x28 Resp:0x0
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1415:audit data&colon; 0x9 0x80
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
  Fn:0x4 Cmd:0x28 Resp:0x0
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1415:audit data&colon; 0xa 0x80
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
  Fn:0x4 Cmd:0x26 Resp:0x0
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1415:audit data&colon;
  0x9 0x36 0x92 0x92 0x89 0x9f 0x9f 0xa8
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
  Fn:0x4 Cmd:0x26 Resp:0x0
5:2012 May 11 13:49:39:BMC:IPMI:585: Bridge.c:1415:audit data&colon;
  0xa 0x36 0x92 0x92 0x89 0x9f 0x9f 0xa8
5:2012 May 11 13:49:39:BMC:bioscom:--: lv_mode_dimm_support.c:217:
  [transition_function]Transition to [High Voltage Mode] Success
```

```

5:2012 May 11 13:49:39:BMC:IPMI:591: VirtualSEL.c:224:SEL Evt[04 00]<
04 00 02 F3 18 AD 4F 20 00 04 25 53 08 00 FF FF >
5:2012 May 11 13:49:39:BMC:BIOSReader:391: BIOSReader.c:227:File Open :
BiosTech_3.txt
5:2012 May 11 13:49:39:BMC:kernel:--<5>[block_transfer_fetch_host_request_for_app]:
2063:block_transfer_fetch_host_request_for_app: BT_OPEN:
HostDescriptor = 131 : Filename = BiosTech_3.txt
7:2012 May 11 13:49:39:BMC:kernel:--<7>[mailbox_isr]:276:
Mailbox[0] Bit Change w/NULL Handler (01 - 10)!
7:2012 May 11 13:49:39:BMC:kernel:--<7>[mailbox_isr]:276:
Mailbox[0] Bit Change w/NULL Handler (01 - 20)!
7:2012 May 11 13:49:39:BMC:kernel:--<7>[mailbox_isr]:276:
Mailbox[0] Bit Change w/NULL Handler (01 - 40)!
5:2012 May 11 13:49:39:BMC:kernel:--<5>LPC Reset ISR -> ResetState: 1
7:2012 May 11 13:49:39:BMC:kernel:--<7>[peci_init_hardware]:490:peci:
unregistered IRQ: [13]
7:2012 May 11 13:49:39:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
1141:block_transfer_deallocate_entire_list
7:2012 May 11 13:49:39:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
1185:block_transfer_deallocate_entire_list : Dumped: 0x0001 files.
5:2012 May 11 13:49:39:BMC:kernel:--<5>LPC Reset ISR -> ResetState: 0
7:2012 May 11 13:49:39:BMC:kernel:--<7>[peci_init_hardware]:472:peci:
registered IRQ: [13]

```

#### Notas:

- Somente a bota do OS não imprime a saída do “do\_power”. Você pode usar este fato a fim determinar rapidamente se o server carregou o OS.
- Somente a bota do OS imprime transições do [High Voltage Mode].

## Ciclo da potência CIMC da interface do utilizador

```

5:2012 May 11 13:50:22:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
Fn:0x0 Cmd:0x2 Resp:0x0
5:2012 May 11 13:50:22:BMC:IPMI:585: Bridge.c:1415:audit data&colon; 0x2
7:2012 May 11 13:50:22:BMC:kernel:--<7>[do_power_off]:188:do_power_off
5:2012 May 11 13:50:22:BMC:kernel:--<5>[do_power_off]:190:Power Driver:
Power Off Logic @ 181790792
6:2012 May 11 13:50:22:BMC:kernel:--<6>[press_button]:105:Power Driver:
Press Power Button @ 181790793
5:2012 May 11 13:50:22:BMC:AUDIT:-- Server power state modify (op:power-cycle)
5:2012 May 11 13:50:26:BMC:kernel:--<5>LPC Reset ISR -> ResetState: 1
7:2012 May 11 13:50:26:BMC:kernel:--<7>[peci_init_hardware]:490:peci:
unregistered IRQ: [13]
7:2012 May 11 13:50:26:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
1141:block_transfer_deallocate_entire_list
7:2012 May 11 13:50:26:BMC:kernel:--<7>[block_transfer_deallocate_entire_list]:
1185:block_transfer_deallocate_entire_list : Dumped: 0x0001 files.
7:2012 May 11 13:50:26:BMC:kernel:--<7>USB FS: VDD Power WAKEUP- Power Good = OFF
7:2012 May 11 13:50:26:BMC:kernel:--<7>kbd_complete: -108, 0/8
7:2012 May 11 13:50:26:BMC:kernel:--<7>mouse_complete: -108, 0/6
7:2012 May 11 13:50:26:BMC:kernel:--<7>USB HS: VDD Power WAKEUP- Power Good = OFF
7:2012 May 11 13:50:26:BMC:kernel:--<7>bulk_out_complete: -108, 0/31, LUN[0][2]
7:2012 May 11 13:50:26:BMC:kernel:--<7>handle_exception: Handling
MSD_STATE_DISCONNECT for interface[0]
7:2012 May 11 13:50:26:BMC:kernel:--<7>do_set_interface(): reset_interface
7:2012 May 11 13:50:26:BMC:kernel:--<7>handle_exception:
Handling MSD_STATE_DISCONNECT for interface[1]
5:2012 May 11 13:50:26:BMC:kernel:--<5>[block_transfer_fetch_host_request_for_app]:
2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
HostBTDescr = 132 : FName = BiosTech_4.txt

```

```
6:2012 May 11 13:50:26:BMC:kernel:-:<6>kbdmouse_write:
    kbd write aborted for device reset.
6:2012 May 11 13:50:26:BMC:kernel:-:<6>kbdmouse_write:
    mouse write aborted for device reset.
6:2012 May 11 13:50:26:BMC:avct_server:-: rvas_wait_for_changes failed
5:2012 May 11 13:50:26:BMC:BIOSReader:391:
    BIOSReader.c:555:File Close : /var/nuova/BIOS/BiosTech_4.txt
```

## Sem energia CIMC da interface do utilizador

```
5:2012 May 11 13:58:57:BMC:IPMI:585: Bridge.c:1388:audit from:kcs
    Fn:0x0 Cmd:0x2 Resp:0x0
7:2012 May 11 13:58:57:BMC:kernel:-:<7>[do_power_off]:188:do_power_off
5:2012 May 11 13:58:57:BMC:kernel:-:<5>[do_power_off]:190:Power Driver:
    Power Off Logic @ 182297296
6:2012 May 11 13:58:57:BMC:kernel:-:<6>[press_button]:105:Power Driver:
    Press Power Button @ 182297296
5:2012 May 11 13:58:57:BMC:IPMI:585: Bridge.c:1415:audit data&colon; 0x0
5:2012 May 11 13:58:57:BMC:AUDIT:-: Server power state modify (op:power-off)
5:2012 May 11 13:59:01:BMC:kernel:-:<5>LPC Reset ISR -> ResetState: 1
7:2012 May 11 13:59:01:BMC:kernel:-:<7>[peci_init_hardware]:490:peci:
    unregistered IRQ: [13]
7:2012 May 11 13:59:01:BMC:kernel:-:<7>[block_transfer_deallocate_entire_list]:
    1141:block_transfer_deallocate_entire_list
7:2012 May 11 13:59:01:BMC:kernel:-:<7>[block_transfer_deallocate_entire_list]:
    1185:block_transfer_deallocate_entire_list : Dumped: 0x0002 files.
7:2012 May 11 13:59:01:BMC:kernel:-:<7>USB FS: VDD Power WAKEUP- Power Good = OFF
7:2012 May 11 13:59:01:BMC:kernel:-:<7>USB HS: VDD Power WAKEUP- Power Good = OFF
7:2012 May 11 13:59:01:BMC:kernel:-:<7>bulk_out_complete: -108, 0/31, LUN[0][2]
7:2012 May 11 13:59:01:BMC:kernel:-:<7>handle_exception: Handling
    MSD_STATE_DISCONNECT for interface[0]
7:2012 May 11 13:59:01:BMC:kernel:-:<7>do_set_interface(): reset_interface
7:2012 May 11 13:59:01:BMC:kernel:-:<7>handle_exception: Handling
    MSD_STATE_DISCONNECT for interface[1]
5:2012 May 11 13:59:01:BMC:kernel:-:<5>[block_transfer_fetch_host_request_for_app]:
    2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
    HostBTDescr = 143 : FName = BiosTech_3.txt
5:2012 May 11 13:59:01:BMC:kernel:-:<5>[block_transfer_fetch_host_request_for_app]:
    2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
    HostBTDescr = 142 : FName = BiosTech_2.txt
6:2012 May 11 13:59:01:BMC:avct_server:-: rvas_wait_for_changes failed
5:2012 May 11 13:59:01:BMC:BIOSReader:391: BIOSReader.c:555:File Close :
    /var/nuova/BIOS/BiosTech_3.txt
5:2012 May 11 13:59:01:BMC:BIOSReader:391: BIOSReader.c:555:File Close :
    /var/nuova/BIOS/BiosTech_2.txt
```

## Potência sobre CIMC da interface do utilizador

```
5:2012 May 11 13:59:13:BMC:IPMI:585: Bridge.c:1388:audit from:
    kcs Fn:0x0 Cmd:0x2 Resp:0x0
5:2012 May 11 13:59:13:BMC:IPMI:585: Bridge.c:1415:audit data&colon; 0x1
7:2012 May 11 13:59:13:BMC:kernel:-:<7>[do_power_on]:226:do_power_on
5:2012 May 11 13:59:13:BMC:kernel:-:<5>[do_power_on]:231:Power Driver:
    Power On Logic Pulse for 250ms @ 182313079
6:2012 May 11 13:59:13:BMC:kernel:-:<6>[press_button]:105:Power Driver:
    Press Power Button @ 182313079
5:2012 May 11 13:59:13:BMC:AUDIT:-: Server power state modify (op:power-on)
6:2012 May 11 13:59:13:BMC:kernel:-:<6>[release_button]:115:Power Driver:
    Release Power Button @ 182313330
7:2012 May 11 13:59:13:BMC:kernel:-:<7>USB FS: VDD Power WAKEUP-
    Power Good = ON
```

```

6:2012 May 11 13:59:13:BMC:kernel:--:<6>se_pilot2_udc_usb_turnon:
    Passed USB1.1 register test (0)
7:2012 May 11 13:59:13:BMC:kernel:--:<7>USB HS: VDD Power WAKEUP-
    Power Good = ON
6:2012 May 11 13:59:13:BMC:kernel:--:<6>se_pilot2_udc_usb_turnon:
    Passed USB2.0 register test (11)
5:2012 May 11 13:59:13:BMC:kernel:--:<5>LPC Reset ISR -> ResetState: 0
7:2012 May 11 13:59:13:BMC:kernel:--:<7>[peci_init_hardware]:472:peci:
    registered IRQ: [13]
5:2012 May 11 13:59:13:BMC:kernel:--:<5>[lpc_reset_handler_Port80_Capture_setup]:
    630:BIOS_POST_CMPLT De-asserted --> BIOS is running
7:2012 May 11 13:59:13:BMC:kernel:--:<7>[block_transfer_deallocate_entire_list]:
    1141:block_transfer_deallocate_entire_list
7:2012 May 11 13:59:13:BMC:kernel:--:<7>[block_transfer_deallocate_entire_list]:
    1185:block_transfer_deallocate_entire_list : Dumped: 0x0000 files.
5:2012 May 11 13:59:13:BMC:IPMI:587: Pilot2SrvPower.c:394:
    Blade Power Changed To: [ ON ]
5:2012 May 11 13:59:13:BMC:kernel:--:<5>[do_power_on]:
    251:Power Driver: Power On Logic Done @ 182313832
5:2012 May 11 13:59:13:BMC:IPMI:590: Pilot2SrvPower.c:
    188:Pilot2SrvPowerOn
5:2012 May 11 13:59:14:BMC:IPMI:591: VirtualSEL.c:224:
    SEL Evt[25 00]< 25 00 02 32 1B AD 4F 20 00 04 25 52 08 01 FF FF >
5:2012 May 11 13:59:14:BMC:IPMI:591: VirtualSEL.c:224:
    SEL Evt[26 00]< 26 00 02 32 1B AD 4F 20 00 04 25 53 08 00 FF FF >
5:2012 May 11 13:59:14:BMC:IPMI:591: VirtualSEL.c:224:
    SEL Evt[27 00]< 27 00 02 32 1B AD 4F 20 00 04 08 62 0B 00 FF FF >
5:2012 May 11 13:59:14:BMC:kernel:--:<5>[block_transfer_fetch_host_request_for_app]:
    2063:block_transfer_fetch_host_request_for_app: BT_OPEN:
    HostDescriptor = 148 : Filename = BiosTech_1.txt
5:2012 May 11 13:59:14:BMC:BIOSReader:391: BIOSReader.c:227:
    File Open : BiosTech_1.txt
7:2012 May 11 13:59:14:BMC:kernel:--:<7>[mailbox_isr]:276:
    Mailbox[0] Bit Change w/NULL Handler (01 - 10)!
7:2012 May 11 13:59:14:BMC:kernel:--:<7>[mailbox_isr]:276:
    Mailbox[0] Bit Change w/NULL Handler (01 - 20)!
7:2012 May 11 13:59:14:BMC:kernel:--:<7>[mailbox_isr]:276:
    Mailbox[0] Bit Change w/NULL Handler (01 - 40)!
5:2012 May 11 13:59:14:BMC:kernel:--:<5>LPC Reset ISR -> ResetState: 1
7:2012 May 11 13:59:14:BMC:kernel:--:<7>[peci_init_hardware]:490:peci:
    unregistered IRQ: [13]
7:2012 May 11 13:59:14:BMC:kernel:--:<7>[block_transfer_deallocate_entire_list]:
    1141:block_transfer_deallocate_entire_list
7:2012 May 11 13:59:14:BMC:kernel:--:<7>[block_transfer_deallocate_entire_list]:
    1185:block_transfer_deallocate_entire_list : Dumped: 0x0001 files.
6:2012 May 11 13:59:14:BMC:avct_server:--: Clear RVAS regs
5:2012 May 11 13:59:14:BMC:kernel:--:<5>LPC Reset ISR -> ResetState: 0

```

## Botão da potência na parte dianteira do server (FORA)

```

6:2012 May 11 14:01:51:BMC:storage:--: SLOT-5:
    Time established as 05/11/12 14:01:27; (75 seconds since power on)
6:2012 May 11 14:01:51:BMC:avct_server:--:
    rvas_wait_for_changes failed
5:2012 May 11 14:01:51:BMC:kernel:--:<5>LPC Reset ISR -> ResetState: 1
7:2012 May 11 14:01:51:BMC:kernel:--:<7>[peci_init_hardware]:490:peci:
    unregistered IRQ: [13]
7:2012 May 11 14:01:51:BMC:kernel:--:<7>[block_transfer_deallocate_entire_list]:
    1141:block_transfer_deallocate_entire_list
7:2012 May 11 14:01:51:BMC:kernel:--:<7>[block_transfer_deallocate_entire_list]:
    1185:block_transfer_deallocate_entire_list : Dumped: 0x0002 files.
7:2012 May 11 14:01:51:BMC:kernel:--:<7>USB FS: VDD Power WAKEUP- Power Good = OFF

```

```
7:2012 May 11 14:01:51:BMC:kernel:-:<7>USB HS: VDD Power WAKEUP- Power Good = OFF
7:2012 May 11 14:01:51:BMC:kernel:-:<7>bulk_out_complete: -108, 0/31, LUN[0][0]
7:2012 May 11 14:01:51:BMC:kernel:-:<7>handle_exception: Handling
MSD_STATE_DISCONNECT for interface[0]
7:2012 May 11 14:01:51:BMC:kernel:-:<7>do_set_interface(): reset_interface
7:2012 May 11 14:01:51:BMC:kernel:-:<7>handle_exception: Handling
MSD_STATE_DISCONNECT for interface[1]
5:2012 May 11 14:01:51:BMC:BIOSReader:391: BIOSReader.c:555:File Close :
/var/nuova/BIOS/BiosTech_3.txt
5:2012 May 11 14:01:51:BMC:BIOSReader:391: BIOSReader.c:555:File Close :
/var/nuova/BIOS/BiosTech_2.txt
5:2012 May 11 14:01:51:BMC:kernel:-:<5>[block_transfer_fetch_host_request_for_app]:
2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
HostBTDescr = 150 : FName = BiosTech_3.txt
5:2012 May 11 14:01:51:BMC:kernel:-:<5>[block_transfer_fetch_host_request_for_app]:
2125:block_transfer_fetch_host_request_for_app : BT_FILE_CLOSE :
HostBTDescr = 149 : FName = BiosTech_2.txt
5:2012 May 11 14:01:51:BMC:IPMI:593: Pilot2SrvPower.c:394:
Blade Power Changed To: [ OFF ]
5:2012 May 11 14:01:51:BMC:IPMI:591: VirtualSEL.c:224:SEL Evt[33 00]<
33 00 02 CF 1B AD 4F 20 00 04 25 52 08 00 FF FF >
6:2012 May 11 14:01:51:BMC:IPMI:583: mcddI2CDrv.c:860:PI2CPerformOP:
ioctl to driver failed to read Bus[f4].Dev[5e]! ErrorStatus[32]
6:2012 May 11 14:01:52:BMC:IPMI:583: mcddI2CDrv.c:860:PI2CPerformOP:
ioctl to driver failed to read Bus[f4].Dev[5e]! ErrorStatus[32]
4:2012 May 11 14:01:52:BMC:avct_server:-: No Video Source Detected!
6:2012 May 11 14:01:52:BMC:avct_server:-: Video Source Detected!
5:2012 May 11 14:01:52:BMC:IPMI:591: VirtualSEL.c:224:
SEL Evt[34 00]< 34 00 02 D0 1B AD 4F 20 00 04 25 53 08 01 FF FF >
5:2012 May 11 14:01:52:BMC:bioscom:-: lv_mode_dimm_support.c:126:
[lpc_reset_seen]LPC Reset Count is Different [0x30:0x31]
Asserted LPC Reset Seen
```

## Botão da potência na parte dianteira do server (SOBRE)

```
5:2012 May 11 14:01:58:BMC:IPMI:591: VirtualSEL.c:224:
SEL Evt[35 00]< 35 00 02 D6 1B AD 4F 20 00 04 08 62 0B 00 FF FF >
7:2012 May 11 14:01:58:BMC:kernel:-:<7>USB FS: VDD Power WAKEUP-
Power Good = ON
6:2012 May 11 14:01:58:BMC:kernel:-:<6>se_pilot2_udc_usb_turnon:
Passed USB1.1 register test (0)
7:2012 May 11 14:01:58:BMC:kernel:-:<7>USB HS: VDD Power WAKEUP-
Power Good = ON
6:2012 May 11 14:01:58:BMC:kernel:-:<6>se_pilot2_udc_usb_turnon:
Passed USB2.0 register test (11)
5:2012 May 11 14:01:58:BMC:kernel:-:<5>LPC Reset ISR -> ResetState: 0
7:2012 May 11 14:01:58:BMC:kernel:-:<7>[peci_init_hardware]:472:peci:
registered IRQ: [13]
5:2012 May 11 14:01:58:BMC:kernel:-:<5>[lpc_reset_handler_Port80_Capture_setup]:
630:BIOS_POST_CMPLT De-asserted --> BIOS is running
7:2012 May 11 14:01:58:BMC:kernel:-:<7>[block_transfer_deallocate_entire_list]:
1141:block_transfer_deallocate_entire_list
7:2012 May 11 14:01:58:BMC:kernel:-:<7>[block_transfer_deallocate_entire_list]:
1185:block_transfer_deallocate_entire_list : Dumped: 0x0000 files.
5:2012 May 11 14:01:59:BMC:IPMI:587: Pilot2SrvPower.c:394:
Blade Power Changed To: [ ON ]
5:2012 May 11 14:01:59:BMC:kernel:-:<5>[block_transfer_fetch_host_request_for_app]:
2063:block_transfer_fetch_host_request_for_app: BT_OPEN:
HostDescriptor = 155 : Filename = BiosTech_1.txt
5:2012 May 11 14:01:59:BMC:BIOSReader:391: BIOSReader.c:227:File Open :
BiosTech_1.txt
5:2012 May 11 14:01:59:BMC:kernel:-:<5>LPC Reset ISR -> ResetState: 1
```

7:2012 May 11 14:01:59:BMC:kernel:-:<7>[peci\_init\_hardware]:490:peci:  
unregistered IRQ: [13]

7:2012 May 11 14:01:59:BMC:kernel:-:<7>[block\_transfer\_deallocate\_entire\_list]:  
1141:block\_transfer\_deallocate\_entire\_list

7:2012 May 11 14:01:59:BMC:kernel:-:<7>[block\_transfer\_deallocate\_entire\_list]:  
1185:block\_transfer\_deallocate\_entire\_list : Dumped: 0x0001 files.

5:2012 May 11 14:01:59:BMC:kernel:-:<5>[block\_transfer\_fetch\_host\_request\_for\_app]:  
2125:block\_transfer\_fetch\_host\_request\_for\_app : BT\_FILE\_CLOSE :  
HostBTDescr = 155 : FName = BiosTech\_1.txt

5:2012 May 11 14:01:59:BMC:BIOSReader:391: BIOSReader.c:555:File Close :  
/var/nuova/BIOS/BiosTech\_1.txt

5:2012 May 11 14:01:59:BMC:kernel:-:<5>LPC Reset ISR -> ResetState: 0

7:2012 May 11 14:01:59:BMC:kernel:-:<7>[peci\_init\_hardware]:472:peci:  
registered IRQ: [13]

5:2012 May 11 14:01:59:BMC:kernel:-:<5>[lpc\_reset\_handler\_Port80\_Capture\_setup]:  
630:BIOS\_POST\_CMPLT De-asserted --> BIOS is running

7:2012 May 11 14:01:59:BMC:kernel:-:<7>[block\_transfer\_deallocate\_entire\_list]:  
1141:block\_transfer\_deallocate\_entire\_list

7:2012 May 11 14:01:59:BMC:kernel:-:<7>[block\_transfer\_deallocate\_entire\_list]:  
1185:block\_transfer\_deallocate\_entire\_list : Dumped: 0x0000 files.

6:2012 May 11 14:01:59:BMC:avct\_server:-: Clear RVAS regs

5:2012 May 11 14:01:59:BMC:IPMI:591: VirtualSEL.c:224:SEL Evt[36 00]<  
36 00 02 D7 1B AD 4F 20 00 04 25 52 08 01 FF FF >

6:2012 May 11 14:02:00:BMC:avct\_server:-: Set TSTMUL reg to 0x00100000

5:2012 May 11 14:02:00:BMC:IPMI:591: VirtualSEL.c:224:SEL Evt[37 00]<  
37 00 02 D8 1B AD 4F 20 00 04 25 53 08 00 FF FF >

6:2012 May 11 14:02:00:BMC:avct\_server:-: Detected VGA Text Mode: 80 x 25 chars

6:2012 May 11 14:02:00:BMC:avct\_server:-: Current Graphics Core Settings are:

6:2012 May 11 14:02:00:BMC:avct\_server:-: 720 x 400, 4 bits per pixel, 640 pitch,  
in VGA mode

6:2012 May 11 14:02:00:BMC:avct\_server:-: Video Signal detected: 720 x 400,  
color depth is: 4 bits

6:2012 May 11 14:02:00:BMC:avct\_server:-: VGA Text mode

6:2012 May 11 14:02:00:BMC:avct\_server:-: Change Detected before TFE start

5:2012 May 11 14:02:00:BMC:bioscom:-: lv\_mode\_dimm\_support.c:126:  
[lpc\_reset\_seen]LPC Reset Count is Different [0x31:0x32]  
Asserted LPC Reset Seen