

Índice

[Introdução](#)

[Pré-requisitos](#)

[Requisitos](#)

[Componentes Utilizados](#)

[Encenações comuns da normalização da mensagem do SORVO](#)

[Copie o valor do encabeçamento da “diversão” ao “” do encabeçamento](#)

[O número de cópia “” ao encabeçamento em um entrante convida ao parâmetro “REQ-URI” \(antes do Cisco IOS Versão 15.4\)](#)

[O número de cópia “” ao encabeçamento em um entrante convida ao parâmetro “REQ-URI” \(com perfis de entrada do SORVO\)](#)

[Questões de interoperabilidade audio de sentido único/no-way com fornecedor](#)

[Remova o apoio do método da “ATUALIZAÇÃO” para evitar questões de interoperabilidade](#)

[Endereço IP de Um ou Mais Servidores Cisco ICM NT à conversão do Domain Name](#)

[Adicionar um prefixo no encabeçamento da “diversão”](#)

[Possíveis problemas](#)

Introdução

Este documento descreve como usar a [ferramenta de teste do perfil do Session Initiation Protocol \(SIP\)](#) que está disponível para o uso em Cisco.com. Os perfis do SORVO são usados a fim manipular a informação de cabeçalho nas mensagens do SORVO. Podem igualmente ser usados para fazer mudanças no protocolo session description (SDP), que é usado para negociar media.

Pré-requisitos

Requisitos

A informação neste documento é baseada de série da geração 1 (2800/3800) ou da geração 2 do roteador do serviço integrado de Cisco (ISR) em 2900/3900) (.

[Componentes Utilizados](#)

A Cisco recomenda que você tenha conhecimento destes tópicos:

- Navegação através do [®] do Cisco IOS
- Formato de mensagem e transações do SORVO

Encenações comuns da normalização da mensagem do SORVO

Esta seção fornece diversas encenações da normalização da mensagem do SORVO que foram consideradas frequentemente. Cada encenação inclui a configuração exigida no Cisco IOS para você referência e um tiro de tela da ferramenta de teste do perfil do SORVO que é mencionada na introdução.

Estas encenações podem ser usadas como referências para a outra manipulação exigida nas mensagens do SORVO.

Copie o valor do encabeçamento da “diversão” ao “” do encabeçamento

SIP-Profile:

```
voice class sip-profiles 1
request INVITE sip-header Diversion copy "< sip:(.*)@.*" u01
request INVITE sip-header From copy ".*< sip:(.*)@.*" u02
request INVITE sip-header From modify "(.*)< sip:.*@(.*)" "\1< sip:\u01@\2"
```

Input Message	Output Message
INVITE sip:18774116706@172.30.238.49:5071 SIP/2.0 Via: SIP/2.0/UDP 17.0.44.11:5060;branch=z9hG4bK6740831D5B From: < sip:8152456266@17.0.44.11>;tag=DEC125B4-3F9 To: < sip:18774116706@172.30.238.49> Date: Tue, 02 Sep 2014 17:33:26 GMT Call-ID: 14BF665C-31FE11E4- FFFFFFFF8168E118-52ABD3C1@17.0.44.11 Supported: 100rel,timer,resource-priority,replaces,sdp-anat Min-SE: 1800 Diversion: < sip:88882614@17.0.44.11>;privacy=off; reason=unconditional,screen=no Content-Length: 0	INVITE sip:18774116706@172.30.238.49:5071 SIP/2.0 Via: SIP/2.0/UDP 17.0.44.11:5060;branch=z9hG4bK6740831D5B From: < sip:88882614@17.0.44.11>;tag=DEC125B4-3F9 To: < sip:18774116706@172.30.238.49> Date: Tue, 02 Sep 2014 17:33:26 GMT Call-ID: 14BF665C-31FE11E4- FFFFFFFF8168E118-52ABD3C1@17.0.44.11 Supported: 100rel,timer,resource-priority,replaces,sdp-anat Min-SE: 1800 Diversion: < sip:88882614@17.0.44.11>;privacy=off; reason=unconditional,screen=no Content-Length: 0

O número de cópia “” ao encabeçamento em um entrante convida ao parâmetro “REQ-URI” (antes do Cisco IOS Vesion 15.4)

Copie o número no ao encabeçamento em um de entrada convidam a mensagem e alteram o que parte CONVIDAM:

SIP-Profile:

```
voice class sip-copylist 1
sip-header TO

voice class sip-profiles 2
request INVITE peer-header sip TO copy "sip:(.*)@" u01
request INVITE sip-header SIP-Req-URI modify ".*(.*)" "INVITE sip:\u01@\1"
```

Input Message	Output Message
<pre>INVITE sip:+18774116700@172.30.238.49:5071 SIP/2.0 Via: SIP/2.0/UDP 17.0.44.11:5060;branch=z9hG4bK6740831D5B From: <sip:8152456266@17.0.44.11>;tag=DEC125B4-3F9 To: <sip:18774116706@172.30.238.49> Date: Tue, 02 Sep 2014 17:33:26 GMT Call-ID: 14BF665C-31FE11E4- FFFFFFFF8168E118-52ABD3C1@17.0.44.11 Supported: 100rel,timer,resource-priority,replaces,sdp-anat Min-SE: 1800 Diversion: <sip:88882614@17.0.44.11>;privacy=off; reason=unconditional,screen=no Content-Length: 0</pre>	<pre>INVITE sip:18774116706@172.30.238.49:5071 SIP/2.0 Via: SIP/2.0/UDP 17.0.44.11:5060;branch=z9hG4bK6740831D5B From: <sip:8152456266@17.0.44.11>;tag=DEC125B4-3F9 To: <sip:18774116706@172.30.238.49> Date: Tue, 02 Sep 2014 17:33:26 GMT Call-ID: 14BF665C-31FE11E4- FFFFFFFF8168E118-52ABD3C1@17.0.44.11 Supported: 100rel,timer,resource-priority,replaces,sdp-anat Min-SE: 1800 Diversion: <sip:88882614@17.0.44.11>;privacy=off; reason=unconditional,screen=no Content-Length: 0</pre>

O número de cópia "" ao encabeçamento em um entrante convida ao parâmetro "REQ-URI" (com perfis de entrada do SORVO)

SIP-Profile:

```
voice class sip-profiles 1
request INVITE sip-header TO copy "sip:(.*)@" u01
request INVITE sip-header SIP-Req-URI modify ".*(.*)" "INVITE sip:\u01@\1"

voice service voip
sip
sip-profiles inbound
sip-profiles 1 inbound
```

Input Message	Output Message
<pre>INVITE sip:+18774116700@172.30.238.49:5071 SIP/2.0 Via: SIP/2.0/UDP 17.0.44.11:5060;branch=z9hG4bK6740831D5B From: <sip:8152456266@17.0.44.11>;tag=DEC125B4-3F9 To: <sip:18774116706@172.30.238.49> Date: Tue, 02 Sep 2014 17:33:26 GMT Call-ID: 14BF665C-31FE11E4- FFFFFFFF8168E118-52ABD3C1@17.0.44.11 Supported: 100rel,timer,resource-priority,replaces,sdp-anat Min-SE: 1800 Diversion: <sip:88882614@17.0.44.11>;privacy=off; reason=unconditional,screen=no Content-Length: 0</pre>	<pre>INVITE sip:18774116706@172.30.238.49:5071 SIP/2.0 Via: SIP/2.0/UDP 17.0.44.11:5060;branch=z9hG4bK6740831D5B From: <sip:8152456266@17.0.44.11>;tag=DEC125B4-3F9 To: <sip:18774116706@172.30.238.49> Date: Tue, 02 Sep 2014 17:33:26 GMT Call-ID: 14BF665C-31FE11E4- FFFFFFFF8168E118-52ABD3C1@17.0.44.11 Supported: 100rel,timer,resource-priority,replaces,sdp-anat Min-SE: 1800 Diversion: <sip:88882614@17.0.44.11>;privacy=off; reason=unconditional,screen=no Content-Length: 0</pre>

Questões de interoperabilidade audio de sentido único/no-way com fornecedor

SIP-Profile:

```
voice class sip-profiles 200
request ANY sip-header Audio-Attributes modify "a=inactive" "a=sendrcv"
request ANY sip-header Audio-Connection-Info modify "0.0.0.0" "10.10.10.1"
```

Input Message	Output Message
<pre>INVITE sip:18774116706@172.30.238.49:5071 SIP/2.0 Content-Disposition: session;handling=required Content-Length: 261 v=0 o=CiscoSystemsSIP-GW-UserAgent 1796 4793 IN IP4 17.0.44.11 s=SIP Call c=IN IP4 17.0.44.11 t=0 0 m=audio 0 RTP/AVP 0 101 19 c=IN IP4 0.0.0.0 a=rtpmap:0 PCMU/8000 a=inactive a=rtpmap:101 telephone-event/8000 a=ftmtp:101 0-16 a=rtpmap:19 CN/8000 a=ptime:20</pre>	<pre>INVITE sip:18774116706@172.30.238.49:5071 SIP/2.0 Content-Disposition: session;handling=required Content-Length: 273 v=0 o=CiscoSystemsSIP-GW-UserAgent 1796 4793 IN IP4 17.0.44.11 s=SIP Call c=IN IP4 17.0.44.11 t=0 0 m=audio 0 RTP/AVP 0 101 19 c=IN IP4 10.10.10.1 a=rtpmap:0 PCMU/8000 a=sendrcv a=rtpmap:101 telephone-event/8000 a=ftmtp:101 0-16 a=rtpmap:19 CN/8000 a=ptime:20</pre>

Remova o apoio do método da "ATUALIZAÇÃO" para evitar questões de interoperabilidade

SIP-Profile:

```
voice class sip-profiles 200
request ANY sip-header Allow-Header modify ", UPDATE" ""
```

Input Message	Output Message
<pre>INVITE sip:18774116706@172.30.238.49:5071 SIP/2.0 Via: SIP/2.0/UDP 17.0.44.11:5060;branch=z9hG4bK6740831D5B From: <sip:8152456266@17.0.44.11>;tag=DEC125B4-3F9 To: <sip:18774116706@172.30.238.49> Date: Tue, 02 Sep 2014 17:33:26 GMT Call-ID: 14BF665C-31FE11E4- FFFFFFFF8168E118-52ABD3C1@17.0.44.11 Allow: INVITE, OPTIONS, BYE, CANCEL, ACK, PRACK, UPDATE, REFER, SUBSCRIBE, NOTIFY, INFO, REGISTER Content-Length: 0</pre>	<pre>INVITE sip:18774116706@172.30.238.49:5071 SIP/2.0 Via: SIP/2.0/UDP 17.0.44.11:5060;branch=z9hG4bK6740831D5B From: <sip:8152456266@17.0.44.11>;tag=DEC125B4-3F9 To: <sip:18774116706@172.30.238.49> Date: Tue, 02 Sep 2014 17:33:26 GMT Call-ID: 14BF665C-31FE11E4- FFFFFFFF8168E118-52ABD3C1@17.0.44.11 Allow: INVITE, OPTIONS, BYE, CANCEL, ACK, PRACK, REFER, SUBSCRIBE, NOTIFY, INFO, REGISTER Content-Length: 0</pre>

Endereço IP de Um ou Mais Servidores Cisco ICM NT à conversão do Domain Name

SIP-Profile:

```
voice class sip-profiles 1
request ANY sip-header SIP-Req-URI modify "10.67.138.241:5060" "sipp.cisco.com"
```

Input Message	Output Message
<pre>INVITE sip:9819940331@10.67.138.241:5060 SIP/2.0 Via: SIP/2.0/UDP 17.0.44.11:5060;branch=z9hG4bK6740831D5B From: <sip:8152456266@17.0.44.11>;tag=DEC125B4-3F9 To: <sip:18774116706@172.30.238.49> Date: Tue, 02 Sep 2014 17:33:26 GMT Call-ID: 14BF665C-31FE11E4- FFFFFFFF8168E118-52ABD3C1@17.0.44.11 Allow: INVITE, OPTIONS, BYE, CANCEL, ACK, PRACK, UPDATE, REFER, SUBSCRIBE, NOTIFY, INFO, REGISTER Content-Length: 0</pre>	<pre>INVITE sip:9819940331@sipp.cisco.com SIP/2.0 Via: SIP/2.0/UDP 17.0.44.11:5060;branch=z9hG4bK6740831D5B From: <sip:8152456266@17.0.44.11>;tag=DEC125B4-3F9 To: <sip:18774116706@172.30.238.49> Date: Tue, 02 Sep 2014 17:33:26 GMT Call-ID: 14BF665C-31FE11E4- FFFFFFFF8168E118-52ABD3C1@17.0.44.11 Allow: INVITE, OPTIONS, BYE, CANCEL, ACK, PRACK, UPDATE, REFER, SUBSCRIBE, NOTIFY, INFO, REGISTER Content-Length: 0</pre>

Adicionar um prefixo no encabeçamento da "diversão"

SIP-Profile:

```
voice class sip-profiles 1
request ANY sip-header Diversion modify "sip:(.*)@" "sip:704264\1@"
```

Input Message	Output Message
<pre>INVITE sip:9819940331@10.67.138.241:5060 SIP/2.0 Via: SIP/2.0/UDP 17.0.44.11:5060;branch=z9hG4bK6740831D5B From: <sip:8152456266@17.0.44.11>;tag=DEC125B4-3F9 To: <sip:18774116706@172.30.238.49> Date: Tue, 02 Sep 2014 17:33:26 GMT Call-ID: 14BF665C-31FE11E4- FFFFFFFF8168E118-52ABD3C1@17.0.44.11 Allow: INVITE, OPTIONS, BYE, CANCEL, ACK, PRACK, UPDATE, REFER, SUBSCRIBE, NOTIFY, INFO, REGISTER Diversion: <sip:2614@17.0.44.11>;privacy=off; reason=unconditional,screen=no Content-Length: 0</pre>	<pre>INVITE sip:9819940331@10.67.138.241:5060 SIP/2.0 Via: SIP/2.0/UDP 17.0.44.11:5060;branch=z9hG4bK6740831D5B From: <sip:8152456266@17.0.44.11>;tag=DEC125B4-3F9 To: <sip:18774116706@172.30.238.49> Date: Tue, 02 Sep 2014 17:33:26 GMT Call-ID: 14BF665C-31FE11E4- FFFFFFFF8168E118-52ABD3C1@17.0.44.11 Allow: INVITE, OPTIONS, BYE, CANCEL, ACK, PRACK, UPDATE, REFER, SUBSCRIBE, NOTIFY, INFO, REGISTER Diversion: <sip:7042642614@17.0.44.11>;privacy=off; reason=unconditional,screen=no Content-Length: 0</pre>

Possíveis problemas

Estão aqui alguns possíveis problemas que você pôde encontrar.

- Após a versão do Cisco IOS 15.4, a característica do perfil do SORVO é introduzida para alterar também mensagens de entrada do SORVO.
- Versões do Cisco IOS 15.3 e somente perfis mais adiantados do SORVO do apoio na direção externa.