

OffRamp faxing de T.37

Índice

[Introdução](#)

[Pré-requisitos](#)

[Requisitos](#)

[Componentes Utilizados](#)

[Convenções](#)

[Configuração](#)

[Diagrama de Rede](#)

[Parâmetros de configuração](#)

[Configuração de OffRamp](#)

[Troubleshooting](#)

[Falhado debuga](#)

[O funcionamento debuga](#)

[Informações Relacionadas](#)

[Introdução](#)

Esta seção do documento principal do [fax de T.37 do FAX over IP store and forward \(guarda e passa adiante\)](#) focaliza no offramp que envia store and forward (guarda e passa adiante). O offramp T.37 é o processo por que um gateway aceita um email, os conversos que enviam por correio eletrônico a um fax, e o envia então para fora através de uma porta de voz.

Este documento contém a configuração necessária necessária obter a característica operacional. A seção da [pesquisa de defeitos](#) vai sobre os **comandos debug** úteis e como interpretar seu significado. A topologia usada é mostrada na seção do [diagrama da rede](#).

[Pré-requisitos](#)

[Requisitos](#)

As exigências específicas para este documento são especificadas na seção principal, [fax de T.37 do FAX over IP store and forward \(guarda e passa adiante\)](#).

[Componentes Utilizados](#)

Este documento não se restringe a versões de software e hardware específicas.

As informações neste documento foram criadas a partir de dispositivos em um ambiente de laboratório específico. Todos os dispositivos utilizados neste documento foram iniciados com uma configuração (padrão) inicial. Se a sua rede estiver ativa, certifique-se de que entende o impacto

potencial de qualquer comando.

Convenções

Para obter mais informações sobre convenções de documento, consulte as [Convenções de dicas técnicas Cisco](#).

Configuração

Nas seções abaixo, os parâmetros da configuração de software de Cisco IOS® relevantes à configuração do fax do offramp são explicados primeiramente, e a configuração 5300 é indicada então com as notas mais adicionais que esclarecem as funções de comandos importantes.

Diagrama de Rede

Este documento utiliza a instalação de rede mostrada no diagrama abaixo.



Parâmetros de configuração

Estão abaixo os comandos comuns usados na configuração de OffRamp do gateway:

Parâmetros imperativos:	
fax-correio do tipo de interface do fax	Permite a funcionalidade de T.37 para o gateway. Exige uma repartição nos 5300, mas não os 5350 ou os 5400.
o mta recebe pseudônimos	Define um hostname a ser usado como um pseudônimo para o gateway OffRamp. Até dez podem ser definidos. O gateway aceita o correio recebido se o nome de host de destino do correio de entrada combina um pseudônimo.
o mta recebe máximo-receptores	Define o número máximo de receptores simultâneos do Simple Mail Transfer Protocol (SMTP) tratados por este gateway.
informação-tipo entrante fax do chamar-número do offramp de	O comando application offramp refere o comando call application voice name . O <i>nome</i> combina o offramp. O comando incoming called-number é usado combinar este par do email multimídia sobre IP (MMoIP) de entrada. O comando

aplicativo do número MMolP da voz do dial peer	information-type fax identifica os atendimentos associados com este par como sendo transmissões de fax.
localização do nome de voz de aplicativo de chamada	Define um nome global para o aplicativo (offramp, neste caso) e seu lugar (em um servidor TFTP externo, neste caso).
Parâmetros opcionais:	
o fax envia o transmitir-subscritor	Define a identificação de assinante de transmissão (TSI).
o fax envia o fax do centro-encabeçame nto envia o fax do esquerdo-encabeçame nto envia o direito-encabeçame nto	As opções são: {\$a\$ \$d\$ \$p\$ \$s\$ \$t\$ corda} <ul style="list-style-type: none"> • \$a\$ — Data • \$d\$ — Endereço de destino • \$s\$ — Endereço do remetente • \$p\$ — Contagem da página • \$t\$ — Tempo de transmissão Use o argumento da <i>corda</i> neste comando introduzir uma sequência de caracteres de texto personalizada.
o fax envia o coverpage	As opções são: <ul style="list-style-type: none"> • permita — Permite o gateway OffRamp de enviar uma capa. • comentário — Adds personalizou comentários à capa. • mostra-detalle — Imprime o encabeçamento inteiro do email como parte da capa.
o mta recebe gerencie-mdn	Permite o gateway OffRamp de responder aos pedidos da notificação de disposição de mensagem (MDN).

[Configuração de OffRamp](#)

Os email foram enviados de Outlook Express ao gateway OffRamp (vdtl-5350-8a) e enviados a um número de destinos.

```
vdtl-5350-8a# show run
Building configuration...
```

```
Current configuration : 6415 bytes
```

```
!
```

```
version 12.2
```

```
service timestamps debug datetime msec localtime
```

```
service timestamps log datetime msec localtime
```

```
no service password-encryption
!
hostname vdtl-5350-8a
!
boot system flash c5350-is-mz.122-7.6.T1
enable secret 5 $1$MmyY$IQ3OW1Yfd9xjOJj5lYaC7.
!
!
resource-pool disable
clock timezone EST -5
!
!
ip subnet-zero
ip cef
ip domain-name testlab-t37.com
ip name-server 172.18.106.36
!
isdn switch-type primary-5ess
!
!
fax send transmitting-subscriber $$
fax send left-header $t$
fax send center-header $$
fax send right-header $p$
fax send coverpage enable
fax send coverpage show-detail
fax send coverpage comment vdtl-5350-8a Offramp Cover Page
fax interface-type fax-mail
mta receive aliases vdtl-5350-8a.testlab-t37.com
mta receive aliases 15.80.8.107
mta receive maximum-recipients 100
call-history-mib retain-timer 500
call-history-mib max-size 500
!
controller T1 3/0
framing esf
linecode b8zs
pri-group timeslots 1-24
!
!
interface FastEthernet0/0
ip address 15.80.8.107 255.255.255.0
!
interface Serial3/0:23
no ip address
isdn switch-type primary-5ess
isdn incoming-voice modem
!
interface Async1/00
no ip address
!
interface Async1/107
no ip address
!
interface Group-Async0
no ip address
no group-range
!
ip classless
ip route 0.0.0.0 0.0.0.0 15.80.8.1
no ip http server
ip pim bidir-enable
!
!
```

```
call rsvp-sync
!
call application voice offramp tftp://172.18.106.10/fax/offramp/app_libretto_offramp.2.0.1.1.tcl
!
voice-port 3/0:D
!
!
mgcp profile default
!
dial-peer voice 9813182 pots
incoming called-number 9813182
destination-pattern 9[2-9].....
direct-inward-dial
port 3/0:D
forward-digits all
!
dial-peer voice 1 mmoip
application offramp
incoming called-number 9.....
information-type fax
!
!
line con 0
exec-timeout 0 0
line aux 0
line vty 0 4
password ww
login
line 1/00 1/107
no flush-at-activation
modem InOut
!
scheduler allocate 10000 400
ntp clock-period 17179848
ntp server 172.18.106.15
end

vdt1-5350-8a#
```

Troubleshooting

Este documento é uma continuação do [OnRamp faxing de T.37](#). A maioria das referências de comandos alistadas nesse documento são usadas igualmente para o OffRamp faxing. Refira esse documento para mais informação.

Falhado debuga

Estes são os logs do **comando debug de uma** chamada de fax mal sucedida. Este **comando debug** foi emitido em um gateway de Cisco 5350, que atuasse como o gateway de fax do offramp para a rede neste exemplo.

```
vdt1-5350-8a# debug mta receive all
All email receive debugging is on
vdt1-5350-8a#
Mar 26 12:15:02.372: esmtp_server_work: calling ehlo
Mar 26 12:15:02.780: esmtp_server_work: calling mail
Mar 26 12:15:03.280: esmtp_server_work: calling rcpt
Mar 26 12:15:03.780: esmtp_server_work: calling data
```

Mar 26 12:15:04.280: (S)R: 'Received: from andyw2k ([172.18.106.183]) by vnt-smtp.testlab-t37.com with Microsoft SMTPSVC(5.0.2195.4453);'
Mar 26 12:15:04.280: (S)R: ' Tue, 26 Mar 2002 12:13:50 -0500'
Mar 26 12:15:04.280: (S)R: 'Message-ID: <000301c1d4e9\$c3a937c0\$b76a12ac@amer.cisco.com>'
Mar 26 12:15:04.280: (S)R: 'From: "Andy" <andy@testlab-t37.com>'
Mar 26 12:15:04.280: (S)R: 'To: <FAX=98915510@vdtl-5350-8a.testlab-t37.com>'
Mar 26 12:15:04.280: (S)R: 'Subject: test email with WinFax Pro...'
Mar 26 12:15:04.284: (S)R: 'MIME-Version: 1.0'
Mar 26 12:15:04.284: (S)R: 'Content-Type: multipart/mixed;'
Mar 26 12:15:04.284: (S)R: '
boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_NextPart_000_0000_01C1D4BF.DABAC5C0" '
Mar 26 12:15:04.284: (S)R: 'X-Mailer: Microsoft Outlook Express 6.00.2600.0000'
Mar 26 12:15:04.284: (S)R: 'X-MimeOLE: Produced By Microsoft MimeOLE V6.00.2600.0000'
Mar 26 12:15:04.284: (S)R: 'Return-Path: andy@testlab-t37.com'
Mar 26 12:15:04.284: (S)R: 'X-OriginalArrivalTime: 26 Mar 2002 17:13:50.0153 (UTC) FILETIME=[98F1B390:01C1D4E9] '
Mar 26 12:15:04.284: (S)R: 'Date: 26 Mar 2002 12:13:50 -0500'
Mar 26 12:15:04.284: (S)R: ''
Mar 26 12:15:04.284: esmtp_server_engine_new_part: Field name : message-id:
Field Value : <000301c1d4e9\$c3a937c0\$b76a12ac@amer.cisco.com>
Field name : from: Field Value : "Andy" <andy@testlab-t37.com>
Field name : to: Field Value : <FAX=98915510@vdtl-5350-8a.testlab-t37.com>
Field name : subject: Field Value : test email with WinFax Pro...
Field name : Content-Type: Field Value : multipart/mixed;

boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_NextPart_000_0000_01C1D4BF.DABAC5C0" '
Field name : date: Field Value : 26 Mar 2002 12:13:50 -0500

vdtl-5350-8a# **debug mta receive all**

All email receive debugging is on

vdtl-5350-8a#

Mar 26 12:15:02.372: esmtp_server_work: calling ehlo
Mar 26 12:15:02.780: esmtp_server_work: calling mail
Mar 26 12:15:03.280: esmtp_server_work: calling rcpt
Mar 26 12:15:03.780: esmtp_server_work: calling data
Mar 26 12:15:04.280: (S)R: 'Received: from andyw2k ([172.18.106.183]) by vnt-smtp.testlab-t37.com with Microsoft SMTPSVC(5.0.2195.4453);'
Mar 26 12:15:04.280: (S)R: ' Tue, 26 Mar 2002 12:13:50 -0500'
Mar 26 12:15:04.280: (S)R: 'Message-ID: <000301c1d4e9\$c3a937c0\$b76a12ac@amer.cisco.com>'
Mar 26 12:15:04.280: (S)R: 'From: "Andy" <andy@testlab-t37.com>'
Mar 26 12:15:04.280: (S)R: 'To: <FAX=98915510@vdtl-5350-8a.testlab-t37.com>'
Mar 26 12:15:04.280: (S)R: 'Subject: test email with WinFax Pro...'
Mar 26 12:15:04.284: (S)R: 'MIME-Version: 1.0'
Mar 26 12:15:04.284: (S)R: 'Content-Type: multipart/mixed;'
Mar 26 12:15:04.284: (S)R: '
boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_NextPart_000_0000_01C1D4BF.DABAC5C0" '
Mar 26 12:15:04.284: (S)R: 'X-Mailer: Microsoft Outlook Express 6.00.2600.0000'
Mar 26 12:15:04.284: (S)R: 'X-MimeOLE: Produced By Microsoft MimeOLE V6.00.2600.0000'
Mar 26 12:15:04.284: (S)R: 'Return-Path: andy@testlab-t37.com'
Mar 26 12:15:04.284: (S)R: 'X-OriginalArrivalTime: 26 Mar 2002 17:13:50.0153 (UTC) FILETIME=[98F1B390:01C1D4E9] '
Mar 26 12:15:04.284: (S)R: 'Date: 26 Mar 2002 12:13:50 -0500'
Mar 26 12:15:04.284: (S)R: ''
Mar 26 12:15:04.284: esmtp_server_engine_new_part: Field name : message-id:
Field Value : <000301c1d4e9\$c3a937c0\$b76a12ac@amer.cisco.com>
Field name : from: Field Value : "Andy" <andy@testlab-t37.com>
Field name : to: Field Value : <FAX=98915510@vdtl-5350-8a.testlab-t37.com>
Field name : subject: Field Value : test email with WinFax Pro...
Field name : Content-Type: Field Value : multipart/mixed;

boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_
NextPart_000_0000_01C1D4BF.DABAC5C0"

Field name : date: Field Value : 26 Mar 2002 12:13:50 -0500

vdctl-5350-8a# debug mta receive all

All email receive debugging is on

vdctl-5350-8a#

Mar 26 12:15:02.372: esmtp_server_work: calling ehlo

Mar 26 12:15:02.780: esmtp_server_work: calling mail

Mar 26 12:15:03.280: esmtp_server_work: calling rcpt

Mar 26 12:15:03.780: esmtp_server_work: calling data

Mar 26 12:15:04.280: (S)R: 'Received: from andyw2k ([172.18.106.183]) by

vnt-smtp.testlab-t37.com with Microsoft SMTPSVC(5.0.2195.4453);'

Mar 26 12:15:04.280: (S)R: ' Tue, 26 Mar 2002 12:13:50 -0500'

Mar 26 12:15:04.280: (S)R: 'Message-ID: <000301c1d4e9\$c3a937c0\$b76a12ac@amer.cisco.com>'

Mar 26 12:15:04.280: (S)R: 'From: "Andy" <andy@testlab-t37.com>'

Mar 26 12:15:04.280: (S)R: 'To: <FAX=98915510@vdctl-5350-8a.testlab-t37.com>'

Mar 26 12:15:04.280: (S)R: 'Subject: test email with WinFax Pro...'

Mar 26 12:15:04.284: (S)R: 'MIME-Version: 1.0'

Mar 26 12:15:04.284: (S)R: 'Content-Type: multipart/mixed;'

Mar 26 12:15:04.284: (S)R: '

boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_
NextPart_000_0000_01C1D4BF.DABAC5C0"

Mar 26 12:15:04.284: (S)R: 'X-Mailer: Microsoft Outlook Express 6.00.2600.0000'

Mar 26 12:15:04.284: (S)R: 'X-MimeOLE: Produced By Microsoft MimeOLE V6.00.2600.0000'

Mar 26 12:15:04.284: (S)R: 'Return-Path: andy@testlab-t37.com'

Mar 26 12:15:04.284: (S)R: 'X-OriginalArrivalTime: 26 Mar 2002 17:13:50.0153 (UTC)

FILETIME=[98F1B390:01C1D4E9]'

Mar 26 12:15:04.284: (S)R: 'Date: 26 Mar 2002 12:13:50 -0500'

Mar 26 12:15:04.284: (S)R: ''

Mar 26 12:15:04.284: esmtp_server_engine_new_part: Field name : message-id:

Field Value : <000301c1d4e9\$c3a937c0\$b76a12ac@amer.cisco.com>

Field name : from: Field Value : "Andy" <andy@testlab-t37.com>

Field name : to: Field Value : <FAX=98915510@vdctl-5350-8a.testlab-t37.com>

Field name : subject: Field Value : test email with WinFax Pro...

Field name : Content-Type: Field Value : multipart/mixed;

boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_
NextPart_000_0000_01C1D4BF.DABAC5C0"

Field name : date: Field Value : 26 Mar 2002 12:13:50 -0500

vdctl-5350-8a# debug mta receive all

All email receive debugging is on

vdctl-5350-8a#

Mar 26 12:15:02.372: esmtp_server_work: calling ehlo

Mar 26 12:15:02.780: esmtp_server_work: calling mail

Mar 26 12:15:03.280: esmtp_server_work: calling rcpt

Mar 26 12:15:03.780: esmtp_server_work: calling data

Mar 26 12:15:04.280: (S)R: 'Received: from andyw2k ([172.18.106.183]) by

vnt-smtp.testlab-t37.com with Microsoft SMTPSVC(5.0.2195.4453);'

Mar 26 12:15:04.280: (S)R: ' Tue, 26 Mar 2002 12:13:50 -0500'

Mar 26 12:15:04.280: (S)R: 'Message-ID: <000301c1d4e9\$c3a937c0\$b76a12ac@amer.cisco.com>'

Mar 26 12:15:04.280: (S)R: 'From: "Andy" <andy@testlab-t37.com>'

Mar 26 12:15:04.280: (S)R: 'To: <FAX=98915510@vdctl-5350-8a.testlab-t37.com>'

Mar 26 12:15:04.280: (S)R: 'Subject: test email with WinFax Pro...'

Mar 26 12:15:04.284: (S)R: 'MIME-Version: 1.0'

Mar 26 12:15:04.284: (S)R: 'Content-Type: multipart/mixed;'

Mar 26 12:15:04.284: (S)R: '

boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_
NextPart_000_0000_01C1D4BF.DABAC5C0"

Mar 26 12:15:04.284: (S)R: 'X-Mailer: Microsoft Outlook Express 6.00.2600.0000'

Mar 26 12:15:04.284: (S)R: 'X-MimeOLE: Produced By Microsoft MimeOLE V6.00.2600.0000'

Mar 26 12:15:04.284: (S)R: 'Return-Path: andy@testlab-t37.com'

```
Mar 26 12:15:04.284: (S)R: 'X-OriginalArrivalTime: 26 Mar 2002 17:13:50.0153 (UTC)
  FILETIME=[98F1B390:01C1D4E9]'
```

```
Mar 26 12:15:04.284: (S)R: 'Date: 26 Mar 2002 12:13:50 -0500'
```

```
Mar 26 12:15:04.284: (S)R: ''
```

```
Mar 26 12:15:04.284: esmtp_server_engine_new_part: Field name : message-id:
  Field Value : <000301c1d4e9$c3a937c0$b76a12ac@amer.cisco.com>
Field name : from: Field Value : "Andy" <andy@testlab-t37.com>
Field name : to: Field Value : <FAX=98915510@vdt1-5350-8a.testlab-t37.com>
Field name : subject: Field Value : test email with WinFax Pro...
Field name : Content-Type: Field Value : multipart/mixed;
```

```
boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_
NextPart_000_0000_01C1D4BF.DABAC5C0"
```

```
Field name : date: Field Value : 26 Mar 2002 12:13:50 -0500
```

[O funcionamento debuga](#)

Estes são os logs do **comando debug de uma chamada de fax** bem sucedida. Os **comandos debug** foram emitidos outra vez em um gateway de Cisco 5350, que fosse o gateway de fax do oframp neste exemplo.

```
vdt1-5350-8a# debug mta receive all
All email receive debugging is on
vdt1-5350-8a#
```

```
Mar 26 11:20:17.231: esmtp_server_work: calling ehlo
Mar 26 11:20:17.683: esmtp_server_work: calling mail
Mar 26 11:20:18.183: esmtp_server_work: calling rcpt
Mar 26 11:20:18.683: esmtp_server_work: calling data
Mar 26 11:20:19.183: (S)R: 'Received: from andyw2k ([172.18.106.183]) by
  vnt-smtp.testlab-t37.com with Microsoft SMTPSVC(5.0.2195.4453);'
```

```
Mar 26 11:20:19.187: (S)R: ' Tue, 26 Mar 2002 11:19:05 -0500'
```

```
Mar 26 11:20:19.187: (S)R: 'Message-ID: <000901c1d4e2$1d55bc60$b76a12ac@amer.cisco.com>'
```

```
Mar 26 11:20:19.187: (S)R: 'Reply-To: "Andy" <andy@testlab-t37.com>'
```

```
Mar 26 11:20:19.187: (S)R: 'From: "Andy" <andy@testlab-t37.com>'
```

```
Mar 26 11:20:19.187: (S)R: 'To: <FAX=98915510@vdt1-5350-8a.testlab-t37.com>'
```

```
Mar 26 11:20:19.187: (S)R: 'Subject: Test fax '
```

```
Mar 26 11:20:19.187: (S)R: 'Date: Tue, 26 Mar 2002 11:20:16 -0500'
```

```
Mar 26 11:20:19.187: (S)R: 'MIME-Version: 1.0'
```

```
Mar 26 11:20:19.187: (S)R: 'Content-Type: multipart/mixed;'
```

```
Mar 26 11:20:19.187: (S)R: ''
```

```
boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_
NextPart_000_0005_01C1D4B8.34737F60"
```

```
Mar 26 11:20:19.187: (S)R: 'X-Priority: 3'
```

```
Mar 26 11:20:19.187: (S)R: 'X-MSMail-Priority: Normal'
```

```
Mar 26 11:20:19.187: (S)R: 'X-Mailer: Microsoft Outlook Express 6.00.2600.0000'
```

```
Mar 26 11:20:19.187: (S)R: 'X-MimeOLE: Produced By Microsoft MimeOLE V6.00.2600.0000'
```

```
Mar 26 11:20:19.187: (S)R: 'Return-Path: andy@testlab-t37.com'
```

```
Mar 26 11:20:19.187: (S)R: 'X-OriginalArrivalTime: 26 Mar 2002 16:19:05.0120 (UTC)
  FILETIME=[F2E97200:01C1D4E1]'
```

```
Mar 26 11:20:19.187: (S)R: ''
```

```
Mar 26 11:20:19.187: esmtp_server_engine_new_part: Field name : message-id:
  Field Value : <000901c1d4e2$1d55bc60$b76a12ac@amer.cisco.com>
Field name : from: Field Value : "Andy" <andy@testlab-t37.com>
Field name : to: Field Value : <FAX=98915510@vdt1-5350-8a.testlab-t37.com>
Field name : subject: Field Value : Test fax
Field name : date: Field Value : Tue, 26 Mar 2002 11:20:16 -0500
Field name : Content-Type: Field Value : multipart/mixed;
```

```
boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_
NextPart_000_0005_01C1D4B8.34737F60"
```


vdctl-5350-8a# **debug mta receive all**

All email receive debugging is on

vdctl-5350-8a#

Mar 26 11:20:17.231: esmtp_server_work: calling ehlo

Mar 26 11:20:17.683: esmtp_server_work: calling mail

Mar 26 11:20:18.183: esmtp_server_work: calling rcpt

Mar 26 11:20:18.683: esmtp_server_work: calling data

Mar 26 11:20:19.183: (S)R: 'Received: from andyw2k ([172.18.106.183]) by vnt-smtp.testlab-t37.com with Microsoft SMTPSVC(5.0.2195.4453);'

Mar 26 11:20:19.187: (S)R: ' Tue, 26 Mar 2002 11:19:05 -0500'

Mar 26 11:20:19.187: (S)R: 'Message-ID: <000901c1d4e2\$1d55bc60\$b76a12ac@amer.cisco.com>'

Mar 26 11:20:19.187: (S)R: 'Reply-To: "Andy" <andy@testlab-t37.com>'

Mar 26 11:20:19.187: (S)R: 'From: "Andy" <andy@testlab-t37.com>'

Mar 26 11:20:19.187: (S)R: 'To: <FAX=98915510@vdctl-5350-8a.testlab-t37.com>'

Mar 26 11:20:19.187: (S)R: 'Subject: Test fax '

Mar 26 11:20:19.187: (S)R: 'Date: Tue, 26 Mar 2002 11:20:16 -0500'

Mar 26 11:20:19.187: (S)R: 'MIME-Version: 1.0'

Mar 26 11:20:19.187: (S)R: 'Content-Type: multipart/mixed;'

Mar 26 11:20:19.187: (S)R: '

boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_NextPart_000_0005_01C1D4B8.34737F60"'

Mar 26 11:20:19.187: (S)R: 'X-Priority: 3'

Mar 26 11:20:19.187: (S)R: 'X-MSMail-Priority: Normal'

Mar 26 11:20:19.187: (S)R: 'X-Mailer: Microsoft Outlook Express 6.00.2600.0000'

Mar 26 11:20:19.187: (S)R: 'X-MimeOLE: Produced By Microsoft MimeOLE V6.00.2600.0000'

Mar 26 11:20:19.187: (S)R: 'Return-Path: andy@testlab-t37.com'

Mar 26 11:20:19.187: (S)R: 'X-OriginalArrivalTime: 26 Mar 2002 16:19:05.0120 (UTC)

FILETIME=[F2E97200:01C1D4E1]'

Mar 26 11:20:19.187: (S)R: ''

Mar 26 11:20:19.187: esmtp_server_engine_new_part: Field name : message-id:

Field Value : <000901c1d4e2\$1d55bc60\$b76a12ac@amer.cisco.com>

Field name : from: Field Value : "Andy" <andy@testlab-t37.com>

Field name : to: Field Value : <FAX=98915510@vdctl-5350-8a.testlab-t37.com>

Field name : subject: Field Value : Test fax

Field name : date: Field Value : Tue, 26 Mar 2002 11:20:16 -0500

Field name : Content-Type: Field Value : multipart/mixed;

boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_NextPart_000_0005_01C1D4B8.34737F60"

vdctl-5350-8a# **debug mta receive all**

All email receive debugging is on

vdctl-5350-8a#

Mar 26 11:20:17.231: esmtp_server_work: calling ehlo

Mar 26 11:20:17.683: esmtp_server_work: calling mail

Mar 26 11:20:18.183: esmtp_server_work: calling rcpt

Mar 26 11:20:18.683: esmtp_server_work: calling data

Mar 26 11:20:19.183: (S)R: 'Received: from andyw2k ([172.18.106.183]) by vnt-smtp.testlab-t37.com with Microsoft SMTPSVC(5.0.2195.4453);'

Mar 26 11:20:19.187: (S)R: ' Tue, 26 Mar 2002 11:19:05 -0500'

Mar 26 11:20:19.187: (S)R: 'Message-ID: <000901c1d4e2\$1d55bc60\$b76a12ac@amer.cisco.com>'

Mar 26 11:20:19.187: (S)R: 'Reply-To: "Andy" <andy@testlab-t37.com>'

Mar 26 11:20:19.187: (S)R: 'From: "Andy" <andy@testlab-t37.com>'

Mar 26 11:20:19.187: (S)R: 'To: <FAX=98915510@vdctl-5350-8a.testlab-t37.com>'

Mar 26 11:20:19.187: (S)R: 'Subject: Test fax '

Mar 26 11:20:19.187: (S)R: 'Date: Tue, 26 Mar 2002 11:20:16 -0500'

Mar 26 11:20:19.187: (S)R: 'MIME-Version: 1.0'

Mar 26 11:20:19.187: (S)R: 'Content-Type: multipart/mixed;'

Mar 26 11:20:19.187: (S)R: '

boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_NextPart_000_0005_01C1D4B8.34737F60"'

Mar 26 11:20:19.187: (S)R: 'X-Priority: 3'

Mar 26 11:20:19.187: (S)R: 'X-MSMail-Priority: Normal'

Mar 26 11:20:19.187: (S)R: 'X-Mailer: Microsoft Outlook Express 6.00.2600.0000'
Mar 26 11:20:19.187: (S)R: 'X-MimeOLE: Produced By Microsoft MimeOLE V6.00.2600.0000'
Mar 26 11:20:19.187: (S)R: 'Return-Path: andy@testlab-t37.com'
Mar 26 11:20:19.187: (S)R: 'X-OriginalArrivalTime: 26 Mar 2002 16:19:05.0120 (UTC)
FILETIME=[F2E97200:01C1D4E1]'
Mar 26 11:20:19.187: (S)R: ''
Mar 26 11:20:19.187: esmtp_server_engine_new_part: Field name : message-id:
Field Value : <000901c1d4e2\$1d55bc60\$b76a12ac@amer.cisco.com>
Field name : from: Field Value : "Andy" <andy@testlab-t37.com>
Field name : to: Field Value : <FAX=98915510@vdtl-5350-8a.testlab-t37.com>
Field name : subject: Field Value : Test fax
Field name : date: Field Value : Tue, 26 Mar 2002 11:20:16 -0500
Field name : Content-Type: Field Value : multipart/mixed;

boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_
NextPart_000_0005_01C1D4B8.34737F60"

vdtl-5350-8a# **debug mta receive all**

All email receive debugging is on

vdtl-5350-8a#

Mar 26 11:20:17.231: esmtp_server_work: calling ehlo
Mar 26 11:20:17.683: esmtp_server_work: calling mail
Mar 26 11:20:18.183: esmtp_server_work: calling rcpt
Mar 26 11:20:18.683: esmtp_server_work: calling data
Mar 26 11:20:19.183: (S)R: 'Received: from andyw2k ([172.18.106.183]) by
vnt-smtp.testlab-t37.com with Microsoft SMTPSVC(5.0.2195.4453);'
Mar 26 11:20:19.187: (S)R: ' Tue, 26 Mar 2002 11:19:05 -0500'
Mar 26 11:20:19.187: (S)R: 'Message-ID: <000901c1d4e2\$1d55bc60\$b76a12ac@amer.cisco.com>'
Mar 26 11:20:19.187: (S)R: 'Reply-To: "Andy" <andy@testlab-t37.com>'
Mar 26 11:20:19.187: (S)R: 'From: "Andy" <andy@testlab-t37.com>'
Mar 26 11:20:19.187: (S)R: 'To: <FAX=98915510@vdtl-5350-8a.testlab-t37.com>'
Mar 26 11:20:19.187: (S)R: 'Subject: Test fax '
Mar 26 11:20:19.187: (S)R: 'Date: Tue, 26 Mar 2002 11:20:16 -0500'
Mar 26 11:20:19.187: (S)R: 'MIME-Version: 1.0'
Mar 26 11:20:19.187: (S)R: 'Content-Type: multipart/mixed;'
Mar 26 11:20:19.187: (S)R: ''
boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_
NextPart_000_0005_01C1D4B8.34737F60"
Mar 26 11:20:19.187: (S)R: 'X-Priority: 3'
Mar 26 11:20:19.187: (S)R: 'X-MSMail-Priority: Normal'
Mar 26 11:20:19.187: (S)R: 'X-Mailer: Microsoft Outlook Express 6.00.2600.0000'
Mar 26 11:20:19.187: (S)R: 'X-MimeOLE: Produced By Microsoft MimeOLE V6.00.2600.0000'
Mar 26 11:20:19.187: (S)R: 'Return-Path: andy@testlab-t37.com'
Mar 26 11:20:19.187: (S)R: 'X-OriginalArrivalTime: 26 Mar 2002 16:19:05.0120 (UTC)
FILETIME=[F2E97200:01C1D4E1]'
Mar 26 11:20:19.187: (S)R: ''
Mar 26 11:20:19.187: esmtp_server_engine_new_part: Field name : message-id:
Field Value : <000901c1d4e2\$1d55bc60\$b76a12ac@amer.cisco.com>
Field name : from: Field Value : "Andy" <andy@testlab-t37.com>
Field name : to: Field Value : <FAX=98915510@vdtl-5350-8a.testlab-t37.com>
Field name : subject: Field Value : Test fax
Field name : date: Field Value : Tue, 26 Mar 2002 11:20:16 -0500
Field name : Content-Type: Field Value : multipart/mixed;

boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_
NextPart_000_0005_01C1D4B8.34737F60"

vdtl-5350-8a# **debug mta receive all**

All email receive debugging is on

vdtl-5350-8a#

Mar 26 11:20:17.231: esmtp_server_work: calling ehlo
Mar 26 11:20:17.683: esmtp_server_work: calling mail
Mar 26 11:20:18.183: esmtp_server_work: calling rcpt

Mar 26 11:20:18.683: esmtp_server_work: calling data
Mar 26 11:20:19.183: (S)R: 'Received: from andyw2k ([172.18.106.183]) by
vnt-smtp.testlab-t37.com with Microsoft SMTPSVC(5.0.2195.4453);'
Mar 26 11:20:19.187: (S)R: ' Tue, 26 Mar 2002 11:19:05 -0500'
Mar 26 11:20:19.187: (S)R: 'Message-ID: <000901c1d4e2\$1d55bc60\$b76a12ac@amer.cisco.com>'
Mar 26 11:20:19.187: (S)R: 'Reply-To: "Andy" <andy@testlab-t37.com>'
Mar 26 11:20:19.187: (S)R: 'From: "Andy" <andy@testlab-t37.com>'
Mar 26 11:20:19.187: (S)R: 'To: <FAX=98915510@vdtl-5350-8a.testlab-t37.com>'
Mar 26 11:20:19.187: (S)R: 'Subject: Test fax '
Mar 26 11:20:19.187: (S)R: 'Date: Tue, 26 Mar 2002 11:20:16 -0500'
Mar 26 11:20:19.187: (S)R: 'MIME-Version: 1.0'
Mar 26 11:20:19.187: (S)R: 'Content-Type: multipart/mixed;'
Mar 26 11:20:19.187: (S)R: '
boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_
NextPart_000_0005_01C1D4B8.34737F60" '
Mar 26 11:20:19.187: (S)R: 'X-Priority: 3'
Mar 26 11:20:19.187: (S)R: 'X-MSMail-Priority: Normal'
Mar 26 11:20:19.187: (S)R: 'X-Mailer: Microsoft Outlook Express 6.00.2600.0000'
Mar 26 11:20:19.187: (S)R: 'X-MimeOLE: Produced By Microsoft MimeOLE V6.00.2600.0000'
Mar 26 11:20:19.187: (S)R: 'Return-Path: andy@testlab-t37.com'
Mar 26 11:20:19.187: (S)R: 'X-OriginalArrivalTime: 26 Mar 2002 16:19:05.0120 (UTC)
 FILETIME=[F2E97200:01C1D4E1] '
Mar 26 11:20:19.187: (S)R: ''
Mar 26 11:20:19.187: esmtp_server_engine_new_part: Field name : message-id:
Field Value : <000901c1d4e2\$1d55bc60\$b76a12ac@amer.cisco.com>
Field name : from: Field Value : "Andy" <andy@testlab-t37.com>
Field name : to: Field Value : <FAX=98915510@vdtl-5350-8a.testlab-t37.com>
Field name : subject: Field Value : Test fax
Field name : date: Field Value : Tue, 26 Mar 2002 11:20:16 -0500
Field name : Content-Type: Field Value : multipart/mixed;

boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_
NextPart_000_0005_01C1D4B8.34737F60"

vdtl-5350-8a# **debug mta receive all**

All email receive debugging is on

vdtl-5350-8a#

Mar 26 11:20:17.231: esmtp_server_work: calling ehlo
Mar 26 11:20:17.683: esmtp_server_work: calling mail
Mar 26 11:20:18.183: esmtp_server_work: calling rcpt
Mar 26 11:20:18.683: esmtp_server_work: calling data
Mar 26 11:20:19.183: (S)R: 'Received: from andyw2k ([172.18.106.183]) by
vnt-smtp.testlab-t37.com with Microsoft SMTPSVC(5.0.2195.4453);'
Mar 26 11:20:19.187: (S)R: ' Tue, 26 Mar 2002 11:19:05 -0500'
Mar 26 11:20:19.187: (S)R: 'Message-ID: <000901c1d4e2\$1d55bc60\$b76a12ac@amer.cisco.com>'
Mar 26 11:20:19.187: (S)R: 'Reply-To: "Andy" <andy@testlab-t37.com>'
Mar 26 11:20:19.187: (S)R: 'From: "Andy" <andy@testlab-t37.com>'
Mar 26 11:20:19.187: (S)R: 'To: <FAX=98915510@vdtl-5350-8a.testlab-t37.com>'
Mar 26 11:20:19.187: (S)R: 'Subject: Test fax '
Mar 26 11:20:19.187: (S)R: 'Date: Tue, 26 Mar 2002 11:20:16 -0500'
Mar 26 11:20:19.187: (S)R: 'MIME-Version: 1.0'
Mar 26 11:20:19.187: (S)R: 'Content-Type: multipart/mixed;'
Mar 26 11:20:19.187: (S)R: '
boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_
NextPart_000_0005_01C1D4B8.34737F60" '
Mar 26 11:20:19.187: (S)R: 'X-Priority: 3'
Mar 26 11:20:19.187: (S)R: 'X-MSMail-Priority: Normal'
Mar 26 11:20:19.187: (S)R: 'X-Mailer: Microsoft Outlook Express 6.00.2600.0000'
Mar 26 11:20:19.187: (S)R: 'X-MimeOLE: Produced By Microsoft MimeOLE V6.00.2600.0000'
Mar 26 11:20:19.187: (S)R: 'Return-Path: andy@testlab-t37.com'
Mar 26 11:20:19.187: (S)R: 'X-OriginalArrivalTime: 26 Mar 2002 16:19:05.0120 (UTC)
 FILETIME=[F2E97200:01C1D4E1] '
Mar 26 11:20:19.187: (S)R: ''

Mar 26 11:20:19.187: esmtp_server_engine_new_part: Field name : message-id:
Field Value : <000901c1d4e2\$1d55bc60\$b76a12ac@amer.cisco.com>
Field name : from: Field Value : "Andy" <andy@testlab-t37.com>
Field name : to: Field Value : <FAX=98915510@vdtl-5350-8a.testlab-t37.com>
Field name : subject: Field Value : Test fax
Field name : date: Field Value : Tue, 26 Mar 2002 11:20:16 -0500
Field name : Content-Type: Field Value : multipart/mixed;

boundary="/en/US/docs/net_mgmt/wan_service_administrator/1.1/administrator/guide/getstart.html=_
NextPart_000_0005_01C1D4B8.34737F60"

vdtl-5350-8a# **debug foip off-ramp**

FOIP Off ramp faxmail debugging is on

vdtl-5350-8a#

vdtl-5350-8a#

vdtl-5350-8a#

Mar 26 11:27:57.667: lapp off: CC_EV_CALL_HANDOFF, cid(0xA7)
Mar 26 11:27:57.667: loffHandoff: called number=98915510, callid=0xA7
Mar 26 11:27:57.667: loffSetupPeer: cid1(0xA7)
Mar 26 11:27:57.667: destPat(98915510),matched(1),pref(),tag(9913182),encap(1)
Mar 26 11:27:57.759: lapp off: CC_EV_CALL_PROCEEDING, cid(0xA8)
Mar 26 11:27:57.875: lapp off: CC_EV_CALL_ALERT, cid(0xA8)
Mar 26 11:28:07.487: lapp off: CC_EV_CALL_CONNECTED, cid(0xA8)
Mar 26 11:28:07.487: st=CALL_SETTING cid(0xA7,0x0,0x0,0xA8),cfid(0x0,0x0,0x0)
Mar 26 11:28:07.487: loffConnected
Mar 26 11:28:07.487: loffFlushPeerTagQueue cid(167) peer list: (empty)
Mar 26 11:28:07.487: lapp off: CC_EV_CONF_CREATE_DONE, cid(0xA8), cid2(0xA9), cfid(0x5F)
Mar 26 11:28:07.487: st=CONFERENCING3 cid(0xA7,0x0,0xA9,0xA8),cfid(0x0,0x0,0x5F)
Mar 26 11:28:07.487: loffConfDone3
Mar 26 11:28:15.419: lapp off: CC_EV_FROM_FMSP_ON_CALL_DETAIL, cid(0xA9)
Mar 26 11:28:15.419: st=WAIT_SESS_INFO cid(0xA7,0x0,0xA9,0xA8),cfid(0x0,0x0,0x5F)
Mar 26 11:28:15.419: loffSessionInfo
Mar 26 11:28:15.419: encd=1, resl=2, spd=27, min_scan_len=0, csid= andy-pc fax
Mar 26 11:28:15.419: lapp off: CC_EV_CONF_CREATE_DONE, cid(0xA9), cid2(0xAA), cfid(0x60)
Mar 26 11:28:15.419: st=CONFERENCING2 cid(0xA7,0xAA,0xA9,0xA8),cfid(0x0,0x60,0x5F)
Mar 26 11:28:15.419: loffConfDone2
Mar 26 11:28:15.419: loff_edit_cover_page: from_personal_name: 0, []
Mar 26 11:28:15.419: loff_edit_cover_page: 0, []
Mar 26 11:28:15.419: loff_edit_cover_page: [andy@testlab-t37.com]

Title: vdtl-5350-8a Offramp Cover Page

To: 98915510

From: andy@testlab-t37.com

Date: Tue, 26 Mar 2002 11:27:55 -0500

Subject: test with a word doc attachment...

Details:

Received: from andyw2k ([172.18.106.183]) by vnt-smtp.testlab-t37.com with Microsoft
SMTPSVC(5.0.2195.44 Message-ID: <001301c1d4e3\$2f020210\$b76a12ac@amer.cisco.com>

Reply-To: "Andy" <andy@testlab-t37.com>

From:

Andy" <andy@testlab-t37.com>

To: <FAX=98915510@vdtl-5350-8a.testlab-t37.com>

Subject: test with a word doc attachment...

Date: Tue, 26 Mar 2002 11:27:55 -0500

MIME-Version: 1.0

Content-Type: multipart/mixed; boundary

"-----=_NextPart_000_000F_01C1D4B9.46214BB0"

X-Priority: 3

X-MSMail-Priority: Normal
X-Mailer: Microsoft Outlook Express 6.00.2600.0000
X-MimeOLE: Produced By Microsoft MimeOLE V6.00.2600.0000
Return-Path: andy@testlab-t37.com
X-OriginalArrivalTime: 26 Mar 2002 16:26:43.0619 (UTC) FILETIME=[0432D730:01C1D4E3]

vdtl-5350-8a# **debug foip off-ramp**
FOIP Off ramp faxmail debugging is on
vdtl-5350-8a#
vdtl-5350-8a#
vdtl-5350-8a#
Mar 26 11:27:57.667: lapp off: CC_EV_CALL_HANDOFF, cid(0xA7)
Mar 26 11:27:57.667: loffHandoff: called number=98915510, callid=0xA7
Mar 26 11:27:57.667: loffSetupPeer: cid1(0xA7)
Mar 26 11:27:57.667: destPat(98915510),matched(1),pref(),tag(9913182),encap(1)
Mar 26 11:27:57.759: lapp off: CC_EV_CALL_PROCEEDING, cid(0xA8)
Mar 26 11:27:57.875: lapp off: CC_EV_CALL_ALERT, cid(0xA8)
Mar 26 11:28:07.487: lapp off: CC_EV_CALL_CONNECTED, cid(0xA8)
Mar 26 11:28:07.487: st=CALL_SETTING cid(0xA7,0x0,0x0,0xA8),cfid(0x0,0x0,0x0)
Mar 26 11:28:07.487: loffConnected
Mar 26 11:28:07.487: loffFlushPeerTagQueue cid(167) peer list: (empty)
Mar 26 11:28:07.487: lapp off: CC_EV_CONF_CREATE_DONE, cid(0xA8), cid2(0xA9), cfid(0x5F)
Mar 26 11:28:07.487: st=CONFERENCING3 cid(0xA7,0x0,0xA9,0xA8),cfid(0x0,0x0,0x5F)
Mar 26 11:28:07.487: loffConfDone3
Mar 26 11:28:15.419: lapp off: CC_EV_FROM_FMSP_ON_CALL_DETAIL, cid(0xA9)
Mar 26 11:28:15.419: st=WAIT_SESS_INFO cid(0xA7,0x0,0xA9,0xA8),cfid(0x0,0x0,0x5F)
Mar 26 11:28:15.419: loffSessionInfo
Mar 26 11:28:15.419: encd=1, resl=2, spd=27, min_scan_len=0, csid= andy-pc fax
Mar 26 11:28:15.419: lapp off: CC_EV_CONF_CREATE_DONE, cid(0xA9), cid2(0xAA), cfid(0x60)
Mar 26 11:28:15.419: st=CONFERENCING2 cid(0xA7,0xAA,0xA9,0xA8),cfid(0x0,0x60,0x5F)
Mar 26 11:28:15.419: loffConfDone2
Mar 26 11:28:15.419: loff_edit_cover_page: from_personal_name: 0, []
Mar 26 11:28:15.419: loff_edit_cover_page: 0, []
Mar 26 11:28:15.419: loff_edit_cover_page: [andy@testlab-t37.com]

Title: vdtl-5350-8a Offramp Cover Page

To: 98915510

From: andy@testlab-t37.com

Date: Tue, 26 Mar 2002 11:27:55 -0500

Subject: test with a word doc attachment...

Details:

Received: from andyw2k ([172.18.106.183]) by vnt-smtp.testlab-t37.com with Microsoft
SMTPSVC(5.0.2195.44 Message-ID: <001301c1d4e3\$2f020210\$b76a12ac@amer.cisco.com>

Reply-To: "Andy" <andy@testlab-t37.com>

From:

Andy" <andy@testlab-t37.com>

To: <FAX=98915510@vdtl-5350-8a.testlab-t37.com>

Subject: test with a word doc attachment...

Date: Tue, 26 Mar 2002 11:27:55 -0500

MIME-Version: 1.0

Content-Type: multipart/mixed; boundary

"-----_NextPart_000_000F_01C1D4B9.46214BB0"

X-Priority: 3

X-MSMail-Priority: Normal

X-Mailer: Microsoft Outlook Express 6.00.2600.0000

X-MimeOLE: Produced By Microsoft MimeOLE V6.00.2600.0000
Return-Path: andy@testlab-t37.com
X-OriginalArrivalTime: 26 Mar 2002 16:26:43.0619 (UTC) FILETIME=[0432D730:01C1D4E3]

vdtl-5350-8a# **debug fmsp send t30**
FMSP send t30 debugging is on
vdtl-5350-8a# **debug fmsp receive t30**
FMSP receive t30 debugging is on
vdtl-5350-8a#
Mar 26 11:43:29.570: t30 call4Leg=173, state=4, substate=7
Mar 26 11:43:29.570: fax2_command_receive: NO_COMMAND, T1
timer is not expired
Mar 26 11:43:33.622: t30 call4Leg=173, state=4, substate=7
Mar 26 11:43:33.622: received flag of modulation:
0
Mar 26 11:43:33.622: t30 call4Leg=173, state=4, substate=7
Mar 26 11:43:33.622: fax2_command_receive: NO_COMMAND, T1
timer is not expired
Mar 26 11:43:35.050: t30 call4Leg=173, state=4, substate=7
Mar 26 11:43:35.050: fax2_command_receive: PROCESSING
Mar 26 11:43:35.662: msg dump:FF C0 2 1E 86 66 4 C6 E B4 9E A6 36 2E 96 16 EE B6 4 4 4 4 4
Mar 26 11:43:35.662:
Mar 26 11:43:35.662: t30 call4Leg=173, state=4, substate=7
Mar 26 11:43:35.662: received: CSI remote id
string: andy-pc fax

vdtl-5350-8a# **debug fmsp send t30**
FMSP send t30 debugging is on
vdtl-5350-8a# **debug fmsp receive t30**
FMSP receive t30 debugging is on
vdtl-5350-8a#
Mar 26 11:43:29.570: t30 call4Leg=173, state=4, substate=7
Mar 26 11:43:29.570: fax2_command_receive: NO_COMMAND, T1
timer is not expired
Mar 26 11:43:33.622: t30 call4Leg=173, state=4, substate=7
Mar 26 11:43:33.622: received flag of modulation:
0
Mar 26 11:43:33.622: t30 call4Leg=173, state=4, substate=7
Mar 26 11:43:33.622: fax2_command_receive: NO_COMMAND, T1
timer is not expired
Mar 26 11:43:35.050: t30 call4Leg=173, state=4, substate=7
Mar 26 11:43:35.050: fax2_command_receive: PROCESSING
Mar 26 11:43:35.662: msg dump:FF C0 2 1E 86 66 4 C6 E B4 9E A6 36 2E 96 16 EE B6 4 4 4 4 4
Mar 26 11:43:35.662:
Mar 26 11:43:35.662: t30 call4Leg=173, state=4, substate=7
Mar 26 11:43:35.662: received: CSI remote id
string: andy-pc fax

[Informações Relacionadas](#)

- [OnRamp faxing de T.37](#)
- [Fax de T.37 do FAX over IP store and forward \(guarda e passa adiante\)](#)
- [Suporte ao Produto de Voz e Comunicações Unificadas](#)
- [Troubleshooting da Telefonia IP Cisco](#)
- [Suporte Técnico - Cisco Systems](#)