

Referência rápida consolidada acesso convergida para moldes do Wireless LAN

Índice

[Introdução](#)

[Pré-requisitos](#)

[Requisitos](#)

[Componentes Utilizados](#)

[Segurança da camada 2](#)

[ABRA o WLAN nenhuma Segurança](#)

[Wired Equivalent Privacy \(WEP\) estático](#)

[Filtro MAC - Base de dados local](#)

[Filtro MAC - Raio externo](#)

[Chave pré-compartilhada protegida Sem fio do acesso 2 \(WPA2\) \(PSK\)](#)

[autenticação local do Extensible Authentication Protocol \(EAP\) do 802.1x \(NGWC usado como o RAIO local\)](#)

[802.1x no raio externo](#)

[Segurança da camada 3](#)

[Transmissão da Web](#)

[Autenticação local da autenticação da Web](#)

[Autenticação da Web com autenticação RADIUS externo \(ISE\)](#)

[Autenticação do web externa](#)

[Autenticação da Web personalizada com autenticação local](#)

[Auto autenticação da Web da âncora](#)

Introdução

Este documento fornece moldes da configuração de CLI de referência rápida para configurações básicas e conhecidas do Wireless LAN da camada 2 e da camada 3 (WLAN). Os moldes baixos são fornecidos para uma cópia e uma pasta rápidas no armário de fiação da próxima geração de Cisco instalações inicial do cliente (NGWC) 5760 e 3850 recreações do laboratório do controlador do Wireless LAN (WLC) e.

Pré-requisitos

Requisitos

Cisco recomenda que você tem o conhecimento a liberação de 3.3 NGWC ou de mais atrasado.

Espera-se que as interfaces virtuais do interruptor (SVI) e os conjuntos de DHCP/espião preconfigured por melhores prática.

Componentes Utilizados

Este documento não se restringe a versões de software e hardware específicas.

As informações neste documento foram criadas a partir de dispositivos em um ambiente de laboratório específico. Todos os dispositivos utilizados neste documento foram iniciados com uma configuração (padrão) inicial. Se a sua rede estiver ativa, certifique-se de que entende o impacto potencial de qualquer comando.

Segurança da camada 2

ABRA o WLAN nenhuma Segurança

```
wlan 1 name testwlan ssid testwlan
  client vlan 20
  no security wpa
  no shut
```

Wired Equivalent Privacy (WEP) estático

```
wlan staticWEP 6 staticWEP
  client vlan 79
  no security wpa
  no security wpa akm dot1x
  no security wpa wpa2
  no security wpa wpa2 ciphers aes
  security static-wep-key encryption 40 ascii 0 Cisco 1
  session-timeout 1800
  no shutdown
```

Filtro MAC - Base de dados local

```
username 24770319eB75 mac
```

```
aaa new-model
aaa authorization network test_mac local
```

```
wlan macfiltering 6 macfiltering
  client vlan Vlan7
  mac-filtering test_mac
  no security wpa
  no security wpa akm dot1x
  no security wpa wpa2
  no security wpa wpa2 ciphers aes
  no shutdown
```

Filtro MAC - Raio externo

```
aaa new-model
aaa group server radius wcm_rad

server name RAD_EXT
subscriber mac-filtering security-mode mac
mac-delimiter colon

radius server RAD_EXT
address ipv4 x.x.x.x auth-port 1812 acct-port 1813
key cisco

aaa authorization network wcm_macfilter group wcm_rad

wlan macfiltering 1 macfiltering
client vlan Vlan7
mac-filtering wcm_macfilter
no security wpa
no security wpa akm dot1x
no security wpa wpa2
no security wpa wpa2 ciphers aes
no shutdown
```

Chave pré-compartilhada protegida Sem fio do acesso 2 (WPA2) (PSK)

```
wlan wpa2psk 1 wpa2psk
client vlan 20
no security wpa akm dot1x
security wpa akm psk set-key ascii 0 Cisco123
no shutdown
```

autenticação local do Extensible Authentication Protocol (EAP) do 802.1x (NGWC usado como o RAIO local)

```
user-name test
privilege 15
password 0 cisco
type network-user description pass=cisco
aaa new-model
aaa authentication dot1x default local
aaa authorization credential-download author_list local
aaa authentication dot1x authen_list local
aaa local authentication authen_list authorization author_list
dot1x system-auth-control
eap profile PEAPProfile
method ?
fast      EAP-FAST method allowed
gtc       EAP-GTC method allowed
leap      EAP-LEAP method allowed
md5       EAP-MD5 method allowed
mschapv2  EAP-MSCHAPV2 method allowed
peap      EAP-PEAP method allowed
tls       EAP-TLS method allowed

method peap
method mschapv2
```

```
wlan TestNGWC 1 TestNGWC
  client vlan VLAN0080
  ip dhcp server 192.168.80.14
  local-auth PEAPProfile
```

802.1x no raio externo

```
user-name test
  privilege 15
  password 0 cisco
  type network-user description pass=cisco
aaa new-model
aaa authentication dot1x default local
aaa authorization credential-download author_list local
aaa authentication dot1x authen_list local
aaa local authentication authen_list authorization author_list
dot1x system-auth-control
eap profile PEAPProfile
method ?
  fast      EAP-FAST method allowed
  gtc       EAP-GTC method allowed
  leap      EAP-LEAP method allowed
  md5       EAP-MD5 method allowed
  mschapv2  EAP-MSCHAPV2 method allowed
  peap      EAP-PEAP method allowed
  tls       EAP-TLS method allowed
```

```
method peap
method mschapv2
wlan TestNGWC 1 TestNGWC
  client vlan VLAN0080
  ip dhcp server 192.168.80.14
  local-auth PEAPProfile
```

Segurança da camada 3

Transmissão da Web

```
user-name test
  privilege 15
  password 0 cisco
  type network-user description pass=cisco
aaa new-model
aaa authentication dot1x default local
aaa authorization credential-download author_list local
aaa authentication dot1x authen_list local
aaa local authentication authen_list authorization author_list
dot1x system-auth-control
eap profile PEAPProfile
method ?
  fast      EAP-FAST method allowed
  gtc       EAP-GTC method allowed
  leap      EAP-LEAP method allowed
  md5       EAP-MD5 method allowed
  mschapv2  EAP-MSCHAPV2 method allowed
  peap      EAP-PEAP method allowed
```

```
tls          EAP-TLS method allowed

method peap
method mschapv2
wlan TestNGWC 1 TestNGWC
client vlan VLAN0080
ip dhcp server 192.168.80.14
local-auth PEAPProfile
```

Autenticação local da autenticação da Web

```
user-name test
  privilege 15
  password 0 cisco
  type network-user description pass=cisco
aaa new-model
aaa authentication dot1x default local
aaa authorization credential-download author_list local
aaa authentication dot1x authen_list local
aaa local authentication authen_list authorization author_list
dot1x system-auth-control
eap profile PEAPProfile
method ?
  fast      EAP-FAST method allowed
  gtc       EAP-GTC method allowed
  leap      EAP-LEAP method allowed
  md5       EAP-MD5 method allowed
  mschapv2  EAP-MSCHAPV2 method allowed
  peap      EAP-PEAP method allowed
  tls       EAP-TLS method allowed
```

```
method peap
method mschapv2
wlan TestNGWC 1 TestNGWC
client vlan VLAN0080
ip dhcp server 192.168.80.14
local-auth PEAPProfile
```

Autenticação da Web com autenticação RADIUS externo (ISE)

```
user-name test
  privilege 15
  password 0 cisco
  type network-user description pass=cisco
aaa new-model
aaa authentication dot1x default local
aaa authorization credential-download author_list local
aaa authentication dot1x authen_list local
aaa local authentication authen_list authorization author_list
dot1x system-auth-control
eap profile PEAPProfile
method ?
  fast      EAP-FAST method allowed
  gtc       EAP-GTC method allowed
  leap      EAP-LEAP method allowed
  md5       EAP-MD5 method allowed
  mschapv2  EAP-MSCHAPV2 method allowed
  peap      EAP-PEAP method allowed
  tls       EAP-TLS method allowed
```

```
method peap
method mschapv2
wlan TestNGWC 1 TestNGWC
client vlan VLAN0080
ip dhcp server 192.168.80.14
local-auth PEAPProfile
```

Autenticação do web externa

```
user-name test
  privilege 15
  password 0 cisco
  type network-user description pass=cisco
aaa new-model
aaa authentication dot1x default local
aaa authorization credential-download author_list local
aaa authentication dot1x authen_list local
aaa local authentication authen_list authorization author_list
dot1x system-auth-control
eap profile PEAPProfile
method ?
  fast      EAP-FAST method allowed
  gtc       EAP-GTC method allowed
  leap      EAP-LEAP method allowed
  md5       EAP-MD5 method allowed
  mschapv2  EAP-MSCHAPV2 method allowed
  peap      EAP-PEAP method allowed
  tls       EAP-TLS method allowed
```

```
method peap
method mschapv2
wlan TestNGWC 1 TestNGWC
client vlan VLAN0080
ip dhcp server 192.168.80.14
local-auth PEAPProfile
```

Autenticação da Web personalizada com autenticação local

```
ip http server
ip device tracking
```

```
aaa new-model
aaa authentication login local_webauth local
aaa authorization network default local
aaa authorization credential-download default local
```

```
username <username> password 0 <password>
```

FTP Configuration for file transfer:

```
ip ftp username <username>
ip ftp password <password>
```

Upload custom html files to flash: with command:

```
5760# copy ftp://x.x.x.x/webauth_login.html flash:
```

Example of flash content:

w-5760-2#dir flash:

Directory of flash:/

```
64649  -rw-      1164   Oct 7 2013 04:36:23 +00:00  webauth_failure.html
64654  -rw-      2047   Oct 7 2013 13:32:38 +00:00  webauth_login.html
64655  -rw-      1208   Oct 7 2013 04:34:12 +00:00  webauth_success.html
64656  -rw-       900   Oct 7 2013 04:35:00 +00:00  webauth_expired.html
64657  -rw-     96894   Oct 7 2013 05:05:09 +00:00  web_auth_logo.png
64658  -rw-     23037   Oct 7 2013 13:17:58 +00:00  web_auth_cisco.png
64660  -rw-      2586   Oct 7 2013 13:31:27 +00:00  web_auth_aup.html
```

```
parameter-map type webauth global
virtual-ip ipv4 1.1.1.1
```

```
parameter-map type webauth custom
type webauth
redirect on-success http://www.cisco.com
banner text ^C CC global ip for redirect ^C
custom-page login device flash:webauth_login.html
custom-page success device flash:webauth_success.html
custom-page failure device flash:webauth_failure.html
custom-page login expired device flash:webauth_expired.html
```

```
wlan cisco 1 cisco
client vlan Vlanx
no security wpa
no security wpa akm dot1x
no security wpa wpa2
no security wpa wpa2 ciphers aes
security web-auth
security web-auth authentication-list local_webauth
security web-auth parameter-map custom
session-timeout 1800
no shutdown
```

Auto autenticação da Web da âncora

```
//Verify//
```

```
show wireless mobility summary
```

```
<snip>
```

IP	Public IP	Group Name	Multicast IP	Link Status
192.168.100.8	-	ngwc	0.0.0.0	UP : UP
192.168.100.15	192.168.100.15	5760		UP : UP

```
radius server ise
address ipv4 192.168.154.119 auth-port 1812 acct-port 1813
key Cisco123
aaa group server radius rad_ise
server name ise
```

```
aaa authentication login ext_ise group rad_ise
parameter-map webauth global
virtual-ip ipv4 1.1.1.1
parameter-map type webauth test_web
type webauth
```

banner

WLAN configs on the Foreign 5760

```
wlan ngwc_guest 3 ngwc_guest
client vlan 254
mobility anchor 192.168.100.8 //Anchor
no security wpa
no security wpa akm dot1x
no security wpa wpa2
no security wpa wpa2 ciphers aes
security web-auth
security web-auth authentication-list wcm_local
security web-auth parameter-map test_web
no shutdown
```

WLAN configs on the Anchor 5760

```
wlan ngwc_guest 3 ngwc_guest
client vlan 254
mobility anchor 192.168.100.8 //Local
no security wpa
no security wpa akm dot1x
no security wpa wpa2
no security wpa wpa2 ciphers aes
security web-auth
security web-auth authentication-list rad_ise
security web-auth parameter-map test_web
no shutdown
```