

Содержание

Вопрос:

ESA может отправить трафик SMTP другому номеру порта кроме 25?

Порт 25 является стандартным использованием серверов Mail Exchange порта SMTP для прислушиваний к сообщениям входящей электронной почты. ESA может быть настроен для отправки почты определенному хосту по альтернативному порту. `smtproutes` команда в CLI является самым простым способом настроить это:

```
mail3.example.com> smtproutes
```

```
There are no routes configured.
```

```
Choose the operation you want to perform:
```

- NEW - Create a new route.
- IMPORT - Import new routes from a file.

```
[ ]> new
```

```
Enter the hostname for which you want to set up a permanent route.
```

```
Partial hostnames such as ".example.com" are allowed.
```

```
Use "ALL" for the default route.
```

```
[ ]> testexchange.example.com
```

```
Enter the destination hosts, separated by commas, which you want mail for  
testexchange.ironport.com to be delivered.
```

```
Enter /dev/null by itself if you wish to discard the mail.
```

```
[ ]> exchange.example.com:1025
```

```
Mapping for testexchange.ironport.com to exchange.example.com:1025 created.
```

```
There are currently 1 routes configured.
```

```
Choose the operation you want to perform:
```

- NEW - Create a new route.
- DELETE - Remove a route.
- PRINT - Display all routes.
- IMPORT - Import new routes from a file.
- EXPORT - Export all routes to a file.
- CLEAR - Remove all routes.

```
[ ]>
```

```
> commit
```

```
Please enter some comments describing your changes:
```

```
[ ]> testing the new exchange server on an alternate port
```

```
Changes committed: Mon Mar 28 14:20:06 2005 PST
```

```
mail3.example.com>
```

В этом случае система настроена для передачи почты за `testexchange. пример. com` для обмена. `пример. com` по порту 1025.

Можно также внести вышеупомянутые изменения через GUI, Сеть->, Маршрут SMTP-> Добавляет Маршрут SMTP и заполняет домен и адресат с требуемым портом. Необходимо отправить и передать изменения, однажды сделанные.

Для настройки ESA для отправки почты определенному хосту по альтернативному порту с помощью GUI устройства выберите Network> IP Interface и модифицируйте параметры настройки IP - интерфейса.