

无法打开RabbitMQ用户界面

目录

[简介](#)

[先决条件](#)

[要求](#)

[使用的组件](#)

[问题](#)

[解决方案](#)

[验证](#)

简介

本文描述如何解决问题，当您连接对RabbitMQ用户界面时(UI)。

先决条件

要求

本文档没有任何特定的要求。

使用的组件

本文档中的信息根据4.7.X和4.8.X。

本文档中的信息都是基于特定实验室环境中的设备编写的。本文档中使用的所有设备最初均采用原始（默认）配置。如果您使用的是真实网络，请确保您已经了解所有命令的潜在影响。

问题

当您设法连接到http://IP_address_of_AMQP:15672通过您的浏览器时，您接收“拒绝的连接”错误。

并且在RabbitMQ控制台，这是您看到：

```
[root@amqp ~]# rabbitmqctl status
Status of node rabbit@amqp ...
Error: unable to connect to node rabbit@amqp: nodedown
```

```
DIAGNOSTICS
=====
```

```
attempted to contact: [rabbit@amqp]
```

```
rabbit@amqp:
* connected to epmd (port 4369) on amqp
* epmd reports: node 'rabbit' not running at all
                no other nodes on amqp
```

* suggestion: start the node

current node details:

```
- node name: 'rabbitmq-cli-3496@amqp'  
- home dir: /var/lib/rabbitmq  
- cookie hash: gsXBP8HgENjwAKcRmvMU6A==
```

解决方案

1.重新配置虚拟机的(VM)主机名。

- 更新/etc/hosts和/etc/hostname与新的主机名。 请勿利用在新的主机名的破折号。

2. 重新安装兔子：

```
rm /etc/cliqr_modules.conf  
yum remove -y wxGTK-g1-2.8.12-20.e17.x86_64
```

- 下载core_installer.bin：

```
chmod +x core+installer.bin  
./core_installer.bin <os> <platform> rabbit  
java -jar cco-installer.jar conn_broker-response.xml
```

- 重新启动VM。

3. 防火墙的开放端口15672：

```
iptables -I INPUT 1 -p tcp --dport 15672 -j ACCEPT  
service iptables save  
service iptables restart
```

验证

预期的输出是：

```
# netstat -atun | grep 15672  
tcp        0      0 0.0.0.0:15672          0.0.0.0:*              LISTEN
```

从另一个VM，请利用此命令确认连接：

```
telnet IP_address_of_AMQP 15672# rabbitmqctl status  
]Status of node rabbit@haamqp2 ...  
[{pid,1759},  
{running_applications,  
  [{rabbitmq_management,"RabbitMQ Management Console","3.5.1"},  
   {rabbitmq_web_dispatch,"RabbitMQ Web Dispatcher","3.5.1"},  
   {webmachine,"webmachine","1.10.3-rmq3.5.1-gite9359c7"},  
   {mochiweb,"MochiMedia Web Server","2.7.0-rmq3.5.1-git680dba8"},  
   {rabbitmq_management_agent,"RabbitMQ Management Agent","3.5.1"},  
   {rabbit,"RabbitMQ","3.5.1"},  
   {ssl,"Erlang/OTP SSL application","6.0"},  
   {public_key,"Public key infrastructure","0.23"},  
   {crypto,"CRYPTO","3.5"},  
   {asn1,"The Erlang ASN1 compiler version 3.0.4","3.0.4"},  
   {os_mon,"CPO  CXC 138 46","2.3.1"},  
   {inets,"INETS  CXC 138 49","5.10.6"},  
   {amqp_client,"RabbitMQ AMQP Client","3.5.1"},  
   {xmerl,"XML parser","1.3.7"},  
   {mnesia,"MNESIA  CXC 138 12","4.12.5"},  
   {sasl,"SASL  CXC 138 11","2.4.1"},  
   {stdlib,"ERTS  CXC 138 10","2.4"},  
   {kernel,"ERTS  CXC 138 10","3.2"}]},  
{os,{unix,linux}},
```

```
{erlang_version,  
  "Erlang/OTP 17 [erts-6.4] [source-2e19e2f] [64-bit] [async-threads:30] [hipe] [kernel-  
poll:true]\n"},  
{memory,  
  [{total,46019504},  
   {connection_readers,97704},  
   {connection_writers,19384},  
   {connection_channels,67928},  
   {connection_other,173656},  
   {queue_procs,165136},  
   {queue_slave_procs,0},  
   {plugins,501128},  
   {other_proc,13684160},  
   {mnesia,87752},  
   {mgmt_db,829016},  
   {msg_index,55056},  
   {other_ets,1144976},  
   {binary,1948544},  
   {code,22194354},  
   {atom,801697},  
   {other_system,4249013}}],  
{alarms,[]},  
{listeners,[[{clustering,25672,"::"},{amqp,5672,"::"},{'amqp/ssl',5671,"::"}]}],  
{vm_memory_high_watermark,0.4},  
{vm_memory_limit,771738828},  
{disk_free_limit,50000000},  
{disk_free,6418993152},  
{file_descriptors,  
  [{total_limit,3996},  
   {total_used,10},  
   {sockets_limit,3594},  
   {sockets_used,6}]},  
{processes,[[{limit,1048576},{used,267}]}],  
{run_queue,0},  
{uptime,1622687}]
```

现在您应该能打开浏览器到http://IP_address_of_AMQP:15672和启动RabbitMQ GUI。默认登录是 **cliqr/cliqr**。