

IM和在线状态和Jabber支持目录URI的

目录

[简介](#)

[问题](#)

[解决方案](#)

简介

此条款描述与Jabber如何的现期杂志与在Cisco Unified Communications Manager IM和在线状态的期待已久的目录统一资源识别符(URI)功能一起使用。

问题

目前，在线状态版本10.5.1支持目录URI;不是所有的客户端支持此功能。参考IM和在线状态服务网络设置文档的[IM地址配置要求](#)部分关于目录URI支持的更多信息。

Directory URI IM Address Interactions and Restrictions

To support multiple domain configurations, you must set Directory URI as the IM address scheme for IM and Presence Service.



Caution If you configure the node to use Directory URI as the IM address scheme, Cisco recommends that you deploy only clients that support Directory URI. Any client that does not support Directory URI will not work if the Directory URI IM address scheme is enabled. Cisco recommends that you use the `UserID@Default_Domain` IM address scheme and not the Directory URI IM address scheme if you have any deployed clients that do not support Directory URI.

Observe the following restrictions and interactions when using the Directory URI IM address scheme:

- All users have a valid Directory URI value configured on Cisco Unified Communications Manager.
- All deployed clients must support Directory URI as the IM address and use EDI-based directory integration.
- UDS-based directory integration is not supported.
- The IM address scheme must be consistent across all IM and Presence Service clusters.
- All clusters must be running a version of Cisco Unified Communications Manager that supports the Directory URI addressing scheme.
- If LDAP Sync is disabled, you can set the Directory URI as a free-form URI. If LDAP Directory Sync is enabled, you can map the Directory URI to the email address (mailid) or the Microsoft OCS/Lync SIP URI (msRTC/SIP-PrimaryUserAddress).
- The Directory URI IM address settings are global and apply to all users in the cluster. You cannot set a different Directory URI IM address for individual users in the cluster.


此摘要导致多数相信Windows客户端的思科的Jabber支持此功能。然而，当前没有Jabber客户端发布目录URI的提供支持。要更加特定，Jabber版本10.5.x和以下不支持目录URI。很可能，Jabber版本10.6也许准备支持目录URI，但是那此时不肯定。


解决方案

因为Jabber不支持目录URI，您应该配置IM和在线状态UserID@的[[Default Domain]。为了配置此，请导航对Presence Server Admin网页，去[在线状态>Advanced在线状态设置](#)，并且选择UserID@ [Default Domain] IM地址方案下拉菜单。

Advanced Presence Settings

Status

 Status: Ready

 Domain and IM Address

Domain and IM Address Settings

Default Domain or IM Address Scheme cannot be changed until the following services are stopped on all nodes :

- Cisco Presence Engine
- Cisco SIP Proxy
- Cisco XCP Router
- Cisco Sync Agent
- Cisco Client Profile Agent

Please ensure High Availability is disabled before stopping these services. **Only one setting below may be changed at a time.**

Do not change Default Domain or IM Address scheme

Default Domain*

joshLab.net

The Default Domain is only used when the IM Address Scheme is "UserID@[Default Domain]"

IM Address Scheme*

UserID@[Default Domain]
UserID@[Default Domain]
Directory URI

Save