

NGWC 5760和3850 WLC本地EAP验证配置示例

目录

[简介](#)

[先决条件](#)

[要求](#)

[使用的组件](#)

[背景信息](#)

[配置](#)

[网络图](#)

[配置](#)

[验证](#)

[故障排除](#)

[启用无线客户端问题的跟踪](#)

[dot1x和EAP的调试](#)

[示例调试](#)

简介

本文描述用于的逐步进程为了配置思科新一代无线控制器(NGWC) 5760个和3850个无线局域网控制器(WLCs)无线网络用户的本地可扩展的认证协议(EAP)验证的。在本文的认证方法是PEAP-MSChapv2，是其中一个最普通的方法可用在恳求者。

先决条件

要求

思科建议您符合这些要求，在您尝试此配置前：

- 有WLC和轻量级接入点(拉普)的基础知识。本文不包括5760和3850 WLCs的启动配置。关于此 particular任务的更多信息，请访问[开始与在支持论坛的WLC 5760和3850](#)。
- 有验证、授权和统计(AAA)服务器的一功能知识。
- 有无线网络和无线安全安全性问题一详尽的知识。
- 本文假设，无线接入点已经加入WLC 5760并且/或者3850。
- 本文假设，请求方为使用的认证方法适当地配置。

使用的组件

本文档中的信息基于以下软件和硬件版本：

- 为了受益于在5760和3850的GUI，并且运行多数最近代码，保证您使用代码03.02.02.SE.150-1.EX2以上。(这是有效在六月25，2013。)
- 用于本文的接入点(AP)是AP1142N。
- 用于本文的请求方是Microsoft (MS) Windows 7企业，与无线卡TP链路n600双波段USB适配器和Cisco Anyconnect版本3.1。

本文档中的信息都是基于特定实验室环境中的设备编写的。本文档中使用的所有设备最初均采用原始(默认)配置。如果您使用的是真实网络，请确保您已经了解所有命令的潜在影响。

背景信息


本地EAP是在控制器允许用户和无线客户端验证本地的认证方法。当您启用本地EAP时，控制器担当身份验证服务器和本地用户数据库，因此它无需依赖于外部身份验证服务器。本地EAP从本地用户数据库获取用户凭证。

输入此CLI命令为了查看本地EAP为在控制器和无线客户端之间的验证支持的方法：

```
3850-1(config-eap-profile)#method ? fast      EAP-FAST method allowed
gtc      EAP-GTC method allowed
leap     EAP-LEAP method allowed
md5      EAP-MD5 method allowed
mschapv2 EAP-MSCHAPV2 method allowed
peap     EAP-PEAP method allowed
tls      EAP-TLS method allowed
```

配置

网络图



配置

完成这些步骤为了配置本地EAP验证：


1. 输入此CLI命令为了创建测试用户：

```
user-name test
  privilege 15
  password 0 cisco
  type network-user description pass=cisco
```

2. 输入此CLI命令为了启用AAA：

```
aaa new-model
```

3. 定义AAA的认证和授权：



输入此命令到CLI为了使EAP会话本地终止。

```
aaa authentication dot1x default local
```

输入此CLI命令为了准备证件下载的一张方法列表：

Note:在本例中，本地方法列表`author_list`配置。此方法列表名称是其中一个CLI命令`aaa本地认证authen_list授权的author_list`的参数。

```
aaa authorization credential-download author_list local
```

输入此CLI命令为了定义验证方法列表，本地EAP使用凭证的验证，当EAP请求与EAP_VERIFY_PASSWORD_EVENT事件时的本地EAP：

Note:此方法列表名称是CLI命令`aaa本地认证authen_list授权的author_list`的参数。

```
aaa authentication dot1x authen_list local
```

输入此CLI命令为了指定本地EAP必须下载/验证凭证的地方：

Note:在这发生前，您必须定义`authen_list`和`author_list`;关于如何的参考的步骤2和3定义方法列

表的更多信息。

```
aaa local authentication authen_list authorization author_list
```

4. 输入此CLI命令为了开始dot1x进程：

```
dot1x system-auth-control
```

5. 创建Eap profile为了定义支持的认证方法。在本例中，PEAP-MSchapv2允许：

```
eap profile PEAPProfile
method peap
method mschapv2
```

6. 配置服务集标识(SSID)为了使用该的Eap profile您创建：

```
wlan TiagoNGWC 1 TiagoNGWC
```

```
client vlan VLAN0080
ip dhcp server 192.168.80.14
local-auth PEAPProfile
```

7. 设置DHCP池和Switch Virtual Interface (SVI)客户端的VLAN。在本例中，这直接地在与使用的NGWC完成VLAN80：

```
ip dhcp excluded-address 192.168.80.1 192.168.80.99
!
ip dhcp pool VLAN80
network 192.168.80.0 255.255.255.0
default-router 192.168.80.14

interface Vlan80
ip address 192.168.80.14 255.255.255.0
```

验证

请使用此部分为了验证您的配置适当地工作。

```
3850-1#show wlan name TiagoNGWC
WLAN Profile Name      : TiagoNGWC
=====
Identifier              : 1
Network Name (SSID)    : TiagoNGWC
Status                  : Enabled
Broadcast SSID         : Enabled
Maximum number of Associated Clients : 0
AAA Policy Override    : Disabled
Network Admission Control
  NAC-State             : Disabled
Number of Active Clients : 1
Exclusionlist Timeout  : 60
Session Timeout       : 1800 seconds
CHD per WLAN          : Enabled
Webauth DHCP exclusion : Disabled
Interface              : VLAN0080
```

```

Interface Status                : Up
Multicast Interface             : Unconfigured
WLAN IPv4 ACL                   : unconfigured
WLAN IPv6 ACL                   : unconfigured
DHCP Server                     : 192.168.80.14
DHCP Address Assignment Required : Disabled
DHCP Option 82                  : Disabled
DHCP Option 82 Format           : ap-mac
DHCP Option 82 Ascii Mode      : Disabled
DHCP Option 82 Rid Mode        : Disabled
QoS Service Policy - Input
  Policy Name                    : unknown
  Policy State                    : None
QoS Service Policy - Output
  Policy Name                    : unknown
  Policy State                    : None
QoS Client Service Policy
  Input Policy Name              : unknown
  Output Policy Name             : unknown
WMM                              : Allowed
Channel Scan Defer Priority:
  Priority (default)             : 4
  Priority (default)             : 5
  Priority (default)             : 6
Scan Defer Time (msecs)         : 100
Media Stream Multicast-direct   : Disabled
CCX - AironetIe Support         : Enabled
CCX - Gratuitous ProbeResponse (GPR) : Disabled
CCX - Diagnostics Channel Capability : Disabled
Dot11-Phone Mode (7920)        : Invalid
Wired Protocol                  : None
Peer-to-Peer Blocking Action    : Disabled
Radio Policy                     : All
DTIM period for 802.11a radio   : 1
DTIM period for 802.11b radio   : 1
Local EAP Authentication        : PEAPProfile
Mac Filter Authorization list name : Disabled
Accounting list name            : Disabled
802.1x authentication list name : Disabled
Security
  802.11 Authentication         : Open System
  Static WEP Keys               : Disabled
  802.1X                        : Disabled
  Wi-Fi Protected Access (WPA/WPA2) : Enabled
    WPA (SSN IE)                : Disabled
    WPA2 (RSN IE)               : Enabled
    TKIP Cipher                  : Disabled
    AES Cipher                   : Enabled
  Auth Key Management
    802.1x                      : Enabled
    PSK                          : Disabled
    CCKM                        : Disabled
  CKIP                          : Disabled
  IP Security                    : Disabled
  IP Security Passthru           : Disabled
  L2TP                          : Disabled
  Web Based Authentication       : Disabled
  Conditional Web Redirect       : Disabled
  Splash-Page Web Redirect       : Disabled
  Auto Anchor                    : Disabled
  Sticky Anchoring              : Enabled
  Cranite Passthru              : Disabled
  Fortress Passthru             : Disabled
  PPTP                          : Disabled

```

```
Infrastructure MFP protection      : Enabled
Client MFP                        : Optional
Webauth On-mac-filter Failure    : Disabled
Webauth Authentication List Name : Disabled
Webauth Parameter Map           : Disabled
Tkip MIC Countermeasure Hold-down Timer : 60
Call Snooping                    : Disabled
Passive Client                   : Disabled
Non Cisco WGB                    : Disabled
Band Select                      : Disabled
Load Balancing                   : Disabled
IP Source Guard                  : Disabled
```

```
3850-1#show wireless client mac-address 6470.0227.0a89 detail
```

```
Client MAC Address : 6470.0227.0a89
Client Username   : tiago
AP MAC Address    : 64d8.146f.e5a0
AP Name: APd48c.b52f.4a1e
Client State     : Associated
Wireless LAN Id  : 1
Wireless LAN Name: TiagoNGWC
BSSID : 64d8.146f.e5a0
Connected For   : 323 secs
Protocol : 802.11n - 2.4 GHz
Channel : 6
IPv4 Address   : 192.168.80.100
IPv6 Address   : Unknown
Association Id  : 1
Authentication Algorithm : Open System
...
Policy Manager State : RUN
Policy Manager Rule Created : Yes
NPU Fast Fast Notified : Yes
Last Policy Manager State : RUN
Client Entry Create Time : 153207 seconds
Policy Type : WPA2
Authentication Key Management : 802.1x
Encryption Cipher : CCMP (AES)
Management Frame Protection : No
EAP Type : PEAP
Interface : VLAN0080
VLAN : 80
Quarantine VLAN : 0
Access VLAN : 80
...
```

[故障排除](#)

请使用此部分为了排除故障您的配置。

启用无线客户端问题的跟踪

输入这些CLI命令为了为无线客户端问题跟踪：

```
set trace group-wireless-client level debug
debug client mac <MAC>
```

输入此CLI命令为了过滤在特定MAC地址：

```
set trace group-wireless-client filter mac <MAC>
```

输入此CLI命令为了查看未过滤的输出：

```
show trace messages group-wireless-client
```

输入此CLI命令为了查看已过滤输出：

```
show trace sys-filtered-traces
```

输入此CLI命令为了查看设置：

```
show trace all-buffer settings
```

您也许需要查看其他跟踪，从属问题是否是Cisco IOS或FED。如果遇到问题，当您尝试检索IP地址时，请启用debug ip设备跟踪。

dot1x和EAP的调试

这是用于dot1x和EAP配置的调试指令：

```
debug aaa wireless all
debug dot1x all
debug eap all
```

示例调试

这是一些示例debug命令outputs：

```
3850-1#
*Sep 19 07:00:21.423: 6470.0227.0A89 Association received from mobile on AP
 64D8.146F.E5A0 1 wcm: cct Msg Sent at 1379573926 se
*Sep 19 07:00:21.423: 6470.0227.0A89 qos upstream policy is unknown and
downstreampolicy is unknown 1 wcm: Sent at 1379573926 se
*Sep 19 07:00:21.423: 6470.0227.0A89 apChanged 0 wlanChanged 0 mscb ipAddr
192.168.80.100, apf RadiusOverride 0x0, numIPv6Addr=0 1 wcm: = 0^M
*Sep 19 07:00:21.423: 6470.0227.0A89 Applying WLAN policy on MSCB. 1 wcm:
ipAddr 192.168.80.100, apf RadiusOverride 0x0, numIPv6Addr=0
*Sep 19 07:00:21.424: 6470.0227.0A89 Applying WLAN ACL policies to client 1
wcm: 192.168.80.100, apf RadiusOverride 0x0, numIPv6Addr=0
*Sep 19 07:00:21.424: 6470.0227.0A89 No Interface ACL used for Wireless
client in WCM(NGWC) 1 wcm: pf RadiusOverride 0x0, numIPv6Addr=0
*Sep 19 07:00:21.424: 6470.0227.0A89 Applying site-specific IPv6 override for
station 6470.0227.0A89 - vapId 1, site 'default-group', interface
'VLAN0080' 1 wcm:
*Sep 19 07:00:21.424: 6470.0227.0A89 Applying local bridging Interface Policy
for station 6470.0227.0A89 - vlan 80, interface 'VLAN0080' 1 wcm: erface
'VLAN0080'
*Sep 19 07:00:21.424: 6470.0227.0A89 STA - rates (8): 1 wcm:
130 132 139 12 18 150 24 36 48 72 96 108 0 0 0 0
*Sep 19 07:00:21.424: 6470.0227.0A89 STA - rates (12): 1 wcm:
130 132 139 12 18 150 24 36 48 72 96 108 0 0 0 0
```

*Sep 19 07:00:21.424: 6470.0227.0A89 new capwap_wtp_iif_id d7844000000004,sm
capwap_wtp_iif_id d7844000000004 1 wcm: an 80, interface 'VLAN0080'
*Sep 19 07:00:21.424: 6470.0227.0A89 In >= L2AUTH_COMPLETE for station
6470.0227.0A89 1 wcm: _iif_id d7844000000004
*Sep 19 07:00:21.424: 6470.0227.0A89 192.168.80.100 RUN (20) Change state
to START (0) last state RUN (20)
1 wcm:
*Sep 19 07:00:21.424: 6470.0227.0A89 WCDB_CHANGE: 1 wcm: Client 1 m_vlan 80
Radio iif id 0xdf0f4000000005 bssid iif id 0xcd248000000015, bssid
64D8.146F.E5A0
*Sep 19 07:00:21.424: 6470.0227.0A89 WCDB_AUTH: 1 wcm: Adding opt82 len 0
*Sep 19 07:00:21.425: 6470.0227.0A89 WCDB_LLM: 1 wcm: NoRun Prev Mob 1, Curr
Mob 1 llmReq 5, return True
*Sep 19 07:00:21.425: 6470.0227.0A89 auth state 0 mob state 1 setWme 0 wme 1
roam_sent 0
1 wcm: rn True
*Sep 19 07:00:21.425: 6470.0227.0A89 WCDB_CHANGE: 1 wcm: auth=ASSOCIATION(0)
vlan 80 radio 0 client_id 0xde51c000000021 mobility=Local(1) src_int
0xd7844000000004 dst_int 0x0 ackflag 2 reassoc_client 0 llm_notif 1 ip
192.168.80.100 ip_learn_type ARP
*Sep 19 07:00:21.425: 6470.0227.0A89 192.168.80.100 START (0) Initializing
policy 1 wcm: 0 client_id 0xde51c000000021 mobility=Local(1) src_int
0xd7844000000004 dst_int 0x0 ackflag 2 reassoc_client 0 llm_notif 1 ip
192.168.80.100 ip_learn_type ARP
*Sep 19 07:00:21.425: PEM recv processing msg Del SCB(4) 1 wcm: T (0)
Initializing policy
*Sep 19 07:00:21.425: 6470.0227.0A89 192.168.80.100 START (0) Change state
to AUTHCHECK (2) last state RUN (20)
1 wcm: bility=Local(1) src_int 0xd7844000000004 dst_int 0x0 ackflag 2
reassoc_client 0 llm_notif 1 ip 192.168.80.100 ip_learn_type ARP
*Sep 19 07:00:21.425: 6470.0227.0A89 192.168.80.100 AUTHCHECK (2) Change
state to 8021X_REQD (3) last state RUN (20)
1 wcm: y=Local(1) src_int 0xd7844000000004 dst_int 0x0 ackflag 2
reassoc_client 0 llm_notif 1 ip 192.168.80.100 ip_learn_type ARP
*Sep 19 07:00:21.425: 6470.0227.0A89 192.168.80.100 8021X_REQD (3) DHCP
required on AP 64D8.146F.E5A0 vapId 1 apVapId 1for this client 1 wcm:
0xd7844000000004 dst_int 0x0 ackflag 2 reassoc_client 0 llm_notif 1 ip
192.168.80.100 ip_learn_type ARP
*Sep 19 07:00:21.425: 6470.0227.0A89 Not Using WMM Compliance code qosCap 00
1 wcm: uired on AP 64D8.146F.E5A0 vapId 1 apVapId 1for this client
*Sep 19 07:00:21.425: 6470.0227.0A89 192.168.80.100 8021X_REQD (3) Plumbed
mobile LWAPP rule on AP 64D8.146F.E5A0 vapId 1 apVapId 1 1 wcm: nt
*Sep 19 07:00:21.425: 6470.0227.0A89 apfPemAddUser2 (apf_policy.c: 1 wcm:161)
Changing state for mobile 6470.0227.0A89 on AP 64D8.146F.E5A0 from
Associated to Associated
*Sep 19 07:00:21.426: 6470.0227.0A89 Stopping deletion of Mobile Station: 1
wcm: (callerId: 48)
*Sep 19 07:00:21.426: 6470.0227.0A89 Ms Timeout = 0, Session Timeout = 1800
1 wcm: llerId: 48)
*Sep 19 07:00:21.426: 6470.0227.0A89 Sending Assoc Response to station on
BSSID 64D8.146F.E5A0 (status 0) ApVapId 1 Slot 0 1 wcm: .146F.E5A0 from
Associated to Associated
*Sep 19 07:00:21.426: 6470.0227.0A89 apfProcessAssocReq (apf_80211.c: 1 wcm:
5260) Changing state for mobile 6470.0227.0A89 on AP 64D8.146F.E5A0 from
Associated to Associated
*Sep 19 07:00:21.426: 6470.0227.0A89 192.168.80.100 8021X_REQD (3) Handling
pemDelScb Event skipping delete 1 wcm: 7.0A89 on AP 64D8.146F.E5A0 from
Associated to Associated
*Sep 19 07:00:21.435: dot1x-sm:[6470.0227.0a89, Ca0] Posting RESTART on
Client 0x60000009
*Sep 19 07:00:21.435: dot1x_auth Ca0: during state auth_authenticated,
got event 13(restart)
*Sep 19 07:00:21.435: @@@ dot1x_auth Ca0: auth_authenticated -> auth_restart
*Sep 19 07:00:21.435: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:exiting

authenticated state

*Sep 19 07:00:21.435: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:
entering restart

*Sep 19 07:00:21.435: dot1x-ev:[6470.0227.0a89, Ca0] Override cfg -
MAC 6470.0227.0a89 - profile PEAPProfile

*Sep 19 07:00:21.435: dot1x-ev:[6470.0227.0a89, Ca0] Override cfg -
SuppTimeout 30s, ReAuthMax 2, MaxReq 2, TxPeriod 30s

***Sep 19 07:00:21.435: dot1x-ev:[6470.0227.0a89, Ca0] Sending create new
context event to EAP for 0x60000009 (6470.0227.0a89)**

*Sep 19 07:00:21.435: EAP-EVENT: Received context create from LL
(Dot1x-Authenticator) (0x60000009)

*Sep 19 07:00:21.436: EAP-AUTH-EVENT: Received AAA ID 0x0000001F from LL

*Sep 19 07:00:21.436: EAP-AUTH-AAA-EVENT: Assigning AAA ID 0x0000001F

*Sep 19 07:00:21.436: EAP-AUTH-EVENT: Received Session ID
"c0a82104523aa0a30000001f" from LL

*Sep 19 07:00:21.436: EAP-AUTH-EVENT: Setting authentication mode:
Passthrough

***Sep 19 07:00:21.436: EAP-EVENT: Using EAP profile "PEAPProfile"
(handle 0x26000052)**

*Sep 19 07:00:21.436: eap_authen : initial state eap_auth_initialize
has enter

*Sep 19 07:00:21.436: EAP-EVENT: Allocated new EAP context
(handle = 0x26000052)

*Sep 19 07:00:21.436: dot1x-sm:[6470.0227.0a89, Ca0] Posting
!EAP_RESTART on Client 0x60000009

*Sep 19 07:00:21.436: dot1x_auth Ca0: during state auth_restart, got
event 6(no_eapRestart)

*Sep 19 07:00:21.436: @@@ dot1x_auth Ca0: auth_restart -> auth_connecting

*Sep 19 07:00:21.436: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:enter
connecting state

*Sep 19 07:00:21.436: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009: restart
connecting

*Sep 19 07:00:21.436: EAP-EVENT: Received EAP event
'EAP_AUTHENTICATOR_START' on handle 0x26000052

*Sep 19 07:00:21.436: eap_authen : during state eap_auth_initialize,
got event 25(eapStartTmo)

*Sep 19 07:00:21.436: @@@ eap_authen : eap_auth_initialize ->
eap_auth_select_action

*Sep 19 07:00:21.436: eap_authen : during state eap_auth_select_action,
got event 20(eapDecisionPropose)

*Sep 19 07:00:21.436: @@@ eap_authen : eap_auth_select_action ->
eap_auth_propose_method

*Sep 19 07:00:21.436: eap_authen : idle during state
eap_auth_propose_method

*Sep 19 07:00:21.436: @@@ eap_authen : eap_auth_propose_method ->
eap_auth_method_request

*Sep 19 07:00:21.436: eap_authen : idle during state
eap_auth_method_request

*Sep 19 07:00:21.436: @@@ eap_authen : eap_auth_method_request ->
eap_auth_tx_packet

*Sep 19 07:00:21.436: EAP-AUTH-EVENT: Current method = Identity

*Sep 19 07:00:21.436: EAP-EVENT: Sending LL (Dot1x-Authenticator) event
'EAP_CUSTOMIZE_ID_REQUEST' on handle 0x26000052

*Sep 19 07:00:21.436: eap_authen : idle during state eap_auth_tx_packet

*Sep 19 07:00:21.437: @@@ eap_authen : eap_auth_tx_packet -> eap_auth_idle

***Sep 19 07:00:21.437: EAP-AUTH-TX-PAK: Code:REQUEST ID:0xA Length:0x0047
Type:IDENTITY**

*Sep 19 07:00:21.437: Payload: 006E6574776F726B69643D546961676F ...

*Sep 19 07:00:21.437: EAP-EVENT: Started 'Authenticator ReqId Retransmit'
timer (30s) for EAP sesion handle 0x26000052

*Sep 19 07:00:21.437: EAP-EVENT: Started EAP tick timer

*Sep 19 07:00:21.437: EAP-EVENT: Sending LL (Dot1x-Authenticator) event
'EAP_TX_PACKET' on handle 0x26000052

*Sep 19 07:00:21.437: dot1x-sm:[6470.0227.0a89, Ca0] Posting RX_REQ on Client

0x60000009

*Sep 19 07:00:21.437: dot1x_auth Ca0: during state auth_connecting, got event 10(eapReq_no_reAuthMax)

*Sep 19 07:00:21.437: @@@ dot1x_auth Ca0: auth_connecting -> auth_authenticating

*Sep 19 07:00:21.437: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009: authenticating state entered

*Sep 19 07:00:21.437: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:connecting authenticating action

*Sep 19 07:00:21.437: dot1x-sm:[6470.0227.0a89, Ca0] Posting AUTH_START for 0x60000009

*Sep 19 07:00:21.437: dot1x_auth_bend Ca0: during state auth_bend_idle, got event 4(eapReq_authStart)

*Sep 19 07:00:21.437: @@@ dot1x_auth_bend Ca0: auth_bend_idle -> auth_bend_request

*Sep 19 07:00:21.437: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:entering request state

*Sep 19 07:00:21.437: dot1x-ev:[6470.0227.0a89, Ca0] Sending EAPOL packet

*Sep 19 07:00:21.437: dot1x-packet:[6470.0227.0a89, Ca0] Platform changed src mac of EAPOL packet

*Sep 19 07:00:21.438: dot1x-registry:registry:dot1x_ether_macaddr called

*Sep 19 07:00:21.438: dot1x-packet:EAPOL pak Tx - Ver: 0x3 type: 0x0

*Sep 19 07:00:21.438: dot1x-packet: length: 0x0047

*Sep 19 07:00:21.438: dot1x-packet:EAP code: 0x1 id: 0xA length: 0x0047

*Sep 19 07:00:21.438: dot1x-packet: type: 0x1

*Sep 19 07:00:21.438: dot1x-packet:[6470.0227.0a89, Ca0] EAPOL packet sent to client 0x60000009

*Sep 19 07:00:21.438: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:idle request action

*Sep 19 07:00:22.149: dot1x-packet:[6470.0227.0a89, Ca0] Queuing an EAPOL pkt on Authenticator Q

*Sep 19 07:00:22.149: dot1x-packet:EAPOL pak rx - Ver: 0x3 type: 0x0

*Sep 19 07:00:22.149: dot1x-packet: length: 0x000A

*Sep 19 07:00:22.149: dot1x-ev:[Ca0] Dequeued pkt: Int Ca0 CODE= 2,TYPE= 1, LEN= 10

*Sep 19 07:00:22.149: dot1x-ev:[Ca0] Received pkt saddr =6470.0227.0a89, daddr = 64d8.146f.e5a0, pae-ether-type = 888e.0300.000a

*Sep 19 07:00:22.149: dot1x-packet:EAPOL pak rx - Ver: 0x3 type: 0x0

*Sep 19 07:00:22.150: dot1x-packet: length: 0x000A

*Sep 19 07:00:22.150: dot1x-sm:[6470.0227.0a89, Ca0] Posting EAPOL_EAP for 0x60000009

*Sep 19 07:00:22.150: dot1x_auth_bend Ca0: during state auth_bend_request, got event 6(eapolEap)

*Sep 19 07:00:22.150: @@@ dot1x_auth_bend Ca0: auth_bend_request -> auth_bend_response

*Sep 19 07:00:22.150: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:entering response state

*Sep 19 07:00:22.150: dot1x-ev:[6470.0227.0a89, Ca0] Response sent to the server from 0x60000009

*Sep 19 07:00:22.150: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:request response action

*Sep 19 07:00:22.150: EAP-EVENT: Received LL (Dot1x-Authenticator) event 'EAP_RX_PACKET' on handle 0x26000052

*Sep 19 07:00:22.150: EAP-AUTH-RX-PAK: Code:RESPONSE ID:0xA Length:0x000A Type:IDENTITY

*Sep 19 07:00:22.150: Payload: 746961676F

*Sep 19 07:00:22.150: eap_authen : during state eap_auth_idle, got event 1(eapRxPacket)

*Sep 19 07:00:22.150: @@@ eap_authen : eap_auth_idle -> eap_auth_received

*Sep 19 07:00:22.150: EAP-AUTH-EVENT: EAP Response received by context 0x26000052

*Sep 19 07:00:22.150: EAP-AUTH-EVENT: EAP Response type = Identity

*Sep 19 07:00:22.150: EAP-EVENT: Stopping 'Authenticator ReqId Retransmit'

```
timer for EAP sesion handle 0x26000052
*Sep 19 07:00:22.150:      eap_authen : during state eap_auth_received, got
event 10(eapMethodData)
*Sep 19 07:00:22.150: @@@ eap_authen : eap_auth_received ->
eap_auth_method_response
*Sep 19 07:00:22.151: EAP-AUTH-EVENT: Received peer identity: tiago
*Sep 19 07:00:22.151: EAP-EVENT: Sending LL (Dot1x-Authenticator) event
'EAP_IDENTITY' on handle 0x26000052
*Sep 19 07:00:22.151:      eap_authen : during state
eap_auth_method_response, got event 13(eapMethodEnd)
*Sep 19 07:00:22.151: @@@ eap_authen : eap_auth_method_response ->
eap_auth_select_action
*Sep 19 07:00:22.151:      eap_authen : during state eap_auth_select_action,
got event 19(eapDecisionPass)
*Sep 19 07:00:22.151: @@@ eap_authen : eap_auth_select_action ->
eap_auth_passthru_init
*Sep 19 07:00:22.151:      eap_authen : during state eap_auth_passthru_init,
got event 22(eapPthruIdentity)
*Sep 19 07:00:22.151: @@@ eap_authen : eap_auth_passthru_init ->
eap_auth_aaa_req
*Sep 19 07:00:22.151: EAP-EVENT: Sending LL (Dot1x-Authenticator) event
'EAP_GET_PEER_MAC_ADDRESS' on handle 0x26000052
*Sep 19 07:00:22.151: EAP-AUTH-AAA-EVENT: Adding Audit-Session-ID
"c0a82104523aa0a30000001f" to RADIUS Req
*Sep 19 07:00:22.151: EAP-AUTH-AAA-EVENT: Added Audit-Session-ID
*Sep 19 07:00:22.151: EAP-AUTH-AAA-EVENT: Adding IDB "0x38167B5C" to
RADIUS Req
*Sep 19 07:00:22.151: EAP-AUTH-AAA-EVENT: Added IDB
*Sep 19 07:00:22.151: EAP-AUTH-AAA-EVENT: Adding EAP profile name
"PEAPProfile" to RADIUS Req
*Sep 19 07:00:22.151: EAP-AUTH-AAA-EVENT: Added EAP profile name to request
*Sep 19 07:00:22.151: EAP-EVENT: Sending LL (Dot1x-Authenticator) event
'EAP_CUSTOMIZE_AAA_REQUEST' on handle 0x26000052
*Sep 19 07:00:22.151: EAP-AUTH-AAA-EVENT: eap_auth_aaa_authen_request_shim
aaa_service 19, eap aaa_list handle 0, mlist handle 0
*Sep 19 07:00:22.151: EAP-AUTH-AAA-EVENT: Request sent successfully
*Sep 19 07:00:22.151:      eap_authen : during state eap_auth_aaa_req, got
event 24(eapAAAReqOk)
*Sep 19 07:00:22.151: @@@ eap_authen : eap_auth_aaa_req ->
eap_auth_aaa_idle
*Sep 19 07:00:22.152: EAP-EVENT: Received context create from LL
(AAA_LOCAL_EAP) (0x00000019)
*Sep 19 07:00:22.152: EAP-AUTH-EVENT: Setting authentication mode: Local
*Sep 19 07:00:22.152: EAP-EVENT: Using EAP profile "PEAPProfile"
(handle 0xCE000053)
*Sep 19 07:00:22.152:      eap_authen : initial state eap_auth_initialize
has enter
*Sep 19 07:00:22.152:      eap_authen : during state eap_auth_initialize,
got event 25(eapStartTmo)
*Sep 19 07:00:22.152: @@@ eap_authen : eap_auth_initialize ->
eap_auth_select_action
*Sep 19 07:00:22.152:      eap_authen : during state eap_auth_select_action,
got event 20(eapDecisionPropose)
*Sep 19 07:00:22.152: @@@ eap_authen : eap_auth_select_action ->
eap_auth_propose_method
*Sep 19 07:00:22.152:      eap_authen : idle during state
eap_auth_propose_method
*Sep 19 07:00:22.152: @@@ eap_authen : eap_auth_propose_method ->
eap_auth_method_request
*Sep 19 07:00:22.152:      eap_authen : during state eap_auth_method_request,
got event 21(eapDecisionWait)
*Sep 19 07:00:22.152: @@@ eap_authen : eap_auth_method_request ->
eap_auth_idle
*Sep 19 07:00:22.152: EAP-EVENT: Allocated new EAP context
```

```
(handle = 0xCE000053)
*Sep 19 07:00:22.152: EAP-EVENT: Received LL (AAA_LOCAL_EAP) event
'EAP_RX_PACKET' on handle 0xCE000053
*Sep 19 07:00:22.152: EAP-AUTH-RX-PAK: Code:RESPONSE ID:0xA Length:0x000A
Type:IDENTITY
*Sep 19 07:00:22.152: Payload: 746961676F
*Sep 19 07:00:22.152: eap_authen : during state eap_auth_idle, got event
1(eapRxPacket)
*Sep 19 07:00:22.152: @@@ eap_authen : eap_auth_idle -> eap_auth_received
*Sep 19 07:00:22.152: EAP-AUTH-EVENT: EAP Response received by context
0xCE000053
*Sep 19 07:00:22.152: EAP-AUTH-EVENT: EAP Response type = Identity
*Sep 19 07:00:22.152: eap_authen : during state eap_auth_received, got
event 10(eapMethodData)
*Sep 19 07:00:22.152: @@@ eap_authen : eap_auth_received ->
eap_auth_method_response
*Sep 19 07:00:22.152: EAP-AUTH-EVENT: Received peer identity: tiago
*Sep 19 07:00:22.153: eap_authen : during state eap_auth_method_response
got event 13(eapMethodEnd)
*Sep 19 07:00:22.153: @@@ eap_authen : eap_auth_method_response ->
eap_auth_select_action
*Sep 19 07:00:22.153: EAP-AUTH-EVENT: Using authentication mode: Local
*Sep 19 07:00:22.153: EAP-EVENT: Local methods by EAP type: [025 026]
*Sep 19 07:00:22.153: eap_authen : during state eap_auth_select_action,
got event 20(eapDecisionPropose)
*Sep 19 07:00:22.153: @@@ eap_authen : eap_auth_select_action ->
eap_auth_propose_method
*Sep 19 07:00:22.153: eap_authen : idle during state
eap_auth_propose_method
*Sep 19 07:00:22.153: @@@ eap_authen : eap_auth_propose_method ->
eap_auth_method_request
*Sep 19 07:00:22.153: EAP-AUTH-EVENT: Maximum EAP packet size: 1456
*Sep 19 07:00:22.153: EAP-EVENT: Sending method (PEAP) event 'New Context'
on handle 0xCE000053
*Sep 19 07:00:22.153: EAP-EVENT: Sending method (PEAP) event 'Receive Packet'
on handle 0xCE000053
*Sep 19 07:00:22.153: EAP-AUTH-EVENT: Waiting for asynchronous reply from
method (PEAP)
*Sep 19 07:00:22.153: eap_authen : during state eap_auth_method_request,
got event 15(eapMethodWaitReply)
*Sep 19 07:00:22.153: @@@ eap_authen : eap_auth_method_request ->
eap_auth_idle
*Sep 19 07:00:22.154: EAP-EVENT: Received Method (PEAP) event
'EAP_METHOD_REPLY' on handle 0xCE000053
*Sep 19 07:00:22.154: eap_authen : during state eap_auth_idle, got event
4(eapMethodReply)
*Sep 19 07:00:22.154: @@@ eap_authen : eap_auth_idle ->
eap_auth_method_response
*Sep 19 07:00:22.154: EAP-AUTH-EVENT: Handling asynchronous method response
for context 0xCE000053
*Sep 19 07:00:22.154: EAP-AUTH-EVENT: EAP method state: Continue
*Sep 19 07:00:22.154: EAP-AUTH-EVENT: EAP method decision: Unknown
*Sep 19 07:00:22.154: eap_authen : during state eap_auth_method_response,
got event 14(eapMethodContinue)
*Sep 19 07:00:22.154: @@@ eap_authen : eap_auth_method_response ->
eap_auth_method_request
*Sep 19 07:00:22.154: eap_authen : idle during state
eap_auth_method_request
*Sep 19 07:00:22.154: @@@ eap_authen : eap_auth_method_request ->
eap_auth_tx_packet
*Sep 19 07:00:22.154: EAP-AUTH-EVENT: Current method = 25
*Sep 19 07:00:22.154: eap_authen : idle during state eap_auth_tx_packet
*Sep 19 07:00:22.154: @@@ eap_authen : eap_auth_tx_packet -> eap_auth_idle
*Sep 19 07:00:22.154: EAP-AUTH-TX-PAK: Code:REQUEST ID:0xB Length:0x0006
```

Type:PEAP
*Sep 19 07:00:22.154: Payload: 21
*Sep 19 07:00:22.154: EAP-EVENT: Sending LL (AAA_LOCAL_EAP) event
'EAP_TX_PACKET' on handle 0xCE000053
*Sep 19 07:00:22.154: EAP-EVENT: eap_aaa_reply
*Sep 19 07:00:22.154: EAP-AUTH-AAA-EVENT: Reply received session_label
BB000020
*Sep 19 07:00:22.154: EAP-AUTH-AAA-EVENT: Response contains EAP Message,
code: 1
*Sep 19 07:00:22.155: EAP-EVENT: Received AAA event 'EAP_AAA_RX_PACKET' on
handle 0x26000052
*Sep 19 07:00:22.155: EAP-AUTH-RX-AAA-PAK: Code:REQUEST ID:0xB Length:0x0006
Type:PEAP
*Sep 19 07:00:22.155: Payload: 21
*Sep 19 07:00:22.155: eap_authen : during state eap_auth_aaa_idle, got
event 5(eapAAARxPacket)
*Sep 19 07:00:22.155: @@@ eap_authen : eap_auth_aaa_idle ->
eap_auth_aaa_resp
*Sep 19 07:00:22.155: eap_authen : idle during state eap_auth_aaa_resp
*Sep 19 07:00:22.155: @@@ eap_authen : eap_auth_aaa_resp ->
eap_auth_tx_packet2
*Sep 19 07:00:22.155: EAP-AUTH-EVENT: Current method = 25
*Sep 19 07:00:22.155: eap_authen : idle during state eap_auth_tx_packet2
*Sep 19 07:00:22.155: @@@ eap_authen : eap_auth_tx_packet2 -> eap_auth_idle2
***Sep 19 07:00:22.155: EAP-AUTH-TX-PAK: Code:REQUEST ID:0xB Length:0x0006**
Type:PEAP
*Sep 19 07:00:22.155: Payload: 21
*Sep 19 07:00:22.155: EAP-EVENT: Started 'Authenticator Retransmit' timer
(30s) for EAP sesion handle 0x26000052
*Sep 19 07:00:22.155: EAP-EVENT: Started EAP tick timer
*Sep 19 07:00:22.155: EAP-EVENT: Sending LL (Dot1x-Authenticator) event
'EAP_TX_PACKET' on handle 0x26000052
*Sep 19 07:00:22.155: dot1x-sm:[6470.0227.0a89, Ca0] Posting EAP_REQ for
0x60000009
*Sep 19 07:00:22.155: dot1x_auth_bend Ca0: during state
auth_bend_response, got event 7(eapReq)
*Sep 19 07:00:22.155: @@@ dot1x_auth_bend Ca0: auth_bend_response ->
auth_bend_request
*Sep 19 07:00:22.155: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:exiting
response state
*Sep 19 07:00:22.155: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:entering
request state
*Sep 19 07:00:22.155: dot1x-ev:[6470.0227.0a89, Ca0] Sending EAPOL packet
*Sep 19 07:00:22.155: dot1x-packet:[6470.0227.0a89, Ca0] Platform changed
src mac of EAPOL packet
*Sep 19 07:00:22.155: dot1x-registry:registry:dot1x_ether_macaddr called
*Sep 19 07:00:22.155: dot1x-packet:EAPOL pak Tx - Ver: 0x3 type: 0x0
*Sep 19 07:00:22.155: dot1x-packet: length: 0x0006
*Sep 19 07:00:22.155: dot1x-packet:EAP code: 0x1 id: 0xB length: 0x0006
*Sep 19 07:00:22.155: dot1x-packet: type: 0x19
*Sep 19 07:00:22.156: dot1x-packet:[6470.0227.0a89, Ca0] EAPOL packet sent
to client 0x60000009
*Sep 19 07:00:22.156: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:response
request action
*Sep 19 07:00:22.395: dot1x-packet:[6470.0227.0a89, Ca0] Queuing an EAPOL
pkt on Authenticator Q
*Sep 19 07:00:22.395: dot1x-packet:EAPOL pak rx - Ver: 0x3 type: 0x0
*Sep 19 07:00:22.395: dot1x-packet: length: 0x0098
*Sep 19 07:00:22.395: dot1x-ev:[Ca0] Dequeued pkt: Int Ca0 CODE= 2,TYPE= 25,
LEN= 152

*Sep 19 07:00:22.396: dot1x-ev:[Ca0] Received pkt saddr =6470.0227.0a89 ,
daddr = 64d8.146f.e5a0, pae-ether-type = 888e.0300.0098
*Sep 19 07:00:22.396: dot1x-packet:EAPOL pak rx - Ver: 0x3 type: 0x0

*Sep 19 07:00:22.396: dot1x-packet: length: 0x0098
*Sep 19 07:00:22.396: dot1x-sm:[6470.0227.0a89, Ca0] Posting EAPOL_EAP for 0x60000009
*Sep 19 07:00:22.396: dot1x_auth_bend Ca0: during state auth_bend_request, got event 6(eapolEap)
*Sep 19 07:00:22.396: @@@ dot1x_auth_bend Ca0: auth_bend_request -> auth_bend_response
*Sep 19 07:00:22.396: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:entering response state
*Sep 19 07:00:22.396: dot1x-ev:[6470.0227.0a89, Ca0] Response sent to the server from 0x60000009
*Sep 19 07:00:22.396: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:request response action
*Sep 19 07:00:22.396: EAP-EVENT: Received LL (Dot1x-Authenticator) event 'EAP_RX_PACKET' on handle 0x26000052
*Sep 19 07:00:22.396: EAP-AUTH-RX-PAK: Code:RESPONSE ID:0xB Length:0x0098 Type:PEAP
*Sep 19 07:00:22.396: Payload: 810000008E1603010089010000850301 ...
*Sep 19 07:00:22.396: eap_authen : during state eap_auth_idle2, got event 1(eapRxPacket)
*Sep 19 07:00:22.396: @@@ eap_authen : eap_auth_idle2 -> eap_auth_received2
*Sep 19 07:00:22.396: EAP-AUTH-EVENT: EAP Response received by context 0x26000052
*Sep 19 07:00:22.396: EAP-AUTH-EVENT: EAP Response type = Method (25)
*Sep 19 07:00:22.396: EAP-EVENT: Stopping 'Authenticator Retransmit' timer for EAP sesion handle 0x26000052
*Sep 19 07:00:22.396: eap_authen : during state eap_auth_received2, got event 10(eapMethodData)
*Sep 19 07:00:22.397: @@@ eap_authen : eap_auth_received2->eap_auth_aaa_req
*Sep 19 07:00:22.397: EAP-AUTH-AAA-EVENT: Adding Audit-Session-ID "c0a82104523aa0a30000001f" to RADIUS Req
*Sep 19 07:00:22.397: EAP-AUTH-AAA-EVENT: Added Audit-Session-ID
*Sep 19 07:00:22.397: EAP-AUTH-AAA-EVENT: Adding IDB "0x38167B5C" to RADIUS Req
*Sep 19 07:00:22.397: EAP-AUTH-AAA-EVENT: Added IDB
*Sep 19 07:00:22.397: EAP-AUTH-AAA-EVENT: Adding EAP profile name "PEAPProfile" to RADIUS Req
*Sep 19 07:00:22.397: EAP-AUTH-AAA-EVENT: Added EAP profile name to request
*Sep 19 07:00:22.397: EAP-EVENT: Sending LL (Dot1x-Authenticator) event 'EAP_CUSTOMIZE_AAA_REQUEST' on handle 0x26000052
*Sep 19 07:00:22.397: EAP-AUTH-AAA-EVENT: eap_auth_aaa_authen_request_shim aaa_service 19, eap aaa_list handle 0, mlist handle 0
*Sep 19 07:00:22.397: EAP-AUTH-AAA-EVENT: Request sent successfully
*Sep 19 07:00:22.397: eap_authen : during state eap_auth_aaa_req, got event 24(eapAAAReqOk)
*Sep 19 07:00:22.397: @@@ eap_authen : eap_auth_aaa_req -> eap_auth_aaa_idle
*Sep 19 07:00:22.397: EAP-EVENT: Received LL (AAA_LOCAL_EAP) event 'EAP_RX_PACKET' on handle 0xCE000053
*Sep 19 07:00:22.398: EAP-AUTH-RX-PAK: Code:RESPONSE ID:0xB Length:0x0098 Type:PEAP
*Sep 19 07:00:22.398: Payload: 810000008E1603010089010000850301 ...
*Sep 19 07:00:22.398: eap_authen : during state eap_auth_idle, got event 1(eapRxPacket)
*Sep 19 07:00:22.398: @@@ eap_authen : eap_auth_idle -> eap_auth_received
*Sep 19 07:00:22.398: EAP-AUTH-EVENT: EAP Response received by context 0xCE000053
*Sep 19 07:00:22.398: EAP-AUTH-EVENT: EAP Response type = Method (25)
*Sep 19 07:00:22.398: eap_authen : during state eap_auth_received, got event 10(eapMethodData)
*Sep 19 07:00:22.398: @@@ eap_authen : eap_auth_received -> eap_auth_method_response
*Sep 19 07:00:22.398: EAP-EVENT: Sending method (PEAP) event 'Receive Packet' on handle 0xCE000053
*Sep 19 07:00:22.398: EAP-AUTH-EVENT: Waiting for asynchronous reply from

```
method (PEAP)
*Sep 19 07:00:22.398:      eap_authen : during state eap_auth_method_response,
got event 15(eapMethodWaitReply)
*Sep 19 07:00:22.398: @@@ eap_authen : eap_auth_method_response ->
eap_auth_idle
*Sep 19 07:00:22.399: EAP-EVENT: Received Method (PEAP) event
'EAP_METHOD_REPLY' on handle 0xCE000053
*Sep 19 07:00:22.399:      eap_authen : during state eap_auth_idle, got event
4(eapMethodReply)
*Sep 19 07:00:22.399: @@@ eap_authen : eap_auth_idle ->
eap_auth_method_response
*Sep 19 07:00:22.399: EAP-AUTH-EVENT: Handling asynchronous method response
for context 0xCE000053
*Sep 19 07:00:22.399: EAP-AUTH-EVENT: EAP method state: Continue
*Sep 19 07:00:22.399: EAP-AUTH-EVENT: EAP method decision: Unknown
*Sep 19 07:00:22.399:      eap_authen : during state eap_auth_method_response,
got event 14(eapMethodContinue)
*Sep 19 07:00:22.399: @@@ eap_authen : eap_auth_method_response ->
eap_auth_method_request
*Sep 19 07:00:22.399:      eap_authen : idle during state
eap_auth_method_request
*Sep 19 07:00:22.399: @@@ eap_authen : eap_auth_method_request ->
eap_auth_tx_packet
*Sep 19 07:00:22.399: EAP-AUTH-EVENT: Current method = 25
*Sep 19 07:00:22.399:      eap_authen : idle during state eap_auth_tx_packet
*Sep 19 07:00:22.399: @@@ eap_authen : eap_auth_tx_packet -> eap_auth_idle
*Sep 19 07:00:22.399: EAP-AUTH-TX-PAK: Code:REQUEST ID:0xC Length:0x02B1
Type:PEAP
*Sep 19 07:00:22.399:      Payload: 81000002A7160301004A020000460301 ...
*Sep 19 07:00:22.399: EAP-EVENT: Sending LL (AAA_LOCAL_EAP) event
'EAP_TX_PACKET' on handle 0xCE000053
*Sep 19 07:00:22.399: EAP-EVENT: eap_aaa_reply
*Sep 19 07:00:22.400: EAP-AUTH-AAA-EVENT: Reply received session_label
BB000020
*Sep 19 07:00:22.400: EAP-AUTH-AAA-EVENT: Response contains EAP Message,
code: 1
*Sep 19 07:00:22.400: EAP-EVENT: Received AAA event 'EAP_AAA_RX_PACKET' on
handle 0x26000052
*Sep 19 07:00:22.400: EAP-AUTH-RX-AAA-PAK: Code:REQUEST ID:0xC Length:0x02B1
Type:PEAP
*Sep 19 07:00:22.400:      Payload: 81000002A7160301004A020000460301 ...
*Sep 19 07:00:22.400:      eap_authen : during state eap_auth_aaa_idle, got
event 5(eapAAARxPacket)
*Sep 19 07:00:22.400: @@@ eap_authen : eap_auth_aaa_idle ->
eap_auth_aaa_resp
*Sep 19 07:00:22.400:      eap_authen : idle during state eap_auth_aaa_resp
*Sep 19 07:00:22.400: @@@ eap_authen : eap_auth_aaa_resp ->
eap_auth_tx_packet2
*Sep 19 07:00:22.400: EAP-AUTH-EVENT: Current method = 25
*Sep 19 07:00:22.400:      eap_authen : idle during state eap_auth_tx_packet2
*Sep 19 07:00:22.400: @@@ eap_authen : eap_auth_tx_packet2 -> eap_auth_idle2
*Sep 19 07:00:22.400: EAP-AUTH-TX-PAK: Code:REQUEST ID:0xC Length:0x02B1
Type:PEAP
*Sep 19 07:00:22.400:      Payload: 81000002A7160301004A020000460301 ...
*Sep 19 07:00:22.400: EAP-EVENT: Started 'Authenticator Retransmit' timer
(30s) for EAP sesion handle 0x26000052
*Sep 19 07:00:22.400: EAP-EVENT: Started EAP tick timer
*Sep 19 07:00:22.400: EAP-EVENT: Sending LL (Dot1x-Authenticator) event
'EAP_TX_PACKET' on handle 0x26000052
*Sep 19 07:00:22.400: dot1x-sm:[6470.0227.0a89, Ca0] Posting EAP_REQ for
0x60000009
*Sep 19 07:00:22.400:      dot1x_auth_bend Ca0: during state
auth_bend_response, got event 7(eapReq)
*Sep 19 07:00:22.400: @@@ dot1x_auth_bend Ca0: auth_bend_response ->
```

```
auth_bend_request
*Sep 19 07:00:22.400: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:exiting
response state
*Sep 19 07:00:22.400: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:entering
request state
*Sep 19 07:00:22.400: dot1x-ev:[6470.0227.0a89, Ca0] Sending EAPOL packet
*Sep 19 07:00:22.401: dot1x-packet:[6470.0227.0a89, Ca0] Platform changed
src mac of EAPOL packet
*Sep 19 07:00:22.401: dot1x-registry:registry:dot1x_ether_macaddr called
*Sep 19 07:00:22.401: dot1x-packet:EAPOL pak Tx - Ver: 0x3 type: 0x0
*Sep 19 07:00:22.401: dot1x-packet: length: 0x02B1
*Sep 19 07:00:22.401: dot1x-packet:EAP code: 0x1 id: 0xC length: 0x02B1
*Sep 19 07:00:22.401: dot1x-packet: type: 0x19
*Sep 19 07:00:22.401: dot1x-packet:[6470.0227.0a89, Ca0] EAPOL packet sent
to client 0x60000009
*Sep 19 07:00:22.401: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:response
request action
*Sep 19 07:00:22.646: dot1x-packet:[6470.0227.0a89, Ca0] Queuing an EAPOL
pkt on Authenticator Q
*Sep 19 07:00:22.646: dot1x-packet:EAPOL pak rx - Ver: 0x3 type: 0x0
*Sep 19 07:00:22.646: dot1x-packet: length: 0x00C8
*Sep 19 07:00:22.646: dot1x-ev:[Ca0] Dequeued pkt: Int Ca0 CODE= 2,TYPE= 25,
LEN= 200

*Sep 19 07:00:22.646: dot1x-ev:[Ca0] Received pkt saddr =6470.0227.0a89 ,
daddr = 64d8.146f.e5a0, pae-ether-type = 888e.0300.00c8
*Sep 19 07:00:22.646: dot1x-packet:EAPOL pak rx - Ver: 0x3 type: 0x0
*Sep 19 07:00:22.646: dot1x-packet: length: 0x00C8
*Sep 19 07:00:22.647: dot1x-sm:[6470.0227.0a89, Ca0] Posting EAPOL_EAP for
0x60000009
*Sep 19 07:00:22.647: dot1x_auth_bend Ca0: during state
auth_bend_request, got event 6(eapolEap)
*Sep 19 07:00:22.647: @@@ dot1x_auth_bend Ca0: auth_bend_request ->
auth_bend_response
*Sep 19 07:00:22.647: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:entering
response state
*Sep 19 07:00:22.647: dot1x-ev:[6470.0227.0a89, Ca0] Response sent to the
server from 0x60000009
*Sep 19 07:00:22.647: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:request
response action
*Sep 19 07:00:22.647: EAP-EVENT: Received LL (Dot1x-Authenticator) event
'EAP_RX_PACKET' on handle 0x26000052
*Sep 19 07:00:22.647: EAP-AUTH-RX-PAK: Code:RESPONSE ID:0xC Length:0x00C8
Type:PEAP
*Sep 19 07:00:22.647: Payload: 81000000BE1603010086100000820080 ...
*Sep 19 07:00:22.647: eap_authen : during state eap_auth_idle2, got
event 1(eapRxPacket)
*Sep 19 07:00:22.647: @@@ eap_authen : eap_auth_idle2 -> eap_auth_received2
*Sep 19 07:00:22.647: EAP-AUTH-EVENT: EAP Response received by context
0x26000052
*Sep 19 07:00:22.647: EAP-AUTH-EVENT: EAP Response type = Method (25)
*Sep 19 07:00:22.647: EAP-EVENT: Stopping 'Authenticator Retransmit' timer
for EAP sesion handle 0x26000052
*Sep 19 07:00:22.647: eap_authen : during state eap_auth_received2, got
event 10(eapMethodData)
*Sep 19 07:00:22.647: @@@ eap_authen : eap_auth_received2 ->
eap_auth_aaa_req
*Sep 19 07:00:22.647: EAP-AUTH-AAA-EVENT: Adding Audit-Session-ID
"c0a82104523aa0a30000001f" to RADIUS Req
*Sep 19 07:00:22.647: EAP-AUTH-AAA-EVENT: Added Audit-Session-ID
*Sep 19 07:00:22.647: EAP-AUTH-AAA-EVENT: Adding IDB "0x38167B5C" to
RADIUS Req
*Sep 19 07:00:22.647: EAP-AUTH-AAA-EVENT: Added IDB
*Sep 19 07:00:22.648:
```


EAP-AUTH-AAA-EVENT: Adding EAP profile name "PEAPProfile" to RADIUS Req
*Sep 19 07:00:22.648: EAP-AUTH-AAA-EVENT: Added EAP profile name to request
*Sep 19 07:00:22.648: EAP-EVENT: Sending LL (Dot1x-Authenticator) event
'EAP_CUSTOMIZE_AAA_REQUEST' on handle 0x26000052
*Sep 19 07:00:22.648: EAP-AUTH-AAA-EVENT: eap_auth_aaa_authen_request_shim
aaa_service 19, eap aaa_list handle 0, mlist handle 0
*Sep 19 07:00:22.648: EAP-AUTH-AAA-EVENT: Request sent successfully
*Sep 19 07:00:22.648: eap_authen : during state eap_auth_aaa_req, got
event 24(eapAAAReqOk)
*Sep 19 07:00:22.648: @@@ eap_authen : eap_auth_aaa_req -> eap_auth_aaa_idle
*Sep 19 07:00:22.648: EAP-EVENT: Received LL (AAA_LOCAL_EAP) event
'EAP_RX_PACKET' on handle 0xCE000053
*Sep 19 07:00:22.648: EAP-AUTH-RX-PAK: Code:RESPONSE ID:0xC Length:0x00C8
Type:PEAP
*Sep 19 07:00:22.648: Payload: 81000000BE1603010086100000820080 ...
*Sep 19 07:00:22.648: eap_authen : during state eap_auth_idle, got event
1(eapRxPacket)
*Sep 19 07:00:22.648: @@@ eap_authen : eap_auth_idle -> eap_auth_received
*Sep 19 07:00:22.648: EAP-AUTH-EVENT: EAP Response received by context
0xCE000053
*Sep 19 07:00:22.648: EAP-AUTH-EVENT: EAP Response type = Method (25)
*Sep 19 07:00:22.649: eap_authen : during state eap_auth_received, got
event 10(eapMethodData)
*Sep 19 07:00:22.649: @@@ eap_authen : eap_auth_received ->
eap_auth_method_response
*Sep 19 07:00:22.649: EAP-EVENT: Sending method (PEAP) event 'Receive Packet'
on handle 0xCE000053
*Sep 19 07:00:22.649: EAP-AUTH-EVENT: Waiting for asynchronous reply from
method (PEAP)
*Sep 19 07:00:22.649: eap_authen : during state eap_auth_method_response,
got event 15(eapMethodWaitReply)
*Sep 19 07:00:22.649: @@@ eap_authen : eap_auth_method_response ->
eap_auth_idle
*Sep 19 07:00:22.675: EAP-EVENT: Received Method (PEAP) event
'EAP_METHOD_REPLY' on handle 0xCE000053
*Sep 19 07:00:22.675: eap_authen : during state eap_auth_idle, got
event 4(eapMethodReply)
*Sep 19 07:00:22.675: @@@ eap_authen : eap_auth_idle ->
eap_auth_method_response
*Sep 19 07:00:22.675: EAP-AUTH-EVENT: Handling asynchronous method response
for context 0xCE000053
*Sep 19 07:00:22.675: EAP-AUTH-EVENT: EAP method state: Continue
*Sep 19 07:00:22.675: EAP-AUTH-EVENT: EAP method decision: Unknown
*Sep 19 07:00:22.675: eap_authen : during state eap_auth_method_response,
got event 14(eapMethodContinue)
*Sep 19 07:00:22.675: @@@ eap_authen : eap_auth_method_response ->
eap_auth_method_request
*Sep 19 07:00:22.675: eap_authen : idle during state
eap_auth_method_request
*Sep 19 07:00:22.675: @@@ eap_authen : eap_auth_method_request ->
eap_auth_tx_packet
*Sep 19 07:00:22.675: EAP-AUTH-EVENT: Current method = 25
*Sep 19 07:00:22.675: eap_authen : idle during state eap_auth_tx_packet
*Sep 19 07:00:22.675: @@@ eap_authen : eap_auth_tx_packet -> eap_auth_idle
*Sep 19 07:00:22.675: EAP-AUTH-TX-PAK: Code:REQUEST ID:0xD Length:0x003D
Type:PEAP
*Sep 19 07:00:22.676: Payload: 81000000331403010001011603010028 ...
*Sep 19 07:00:22.676: EAP-EVENT: Sending LL (AAA_LOCAL_EAP) event
'EAP_TX_PACKET' on handle 0xCE000053
*Sep 19 07:00:22.676: EAP-EVENT: eap_aaa_reply
*Sep 19 07:00:22.676: EAP-AUTH-AAA-EVENT: Reply received session_label
BB000020
*Sep 19 07:00:22.676: EAP-AUTH-AAA-EVENT: Response contains EAP Message,
code: 1

*Sep 19 07:00:22.676: EAP-EVENT: Received AAA event 'EAP_AAA_RX_PACKET' on handle 0x26000052

*Sep 19 07:00:22.676: EAP-AUTH-RX-AAA-PAK: Code:REQUEST ID:0xD Length:0x003D Type:PEAP

*Sep 19 07:00:22.676: Payload: 81000000331403010001011603010028 ...

*Sep 19 07:00:22.676: eap_authen : during state eap_auth_aaa_idle, got event 5(eapAAARxPacket)

*Sep 19 07:00:22.676: @@@ eap_authen : eap_auth_aaa_idle -> eap_auth_aaa_resp

*Sep 19 07:00:22.676: eap_authen : idle during state eap_auth_aaa_resp

*Sep 19 07:00:22.676: @@@ eap_authen : eap_auth_aaa_resp -> eap_auth_tx_packet2

*Sep 19 07:00:22.676: EAP-AUTH-EVENT: Current method = 25

*Sep 19 07:00:22.676: eap_authen : idle during state eap_auth_tx_packet2

*Sep 19 07:00:22.676: @@@ eap_authen : eap_auth_tx_packet2 -> eap_auth_idle2

*Sep 19 07:00:22.676: EAP-AUTH-TX-PAK: Code:REQUEST ID:0xD Length:0x003D Type:PEAP

*Sep 19 07:00:22.676: Payload: 81000000331403010001011603010028 ...

*Sep 19 07:00:22.676: EAP-EVENT: Started 'Authenticator Retransmit' timer (30s) for EAP sesion handle 0x26000052

*Sep 19 07:00:22.676: EAP-EVENT: Started EAP tick timer

*Sep 19 07:00:22.676: EAP-EVENT: Sending LL (Dot1x-Authenticator) event 'EAP_TX_PACKET' on handle 0x26000052

*Sep 19 07:00:22.677: dot1x-sm:[6470.0227.0a89, Ca0] Posting EAP_REQ for 0x60000009

*Sep 19 07:00:22.677: dot1x_auth_bend Ca0: during state auth_bend_response, got event 7(eapReq)

*Sep 19 07:00:22.677: @@@ dot1x_auth_bend Ca0: auth_bend_response -> auth_bend_request

*Sep 19 07:00:22.677: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:exiting response state

*Sep 19 07:00:22.677: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:entering request state

*Sep 19 07:00:22.677: dot1x-ev:[6470.0227.0a89, Ca0] Sending EAPOL packet

*Sep 19 07:00:22.677: dot1x-packet:[6470.0227.0a89, Ca0] Platform changed src mac of EAPOL packet

*Sep 19 07:00:22.677: dot1x-registry:registry:dot1x_ether_macaddr called

*Sep 19 07:00:22.677: dot1x-packet:EAPOL pak Tx - Ver: 0x3 type: 0x0

*Sep 19 07:00:22.677: dot1x-packet: length: 0x003D

*Sep 19 07:00:22.677: dot1x-packet:EAP code: 0x1 id: 0xD length: 0x003D

*Sep 19 07:00:22.677: dot1x-packet: type: 0x19

*Sep 19 07:00:22.677: dot1x-packet:[6470.0227.0a89, Ca0] EAPOL packet sent to client 0x60000009

*Sep 19 07:00:22.677: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:response request action

*Sep 19 07:00:22.902: dot1x-packet:[6470.0227.0a89, Ca0] Queuing an EAPOL pkt on Authenticator Q

*Sep 19 07:00:22.903: dot1x-packet:EAPOL pak rx - Ver: 0x3 type: 0x0

*Sep 19 07:00:22.903: dot1x-packet: length: 0x0006

*Sep 19 07:00:22.903: dot1x-ev:[Ca0] Dequeued pkt: Int Ca0 CODE= 2,TYPE= 25, LEN= 6

*Sep 19 07:00:22.903: dot1x-ev:[Ca0] Received pkt saddr =6470.0227.0a89 , daddr = 64d8.146f.e5a0, pae-ether-type = 888e.0300.0006

*Sep 19 07:00:22.903: dot1x-packet:EAPOL pak rx - Ver: 0x3 type: 0x0

*Sep 19 07:00:22.903: dot1x-packet: length: 0x0006

*Sep 19 07:00:22.903: dot1x-sm:[6470.0227.0a89, Ca0] Posting EAPOL_EAP for 0x60000009

*Sep 19 07:00:22.903: dot1x_auth_bend Ca0: during state auth_bend_request, got event 6(eapolEap)

*Sep 19 07:00:22.903: @@@ dot1x_auth_bend Ca0: auth_bend_request -> auth_bend_response

*Sep 19 07:00:22.903: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:entering response state

*Sep 19 07:00:22.903: dot1x-ev:[6470.0227.0a89, Ca0] Response sent to the server from 0x60000009

*Sep 19 07:00:22.903: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:request response action

*Sep 19 07:00:22.904: EAP-EVENT: Received LL (Dot1x-Authenticator) event 'EAP_RX_PACKET' on handle 0x26000052

*Sep 19 07:00:22.904: EAP-AUTH-RX-PAK: Code:RESPONSE ID:0xD Length:0x0006 Type:PEAP

*Sep 19 07:00:22.904: Payload: 01

*Sep 19 07:00:22.904: eap_authen : during state eap_auth_idle2, got event 1(eapRxPacket)

*Sep 19 07:00:22.904: @@@ eap_authen : eap_auth_idle2 -> eap_auth_received2

*Sep 19 07:00:22.904: EAP-AUTH-EVENT: EAP Response received by context 0x26000052

*Sep 19 07:00:22.904: EAP-AUTH-EVENT: EAP Response type = Method (25)

*Sep 19 07:00:22.904: EAP-EVENT: Stopping 'Authenticator Retransmit' timer for EAP sesion handle 0x26000052

*Sep 19 07:00:22.904: eap_authen : during state eap_auth_received2, got event 10(eapMethodData)

*Sep 19 07:00:22.904: @@@ eap_authen : eap_auth_received2 -> eap_auth_aaa_req

*Sep 19 07:00:22.904: EAP-AUTH-AAA-EVENT: Adding Audit-Session-ID "c0a82104523aa0a30000001f" to RADIUS Req

*Sep 19 07:00:22.904: EAP-AUTH-AAA-EVENT: Added Audit-Session-ID

*Sep 19 07:00:22.904: EAP-AUTH-AAA-EVENT: Adding IDB "0x38167B5C" to RADIUS Req

*Sep 19 07:00:22.904: EAP-AUTH-AAA-EVENT: Added IDB

***Sep 19 07:00:22.904: EAP-AUTH-AAA-EVENT: Adding EAP profile name "PEAPProfile" to RADIUS Req**

*Sep 19 07:00:22.904: EAP-AUTH-AAA-EVENT: Added EAP profile name to request

*Sep 19 07:00:22.904: EAP-EVENT: Sending LL (Dot1x-Authenticator) event 'EAP_CUSTOMIZE_AAA_REQUEST' on handle 0x26000052

*Sep 19 07:00:22.904: EAP-AUTH-AAA-EVENT: eap_auth_aaa_authen_request_shim aaa_service 19, eap aaa_list handle 0, mlist handle 0

*Sep 19 07:00:22.905: EAP-AUTH-AAA-EVENT: Request sent successfully

*Sep 19 07:00:22.905: eap_authen : during state eap_auth_aaa_req, got event 24(eapAAAReqOk)

*Sep 19 07:00:22.905: @@@ eap_authen : eap_auth_aaa_req -> eap_auth_aaa_idle

*Sep 19 07:00:22.905: EAP-EVENT: Received LL (AAA_LOCAL_EAP) event 'EAP_RX_PACKET' on handle 0xCE000053

*Sep 19 07:00:22.905: EAP-AUTH-RX-PAK: Code:RESPONSE ID:0xD Length:0x0006 Type:PEAP

*Sep 19 07:00:22.905: Payload: 01

*Sep 19 07:00:22.905: eap_authen : during state eap_auth_idle, got event 1(eapRxPacket)

*Sep 19 07:00:22.905: @@@ eap_authen : eap_auth_idle -> eap_auth_received

*Sep 19 07:00:22.905: EAP-AUTH-EVENT: EAP Response received by context 0xCE000053

*Sep 19 07:00:22.905: EAP-AUTH-EVENT: EAP Response type = Method (25)

*Sep 19 07:00:22.905: eap_authen : during state eap_auth_received, got event 10(eapMethodData)

*Sep 19 07:00:22.905: @@@ eap_authen : eap_auth_received -> eap_auth_method_response

*Sep 19 07:00:22.905: EAP-EVENT: Sending method (PEAP) event 'Receive Packet' on handle 0xCE000053

*Sep 19 07:00:22.905: EAP-EVENT: Received context create from LL (PEAP) (0x69000006)

*Sep 19 07:00:22.905: EAP-AUTH-EVENT: Setting authentication mode: Local

*Sep 19 07:00:22.905: EAP-EVENT: Using EAP profile "PEAP Inner Method EAP Profile" (handle 0x99000054)

*Sep 19 07:00:22.905: eap_authen : initial state eap_auth_initialize has enter

*Sep 19 07:00:22.905: EAP-EVENT: Allocated new EAP context (handle = 0x99000054)

*Sep 19 07:00:22.906: EAP-AUTH-EVENT: Waiting for asynchronous reply from

```
method (PEAP)
*Sep 19 07:00:22.906:      eap_authen : during state eap_auth_method_response,
got event 15(eapMethodWaitReply)
*Sep 19 07:00:22.906: @@@ eap_authen : eap_auth_method_response ->
eap_auth_idle
*Sep 19 07:00:22.906: EAP-EVENT: Received EAP event 'EAP_AUTHENTICATOR_START'
on handle 0x99000054
*Sep 19 07:00:22.906:      eap_authen : during state eap_auth_initialize, got
event 25(eapStartTmo)
*Sep 19 07:00:22.906: @@@ eap_authen : eap_auth_initialize ->
eap_auth_select_action
*Sep 19 07:00:22.906:      eap_authen : during state eap_auth_select_action,
got event 20(eapDecisionPropose)
*Sep 19 07:00:22.906: @@@ eap_authen : eap_auth_select_action ->
eap_auth_propose_method
*Sep 19 07:00:22.906:      eap_authen : idle during state
eap_auth_propose_method
*Sep 19 07:00:22.906: @@@ eap_authen : eap_auth_propose_method ->
eap_auth_method_request
*Sep 19 07:00:22.908: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:response
request action
*Sep 19 07:00:23.148: dot1x-packet:[6470.0227.0a89, Ca0] Queuing an EAPOL pkt
on Authenticator Q
*Sep 19 07:00:23.148: dot1x-packet:EAPOL pak rx - Ver: 0x3  type: 0x0
*Sep 19 07:00:23.148: dot1x-packet: length: 0x0048
*Sep 19 07:00:23.148: dot1x-ev:[Ca0] Dequeued pkt: Int Ca0 CODE= 2,TYPE= 25,
LEN= 72

*Sep 19 07:00:23.148: dot1x-ev:[Ca0] Received pkt saddr =6470.0227.0a89 ,
daddr = 64d8.146f.e5a0, pae-ether-type = 888e.0300.0048
*Sep 19 07:00:23.148: dot1x-packet:EAPOL pak rx - Ver: 0x3  type: 0x0
*Sep 19 07:00:23.148: dot1x-packet: length: 0x0048
*Sep 19 07:00:23.148: dot1x-sm:[6470.0227.0a89, Ca0] Posting EAPOL_EAP for
0x60000009
*Sep 19 07:00:23.148:      dot1x_auth_bend Ca0: during state
auth_bend_request, got event 6(eapolEap)
*Sep 19 07:00:23.148: @@@ dot1x_auth_bend Ca0: auth_bend_request ->
auth_bend_response
*Sep 19 07:00:23.148: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:entering
response state
*Sep 19 07:00:23.148: dot1x-ev:[6470.0227.0a89, Ca0] Response sent to the
server from 0x60000009
*Sep 19 07:00:23.148: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:request
response action
*Sep 19 07:00:23.149: EAP-EVENT: Received LL (Dot1x-Authenticator) event
'EAP_RX_PACKET' on handle 0x26000052
*Sep 19 07:00:23.149: EAP-AUTH-RX-PAK: Code:RESPONSE ID:0xE Length:0x0048
Type:PEAP
*Sep 19 07:00:23.149:      Payload:  011703010018E5BC67F95BDE2D2BF45C ...
*Sep 19 07:00:23.149:      eap_authen : during state eap_auth_idle2, got event
1(eapRxPacket)
*Sep 19 07:00:23.149: @@@ eap_authen : eap_auth_idle2 -> eap_auth_received2
*Sep 19 07:00:23.149: EAP-AUTH-EVENT: EAP Response received by context
0x26000052
*Sep 19 07:00:23.149: EAP-AUTH-EVENT: EAP Response type = Method (25)
*Sep 19 07:00:23.149: EAP-EVENT: Stopping 'Authenticator Retransmit' timer
for EAP sesion handle 0x26000052
*Sep 19 07:00:23.149:      eap_authen : during state eap_auth_received2, got
event 10(eapMethodData)
*Sep 19 07:00:23.149: @@@ eap_authen : eap_auth_received2 -> eap_auth_aaa_req
*Sep 19 07:00:23.149: EAP-AUTH-AAA-EVENT: Adding Audit-Session-ID
"c0a82104523aa0a30000001f" to RADIUS Req
*Sep 19 07:00:23.149: EAP-AUTH-AAA-EVENT: Added Audit-Session-ID
*Sep 19 07:00:23.149: EAP-AUTH-AAA-EVENT: Adding IDB "0x38167B5C" to RADIUS
```

Req

```
*Sep 19 07:00:23.149: EAP-AUTH-AAA-EVENT: Added IDB
*Sep 19 07:00:23.149: EAP-AUTH-AAA-EVENT: Adding EAP profile name
"PEAPProfile" to RADIUS Req
*Sep 19 07:00:23.149: EAP-AUTH-AAA-EVENT: Added EAP profile name to request
*Sep 19 07:00:23.149: EAP-EVENT: Sending LL (Dot1x-Authenticator) event
'EAP_CUSTOMIZE_AAA_REQUEST' on handle 0x26000052
*Sep 19 07:00:23.149: EAP-AUTH-AAA-EVENT: eap_auth_aaa_authen_request_shim
aaa_service 19, eap aaa_list handle 0, mlist handle 0
*Sep 19 07:00:23.150: EAP-AUTH-AAA-EVENT: Request sent successfully
*Sep 19 07:00:23.150: eap_authen : during state eap_auth_aaa_req, got
event 24(eapAAReqOk)
*Sep 19 07:00:23.150: @@@ eap_authen : eap_auth_aaa_req -> eap_auth_aaa_idle
*Sep 19 07:00:23.150: EAP-EVENT: Received LL (AAA_LOCAL_EAP) event
'EAP_RX_PACKET' on handle 0xCE000053
*Sep 19 07:00:23.150: EAP-AUTH-RX-PAK: Code:RESPONSE ID:0xE Length:0x0048
Type:PEAP
*Sep 19 07:00:23.150: Payload: 011703010018E5BC67F95BDE2D2BF45C ...
*Sep 19 07:00:23.150: eap_authen : during state eap_auth_idle, got event
1(eapRxPacket)
*Sep 19 07:00:23.150: @@@ eap_authen : eap_auth_idle -> eap_auth_received
*Sep 19 07:00:23.150: EAP-AUTH-EVENT: EAP Response received by context
0xCE000053
*Sep 19 07:00:23.150: EAP-AUTH-EVENT: EAP Response type = Method (25)
*Sep 19 07:00:23.150: eap_authen : during state eap_auth_received, got
event 10(eapMethodData)
*Sep 19 07:00:23.150: @@@ eap_authen : eap_auth_received ->
eap_auth_method_response
*Sep 19 07:00:23.150: EAP-EVENT: Sending method (PEAP) event 'Receive Packet'
on handle 0xCE000053
*Sep 19 07:00:23.150: EAP-AUTH-EVENT: Waiting for asynchronous reply from
method (PEAP)
*Sep 19 07:00:23.150: eap_authen : during state eap_auth_method_response,
got event 15(eapMethodWaitReply)
*Sep 19 07:00:23.150: @@@ eap_authen : eap_auth_method_response ->
eap_auth_idle
*Sep 19 07:00:23.151: EAP-EVENT: Received LL (PEAP) event 'EAP_RX_PACKET' on
handle 0x99000054
*Sep 19 07:00:23.151: EAP-AUTH-RX-PAK: Code:RESPONSE ID:0xE Length:0x000A
Type:IDENTITY
*Sep 19 07:00:23.151: Payload: 746961676F
*Sep 19 07:00:23.151: eap_authen : during state eap_auth_idle, got event
1(eapRxPacket)
*Sep 19 07:00:23.151: @@@ eap_authen : eap_auth_idle -> eap_auth_received
*Sep 19 07:00:23.151: EAP-AUTH-EVENT: EAP Response received by context
0x99000054
*Sep 19 07:00:23.151: EAP-AUTH-EVENT: EAP Response type = Identity
*Sep 19 07:00:23.151: eap_authen : during state eap_auth_received, got
event 10(eapMethodData)
*Sep 19 07:00:23.151: @@@ eap_authen : eap_auth_received ->
eap_auth_method_response
*Sep 19 07:00:23.151: EAP-AUTH-EVENT: Received peer identity: tiago
*Sep 19 07:00:23.151: eap_authen : during state eap_auth_method_response,
got event 13(eapMethodEnd)
*Sep 19 07:00:23.151: @@@ eap_authen : eap_auth_method_response ->
eap_auth_select_action
*Sep 19 07:00:23.151: EAP-AUTH-EVENT: Using authentication mode: Local
*Sep 19 07:00:23.151: EAP-EVENT: Sending LL (PEAP) event
'EAP_GET_CREDENTIAL_PROFILE_FROM_USERNAME' on handle 0x99000054
*Sep 19 07:00:23.151: EAP-EVENT: Sending LL (AAA_LOCAL_EAP) event
'EAP_GET_CREDENTIAL_PROFILE_FROM_USERNAME' on handle 0xCE000053
*Sep 19 07:00:23.151: EAP-AUTH-EVENT: Waiting for asynchronous reply from LL
(AAA_LOCAL_EAP)
*Sep 19 07:00:23.151: EAP-AUTH-EVENT: Waiting for asynchronous reply from LL
```

(PEAP)

*Sep 19 07:00:23.152: EAP-EVENT: Local methods by EAP type: [006 026]

*Sep 19 07:00:23.152: eap_authen : during state eap_auth_select_action, got event 21(eapDecisionWait)

*Sep 19 07:00:23.152: @@@ eap_authen : eap_auth_select_action -> eap_auth_idle

*Sep 19 07:00:23.152: EAP-EVENT: Received LL (AAA_LOCAL_EAP) event 'EAP_LL_REPLY' on handle 0xCE000053

*Sep 19 07:00:23.152: EAP-AUTH-EVENT: Relaying LL response for context 0xCE000053

*Sep 19 07:00:23.152: EAP-AUTH-EVENT: Using credential profile name: tiago (0xCE000053)

*Sep 19 07:00:23.152: EAP-EVENT: Sending method (PEAP) event 'LL Response' on handle 0xCE000053

*Sep 19 07:00:23.152: EAP-EVENT: Received LL (PEAP) event 'EAP_LL_REPLY' on handle 0x99000054

*Sep 19 07:00:23.152: eap_authen : during state eap_auth_idle, got event 2(eapLLReply)

*Sep 19 07:00:23.152: @@@ eap_authen : eap_auth_idle -> eap_auth_select_action

*Sep 19 07:00:23.152: EAP-AUTH-EVENT: Using credential profile name: tiago (0x99000054)

*Sep 19 07:00:23.152: eap_authen : during state eap_auth_select_action, got event 20(eapDecisionPropose)

*Sep 19 07:00:23.152: @@@ eap_authen : eap_auth_select_action -> eap_auth_propose_method

*Sep 19 07:00:23.152: eap_authen : idle during state eap_auth_propose_method

*Sep 19 07:00:23.152: @@@ eap_authen : eap_auth_propose_method -> eap_auth_method_request

*Sep 19 07:00:23.152: EAP-AUTH-EVENT: Maximum EAP packet size: 1464

*Sep 19 07:00:23.152: EAP-EVENT: Sending method (GTC) event 'New Context' on handle 0x99000054

*Sep 19 07:00:23.153: EAP-EVENT: Sending method (GTC) event 'Receive Packet' on handle 0x99000054

*Sep 19 07:00:23.153: EAP-AUTH-EVENT: Method (GTC) state: Continue

*Sep 19 07:00:23.153: EAP-AUTH-EVENT: Method (GTC) decision: Unknown

*Sep 19 07:00:23.153: eap_authen : idle during state eap_auth_method_request

*Sep 19 07:00:23.153: @@@ eap_authen : eap_auth_method_request -> eap_auth_tx_packet

*Sep 19 07:00:23.153: EAP-AUTH-EVENT: Current method = 6

*Sep 19 07:00:23.153: eap_authen : idle during state eap_auth_tx_packet

*Sep 19 07:00:23.153: @@@ eap_authen : eap_auth_tx_packet -> eap_auth_idle

*Sep 19 07:00:23.153: EAP-AUTH-TX-PAK: Code:REQUEST ID:0xF Length:0x0005 Type:GTC

*Sep 19 07:00:23.153: EAP-EVENT: Sending LL (PEAP) event 'EAP_TX_PACKET' on handle 0x99000054

*Sep 19 07:00:23.153: EAP-EVENT: Received Method (PEAP) event 'EAP_METHOD_REPLY' on handle 0xCE000053

*Sep 19 07:00:23.153: eap_authen : during state eap_auth_idle, got event 4(eapMethodReply)

*Sep 19 07:00:23.153: @@@ eap_authen : eap_auth_idle -> eap_auth_method_response

*Sep 19 07:00:23.153: EAP-AUTH-EVENT: Handling asynchronous method response for context 0xCE000053

*Sep 19 07:00:23.153: EAP-AUTH-EVENT: EAP method state: Continue

*Sep 19 07:00:23.153: EAP-AUTH-EVENT: EAP method decision: Unknown

*Sep 19 07:00:23.153: eap_authen : during state eap_auth_method_response, got event 14(eapMethodContinue)

*Sep 19 07:00:23.153: @@@ eap_authen : eap_auth_method_response -> eap_auth_method_request

*Sep 19 07:00:23.153: eap_authen : idle during state

```
eap_auth_method_request
*Sep 19 07:00:23.153: @@@ eap_authen : eap_auth_method_request ->
eap_auth_tx_packet
*Sep 19 07:00:23.153: EAP-AUTH-EVENT: Current method = 25
*Sep 19 07:00:23.153: eap_authen : idle during state eap_auth_tx_packet
*Sep 19 07:00:23.153: @@@ eap_authen : eap_auth_tx_packet -> eap_auth_idle
*Sep 19 07:00:23.153: EAP-AUTH-TX-PAK: Code:REQUEST ID:0xF Length:0x002B
Type:PEAP
*Sep 19 07:00:23.153: Payload: 011703010020377AEA34B95C78A82976 ...
*Sep 19 07:00:23.153: EAP-EVENT: Sending LL (AAA_LOCAL_EAP) event
'EAP_TX_PACKET' on handle 0xCE000053
*Sep 19 07:00:23.154: EAP-EVENT: eap_aaa_reply
*Sep 19 07:00:23.154: EAP-AUTH-AAA-EVENT: Reply received session_label
BB000020
*Sep 19 07:00:23.154: EAP-AUTH-AAA-EVENT: Response contains EAP Message,
code: 1
*Sep 19 07:00:23.154: EAP-EVENT: Received AAA event 'EAP_AAA_RX_PACKET' on
handle 0x26000052
*Sep 19 07:00:23.154: EAP-AUTH-RX-AAA-PAK: Code:REQUEST ID:0xF Length:0x002B
Type:PEAP
*Sep 19 07:00:23.154: Payload: 011703010020377AEA34B95C78A82976 ...
*Sep 19 07:00:23.154: eap_authen : during state eap_auth_aaa_idle, got
event 5(eapAAARxPacket)
*Sep 19 07:00:23.154: @@@ eap_authen : eap_auth_aaa_idle -> eap_auth_aaa_resp
*Sep 19 07:00:23.154: eap_authen : idle during state eap_auth_aaa_resp
*Sep 19 07:00:23.154: @@@ eap_authen : eap_auth_aaa_resp ->
eap_auth_tx_packet2
*Sep 19 07:00:23.154: EAP-AUTH-EVENT: Current method = 25
*Sep 19 07:00:23.154: eap_authen : idle during state eap_auth_tx_packet2
*Sep 19 07:00:23.154: @@@ eap_authen : eap_auth_tx_packet2 -> eap_auth_idle2
*Sep 19 07:00:23.154: EAP-AUTH-TX-PAK: Code:REQUEST ID:0xF Length:0x002B
Type:PEAP
*Sep 19 07:00:23.154: Payload: 011703010020377AEA34B95C78A82976 ...
*Sep 19 07:00:23.154: EAP-EVENT: Started 'Authenticator Retransmit' timer
(30s) for EAP sesion handle 0x26000052
*Sep 19 07:00:23.154: EAP-EVENT: Started EAP tick timer
*Sep 19 07:00:23.154: EAP-EVENT: Sending LL (Dot1x-Authenticator) event
'EAP_TX_PACKET' on handle 0x26000052
*Sep 19 07:00:23.154: dot1x-sm:[6470.0227.0a89, Ca0] Posting EAP_REQ for
0x60000009
*Sep 19 07:00:23.154: dot1x_auth_bend Ca0: during state auth_bend_response,
got event 7(eapReq)
*Sep 19 07:00:23.154: @@@ dot1x_auth_bend Ca0: auth_bend_response ->
auth_bend_request
*Sep 19 07:00:23.154: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:exiting
response state
*Sep 19 07:00:23.871: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:response
request action
*Sep 19 07:00:24.114: dot1x-packet:[6470.0227.0a89, Ca0] Queuing an EAPOL pkt
on Authenticator Q
*Sep 19 07:00:24.114: dot1x-packet:EAPOL pak rx - Ver: 0x3 type: 0x0
*Sep 19 07:00:24.114: dot1x-packet: length: 0x0048
*Sep 19 07:00:24.114: dot1x-ev:[Ca0] Dequeued pkt: Int Ca0 CODE= 2,TYPE= 25,
LEN= 72
*Sep 19 07:00:24.114: dot1x-ev:[Ca0] Received pkt saddr =6470.0227.0a89 ,
daddr = 64d8.146f.e5a0, pae-ether-type = 888e.0300.0048
*Sep 19 07:00:24.115: dot1x-packet:EAPOL pak rx - Ver: 0x3 type: 0x0
*Sep 19 07:00:24.115: dot1x-packet: length: 0x0048
*Sep 19 07:00:24.115: dot1x-sm:[6470.0227.0a89, Ca0] Posting EAPOL_EAP for
0x60000009
*Sep 19 07:00:24.115: dot1x_auth_bend Ca0: during state auth_bend_request,
got event 6(eapolEap)
*Sep 19 07:00:24.115: @@@ dot1x_auth_bend Ca0: auth_bend_request ->
```

```
auth_bend_response
*Sep 19 07:00:24.115: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:entering
response state
*Sep 19 07:00:24.115: dot1x-ev:[6470.0227.0a89, Ca0] Response sent to the
server from 0x60000009
*Sep 19 07:00:24.115: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:request
response action
*Sep 19 07:00:24.115: EAP-EVENT: Received LL (Dot1x-Authenticator) event
'EAP_RX_PACKET' on handle 0x26000052
*Sep 19 07:00:24.115: EAP-AUTH-RX-PAK: Code:RESPONSE ID:0x12 Length:0x0048
Type:PEAP
*Sep 19 07:00:24.115: Payload: 0117030100186DEF131BC85E44CBDD50 ...
*Sep 19 07:00:24.115: eap_authen : during state eap_auth_idle2, got
event 1(eapRxPacket)
*Sep 19 07:00:24.115: @@@ eap_authen : eap_auth_idle2 -> eap_auth_received2
*Sep 19 07:00:24.115: EAP-AUTH-EVENT: EAP Response received by context
0x26000052
*Sep 19 07:00:24.115: EAP-AUTH-EVENT: EAP Response type = Method (25)
*Sep 19 07:00:24.115: EAP-EVENT: Stopping 'Authenticator Retransmit' timer
for EAP sesion handle 0x26000052
*Sep 19 07:00:24.115: eap_authen : during state eap_auth_received2, got
event 10(eapMethodData)
*Sep 19 07:00:24.115: @@@ eap_authen : eap_auth_received2 -> eap_auth_aaa_req
*Sep 19 07:00:24.116: EAP-AUTH-AAA-EVENT: Adding Audit-Session-ID
"c0a82104523aa0a30000001f" to RADIUS Req
*Sep 19 07:00:24.116: EAP-AUTH-AAA-EVENT: Added Audit-Session-ID
*Sep 19 07:00:24.116: EAP-AUTH-AAA-EVENT: Adding IDB "0x38167B5C" to
RADIUS Req
*Sep 19 07:00:24.116: EAP-AUTH-AAA-EVENT: Added IDB
*Sep 19 07:00:24.116: EAP-AUTH-AAA-EVENT: Adding EAP profile name
"PEAPProfile" to RADIUS Req
*Sep 19 07:00:24.116: EAP-AUTH-AAA-EVENT: Added EAP profile name to request
*Sep 19 07:00:24.116: EAP-EVENT: Sending LL (Dot1x-Authenticator) event
'EAP_CUSTOMIZE_AAA_REQUEST' on handle 0x26000052
*Sep 19 07:00:24.116: EAP-AUTH-AAA-EVENT: eap_auth_aaa_authen_request_shim
aaa_service 19, eap aaa_list handle 0, mlist handle 0
*Sep 19 07:00:24.116: EAP-AUTH-AAA-EVENT: Request sent successfully
*Sep 19 07:00:24.116: eap_authen : during state eap_auth_aaa_req, got
event 24(eapAAAReqOk)
*Sep 19 07:00:24.116: @@@ eap_authen : eap_auth_aaa_req -> eap_auth_aaa_idle
*Sep 19 07:00:24.116: EAP-EVENT: Received LL (AAA_LOCAL_EAP) event
'EAP_RX_PACKET' on handle 0xCE000053
*Sep 19 07:00:24.116: EAP-AUTH-RX-PAK: Code:RESPONSE ID:0x12 Length:0x0048
Type:PEAP
*Sep 19 07:00:24.117: Payload: 0117030100186DEF131BC85E44CBDD50 ...
*Sep 19 07:00:24.117: eap_authen : during state eap_auth_idle, got event
1(eapRxPacket)
*Sep 19 07:00:24.117: @@@ eap_authen : eap_auth_idle -> eap_auth_received
*Sep 19 07:00:24.117: EAP-AUTH-EVENT: EAP Response received by context
0xCE000053
*Sep 19 07:00:24.117: EAP-AUTH-EVENT: EAP Response type = Method (25)
*Sep 19 07:00:24.117: eap_authen : during state eap_auth_received, got
event 10(eapMethodData)
*Sep 19 07:00:24.117: @@@ eap_authen : eap_auth_received ->
eap_auth_method_response
*Sep 19 07:00:24.117: EAP-EVENT: Sending method (PEAP) event 'Receive Packet'
on handle 0xCE000053
*Sep 19 07:00:24.117: EAP-AUTH-EVENT: Waiting for asynchronous reply from
method (PEAP)
*Sep 19 07:00:24.117: eap_authen : during state eap_auth_method_response,
got event 15(eapMethodWaitReply)
*Sep 19 07:00:24.117: @@@ eap_authen : eap_auth_method_response ->
eap_auth_idle
*Sep 19 07:00:24.118: EAP-EVENT: Received Method (PEAP) event
```


'EAP_METHOD_REPLY' on handle 0xCE000053

*Sep 19 07:00:24.118: eap_authen : during state eap_auth_idle, got event 4(eapMethodReply)

*Sep 19 07:00:24.118: @@@ eap_authen : eap_auth_idle -> eap_auth_method_response

*Sep 19 07:00:24.118: EAP-AUTH-EVENT: Handling asynchronous method response for context 0xCE000053

*Sep 19 07:00:24.118: EAP-EVENT: Sending LL (AAA_LOCAL_EAP) event 'EAP_KEY_AVAILABLE' on handle 0xCE000053

*Sep 19 07:00:24.118: EAP-AUTH-EVENT: EAP method state: Done

*Sep 19 07:00:24.118: EAP-AUTH-EVENT: EAP method decision: Unconditional Success

*Sep 19 07:00:24.118: eap_authen : during state eap_auth_method_response, got event 13(eapMethodEnd)

*Sep 19 07:00:24.118: @@@ eap_authen : eap_auth_method_response -> eap_auth_select_action

*Sep 19 07:00:24.118: eap_authen : during state eap_auth_select_action, got event 18(eapDecisionSuccess)

*Sep 19 07:00:24.118: @@@ eap_authen : eap_auth_select_action -> eap_auth_success

*Sep 19 07:00:24.118: EAP-EVENT: Received get canned status from lower layer (0xCE000053)

***Sep 19 07:00:24.118: EAP-AUTH-TX-PAK: Code:SUCCESS ID:0x12 Length:0x0004**

*Sep 19 07:00:24.118: EAP-EVENT: Sending method (PEAP) event 'Free Context' on handle 0xCE000053

***Sep 19 07:00:24.119: EAP-EVENT: Sending LL (AAA_LOCAL_EAP) event 'EAP_SUCCESS' on handle 0xCE000053**

*Sep 19 07:00:24.119: EAP-EVENT: Received free context (0xCE000053) from LL (AAA_LOCAL_EAP)

*Sep 19 07:00:24.119: EAP-EVENT: eap_aaa_reply

*Sep 19 07:00:24.119: EAP-AUTH-AAA-EVENT: Reply received session_label BB000020

*Sep 19 07:00:24.119: EAP-AUTH-AAA-EVENT: Response contains EAP Message, code: 3

*Sep 19 07:00:24.119: EAP-AUTH-AAA-EVENT: Response contains MS MPPE Send Key, length:139

*Sep 19 07:00:24.119: EAP-AUTH-AAA-EVENT: Response contains MS MPPE Recv Key, length:97

*Sep 19 07:00:24.119: EAP-EVENT: Sending LL (Dot1x-Authenticator) event 'EAP_KEY_AVAILABLE' on handle 0x26000052

*Sep 19 07:00:24.119: EAP-AUTH-AAA-EVENT: Authorization not required for this context

*Sep 19 07:00:24.119: EAP-EVENT: Received LL (AAA_LOCAL_EAP) event 'EAP_DELETE' on handle 0xCE000053

*Sep 19 07:00:24.119: EAP-AUTH-AAA-ERROR: Failed to delete aaa coord transaction for 0xCE000053

*Sep 19 07:00:24.119: EAP-AUTH-EVENT: Freed EAP auth context

*Sep 19 07:00:24.119: EAP-EVENT: Freed EAP context

***Sep 19 07:00:24.120: EAP-EVENT: Received AAA event 'EAP_AAA_SUCCESS' on handle 0x26000052**

*Sep 19 07:00:24.120: eap_authen : during state eap_auth_aaa_idle, got event 7(eapAAASuccess)

*Sep 19 07:00:24.120: @@@ eap_authen : eap_auth_aaa_idle -> eap_auth_success

*Sep 19 07:00:24.120: EAP-AUTH-TX-PAK: Code:SUCCESS ID:0x12 Length:0x0004

*Sep 19 07:00:24.120: EAP-AUTH-EVENT: SUCCESS for EAP method ID: 25, name: PEAP, on handle 0x26000052

*Sep 19 07:00:24.120: EAP-EVENT: Sending LL (Dot1x-Authenticator) event 'EAP_SUCCESS' on handle 0x26000052

*Sep 19 07:00:24.120: dot1x-packet:[6470.0227.0a89, Ca0] Received an EAP Success

*Sep 19 07:00:24.120: dot1x-sm:[6470.0227.0a89, Ca0] Posting EAP_SUCCESS for 0x60000009

*Sep 19 07:00:24.120: dot1x_auth_bend Ca0: during state auth_bend_response, got event 11(eapSuccess)

*Sep 19 07:00:24.120: @@@ dot1x_auth_bend Ca0: auth_bend_response ->
auth_bend_success

*Sep 19 07:00:24.120: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:exiting
response state

*Sep 19 07:00:24.120: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:entering
success state

*Sep 19 07:00:24.120: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:response
success action

*Sep 19 07:00:24.120: dot1x_auth_bend Ca0: idle during state
auth_bend_success

*Sep 19 07:00:24.121: @@@ dot1x_auth_bend Ca0: auth_bend_success ->
auth_bend_idle

*Sep 19 07:00:24.121: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:entering
idle state

*Sep 19 07:00:24.121: dot1x-sm:[6470.0227.0a89, Ca0] Posting AUTH_SUCCESS on
Client 0x60000009

*Sep 19 07:00:24.121: dot1x_auth Ca0: during state auth_authenticating,
got event 12(authSuccess_portValid)

*Sep 19 07:00:24.121: @@@ dot1x_auth Ca0: auth_authenticating ->
auth_authc_result

*Sep 19 07:00:24.121: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:exiting
authenticating state

*Sep 19 07:00:24.121: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:entering
authc result state

*Sep 19 07:00:24.121: dot1x-ev:[6470.0227.0a89, Ca0] Sending EAPOL success
immediately

*Sep 19 07:00:24.121: dot1x-ev:[6470.0227.0a89, Ca0] Sending EAPOL packet

*Sep 19 07:00:24.121: dot1x-packet:[6470.0227.0a89, Ca0] Platform changed
src mac of EAPOL packet

*Sep 19 07:00:24.121: dot1x-registry:registry:dot1x_ether_macaddr called

*Sep 19 07:00:24.121: dot1x-packet:EAPOL pak Tx - Ver: 0x3 type: 0x0

*Sep 19 07:00:24.121: dot1x-packet: length: 0x0004

*Sep 19 07:00:24.121: dot1x-packet:EAP code: 0x3 id: 0x12 length: 0x0004

*Sep 19 07:00:24.121: dot1x-packet:[6470.0227.0a89, Ca0] EAPOL packet sent
to client 0x60000009

*Sep 19 07:00:24.122: dot1x-ev:[6470.0227.0a89, Ca0] Received Authz Success
for the client 0x60000009 (6470.0227.0a89)

***Sep 19 07:00:24.122: dot1x-sm:[6470.0227.0a89, Ca0] Posting AUTHZ_SUCCESS
on Client 0x60000009**

*Sep 19 07:00:24.122: dot1x_auth Ca0: during state auth_authc_result,
got event 23(authzSuccess)

*Sep 19 07:00:24.122: @@@ dot1x_auth Ca0: auth_authc_result ->
auth_authenticated

*Sep 19 07:00:24.122: dot1x-sm:[6470.0227.0a89, Ca0] 0x60000009:entering
authenticated state

*Sep 19 07:00:24.122: dot1x-ev:[6470.0227.0a89, Ca0] EAPOL success packet
was sent earlier.

*Sep 19 07:00:24.122: EAP-EVENT: Received free context (0x26000052) from LL
(Dot1x-Authenticator)

*Sep 19 07:00:24.122: EAP-EVENT: Received LL (Dot1x-Authenticator) event
'EAP_DELETE' on handle 0x26000052

*Sep 19 07:00:24.123: EAP-AUTH-AAA-ERROR: Failed to delete aaa coord
transaction for 0x26000052

*Sep 19 07:00:24.123: EAP-AUTH-EVENT: Freed EAP auth context

*Sep 19 07:00:24.123: EAP-EVENT: Freed EAP context

*Sep 19 07:00:24.122: 6470.0227.0A89
client incoming attribute size are 304 1 wcm: pemDelScb Event skipping
delete

***Sep 19 07:00:24.636: 6470.0227.0A89 192.168.80.100 8021X_REQD (3) Change
state to L2AUTHCOMPLETE (4) last state RUN (20)**
1 wcm: ^K4D8.146F.E5A

*Sep 19 07:00:24.636: 6470.0227.0A89 WCDB_CHANGE: 1 wcm: Client 1 m_vlan 80
Radio iif id 0xdf0f4000000005 bssid iif id 0xcd248000000015,
bssid 64D8.146F.E5A0

*Sep 19 07:00:24.636: 6470.0227.0A89 WCDB_AUTH: 1 wcm: Adding opt82 len 0
*Sep 19 07:00:24.636: 6470.0227.0A89 WCDB_CHANGE: 1 wcm: Suppressing SPI
(L2 Auth for reassoc) pemstate 4 state L2_AUTH(1) vlan 80 client_id
0xde51c000000021 mob 1 ackflag 2 dropd 0
*Sep 19 07:00:24.636: 6470.0227.0A89 192.168.80.100 L2AUTHCOMPLETE (4)
pemAdvanceState2: 1 wcm: MOBILITY-COMPLETE with state 4.
*Sep 19 07:00:24.636: 6470.0227.0A89 Send request to EPM 1 wcm: UTHCOMPLETE
(4) pemAdvanceState2: MOBILITY-COMPLETE with state 4.
*Sep 19 07:00:24.649: 6470.0227.0A89 Received _EPM_SPI_STATUS_SUCCESS for
request sent for client 1 wcm: for client
*Sep 19 07:00:24.649: 6470.0227.0A89 Post-auth policy ACK recvd from EPM,
unset flag on MSCB 1 wcm: ient
*Sep 19 07:00:24.907: EAP-EVENT: Stopped EAP tick timer