

如何在離開網路的電子郵件上標籤頁尾/免責宣告？

目錄

問題：

如何為特定使用者組在離開網路的電子郵件上標籤頁尾/免責宣告？

許多組織都希望對來自其電子郵件系統的傳出郵件設定頁尾。這通常是出於法律原因，例如向郵件新增免責宣告或警告收件人郵件包含受保護的通訊。在AsyncOS中，這稱為「頁尾標籤」。

頁尾印章是一個相當不精確的藝術，通常只適用於外發郵件。這是因為許多郵件具有複雜的結構，如HTML或Microsoft Word正文部分，在這些正文部分新增頁尾可能是可能的，也可能不可能。頁尾標籤有兩個步驟。首先建立頁尾。然後，以三種方式之一將頁尾新增到郵件中。

1. 首先建立頁尾。在GUI中，導航至Mail Policies -> Text Resources，然後點選Add Text Resource
2. 建立一個沒有條件的傳出內容過濾器（這樣，它將被應用到郵件策略中的所有郵件），並使用您建立的頁尾執行「新增頁尾」操作
3. 在策略中啟用頁尾標籤篩選器。

提示：雖然頁尾標籤可以在監聽程式上完成，也可以使用消息過濾器或內容過濾器完成，但針對特定使用者組執行此操作的最簡單方法就是使用內容過濾器。

還可以使用郵件過濾器新增郵件頁尾：

```
AddOutgoingDisclaimer:
if      (recv-listener == "OutboundMail")
and (mail-from == ("@exchange\\.example\\.com$")) {
  add-footer("Disclaimer");
}
```

您還可以向特定監聽程式上接收的所有消息新增頁尾。 例如：

```
smtp.scu.com>listenerconfig
```

```
Currently configured listeners:
```

1. InboundMail (on PublicNet, 192.35.195.42) SMTP TCP Port 25 Public
2. OutboundMail (on Privatenet, 172.20.0.142) SMTP TCP Port 25 Private

```
Choose the operation you want to perform:
```

- NEW - Create a new listener.
- EDIT - Modify a listener.
- DELETE - Remove a listener.
- SETUP - Change global settings.

[]> edit

Enter the name or number of the listener you wish to edit.

[]> 2

Name: OutboundMail
Type: Private
Interface: Privatenet (172.20.0.142/24) TCP Port 25
Protocol: SMTP
Default Domain:
Max Concurrency: 600 (TCP Queue: 50)
Domain Map: Disabled
TLS: No
SMTP Authentication: Disabled
Bounce Profile: Default
Footer: None
LDAP: Off

Choose the operation you want to perform:

- NAME - Change the name of the listener.
- INTERFACE - Change the interface.
- LIMITS - Change the injection limits.
- SETUP - Configure general options.
- HOSTACCESS - Modify the Host Access Table.
- BOUNCECONFIG - Choose the bounce profile to use for messages injected on this listener.
- MASQUERADE - Configure the Domain Masquerading Table.
- DOMAINMAP - Configure domain mappings.
- LDAPACCEPT - Configure an LDAP query to determine whether a recipient address should be accepted or bounced/dropped.

[]> setup

Enter the default domain for email addresses without a fully qualified domain name.

Enter the word "DELETE" to clear the setting and disable the addition of a default domain.

[]>

Would you like the system to add a received header to each message received on this listener? [Y]>

Would you like to enable SenderBase Reputation Filters and IP Profiling support? [N]>

Would you like to attach a footer to all mail on this listener? [N]> y

1. Disclaimer

[1]>

Name: OutboundMail
Type: Private
Interface: Privatenet (172.20.0.142/24) TCP Port 25
Protocol: SMTP
Default Domain:
Max Concurrency: 600 (TCP Queue: 50)
Domain Map: Disabled
TLS: No
SMTP Authentication: Disabled
Bounce Profile: Default
Footer: Disclaimer
LDAP: Off

Choose the operation you want to perform:

- NAME - Change the name of the listener.
 - INTERFACE - Change the interface.
 - LIMITS - Change the injection limits.
 - SETUP - Configure general options.
 - HOSTACCESS - Modify the Host Access Table.
 - BOUNCECONFIG - Choose the bounce profile to use for messages injected on this listener.
 - MASQUERADE - Configure the Domain Masquerading Table.
 - DOMAINMAP - Configure domain mappings.
 - LDAPACCEPT - Configure an LDAP query to determine whether a recipient address should be accepted or bounced/dropped.
- []>

Currently configured listeners:

1. InboundMail (on PublicNet, 192.168.195.42) SMTP TCP Port 25 Public
2. OutboundMail (on Privatenet, 172.20.0.142) SMTP TCP Port 25 Private

Choose the operation you want to perform:

- NEW - Create a new listener.
 - EDIT - Modify a listener.
 - DELETE - Remove a listener.
 - SETUP - Change global settings.
- []>

smtp.scu.com>commit

Please enter some comments describing your changes:

[]> add outgoing Disclaimer on OutboundMail listener

Changes committed: Tue Nov 23 19:48:47 2004 MST

提示：在較新版本的AsyncOS中，您還可以在郵件上方新增免責宣告