

# ESA是否可將SMTP流量傳送到除25以外的其他埠號？

## 目錄：

### 問題：

ESA是否可將SMTP流量傳送到除25以外的其他埠號？

埠25是標準SMTP埠郵件交換伺服器用於偵聽傳入電子郵件。可以將ESA配置為通過備用埠將郵件傳送到特定主機。其 `smtproutes` cli 中的指令是設定此指令的最簡單方式：

```
mail3.example.com> smtproutes
```

```
There are no routes configured.
```

```
Choose the operation you want to perform:
```

- NEW - Create a new route.
  - IMPORT - Import new routes from a file.
- ```
[ ]> new
```

```
Enter the hostname for which you want to set up a permanent route.
```

```
Partial hostnames such as ".example.com" are allowed.
```

```
Use "ALL" for the default route.
```

```
[ ]> testexchange.example.com
```

```
Enter the destination hosts, separated by commas, which you want mail for  
testexchange.ironport.com to be delivered.
```

```
Enter /dev/null by itself if you wish to discard the mail.
```

```
[ ]> exchange.example.com:1025
```

```
Mapping for testexchange.ironport.com to exchange.example.com:1025 created.
```

```
There are currently 1 routes configured.
```

```
Choose the operation you want to perform:
```

- NEW - Create a new route.
  - DELETE - Remove a route.
  - PRINT - Display all routes.
  - IMPORT - Import new routes from a file.
  - EXPORT - Export all routes to a file.
  - CLEAR - Remove all routes.
- ```
[ ]>
```

```
> commit
```

```
Please enter some comments describing your changes:
```

```
[ ]> testing the new exchange server on an alternate port
```

```
Changes committed: Mon Mar 28 14:20:06 2005 PST  
mail3.example.com>
```

在這種情況下，系統配置為通過埠1025將testexchange.example.com的郵件傳送到exchange.example.com。

您也可以通過GUI、網路 —>SMTP路由 —>新增SMTP路由並使用所需埠填寫域和目的主機，進行上述更改。完成之後，您必須提交和提交更改。

要配置ESA以使用裝置GUI通過備用埠將郵件傳送到特定主機，請選擇Network > IP Interface並修改IP介面的設定。