



INDEX

Symbols

* (asterisk)

- autolearned entries **45-14**
- first operational port **36-16**
- port security wildcards **45-10**

Numerics

- 1-Gigabit speed
 - configuring **5-5**

A

AAA

- accounting **16-2**
- authentication **16-2**
- authorization **16-2**
- benefits **16-2**
- configuration process **16-7**
- configuring **16-6 to 16-12**
- default settings **16-13**
- description **16-1**
- DHCHAP authentication **44-9**
- enabling MSCHAP authentication **16-9**
- example configuration **16-13**
- field descriptions **16-1**
- guidelines **16-6**
- limitations **16-6**
- monitoring TACACS+ servers **18-3**
- prerequisites **16-5**
- TACACS+ server groups **17-15, 18-8, 18-14**
- user login process **16-4**

- verifying configurations **16-13**
- AAA accounting
 - adding rule methods **16-1**
 - changing rule methods **16-1**
 - configuring default methods **16-10**
 - deleting rule methods **16-1**
 - rearranging rule methods **16-1**
- AAA accounting logs
 - clearing **16-12**
 - displaying **16-12**
- AAA authentication rules
 - adding methods **16-1**
 - changing methods **16-1**
 - deleting methods **16-1**
 - rearranging methods **16-1**
- AAA login authentication
 - configuring console methods **16-7**
 - configuring default methods **16-8**
- AAA logins
 - enabling authentication failure messages **16-8**
- AAA protocols
 - RADIUS **16-1**
 - TACACS+ **16-1**
- AAA server groups
 - description **16-3**
- AAA servers
 - specifying SNMPv3 parameters **16-11, 16-12**
 - specifying user roles **16-12**
 - specifying user roles in VSAs **16-11**
- AAA services
 - configuration options **16-3**
 - remote **16-2**
 - security **16-1**

Send feedback to nx5000-docfeedback@cisco.com

- accounting
 - description **16-2**
 - active zone sets
 - considerations **38-4**
 - enabling distribution **38-13**
 - address allocation cache
 - description **33-20**
 - administrative speeds
 - configuring **32-10**
 - administrative states
 - description **32-5**
 - setting **32-9**
 - administrators
 - default passwords **3-10**
 - aging time
 - accelerated
 - for MSTP **9-21**
 - maximum
 - for MSTP **9-22**
 - authentication
 - description **16-2**
 - fabric security **44-1**
 - local **16-2**
 - methods **16-3**
 - remote **16-2**
 - user login **16-4**
 - authentication, authorization, and accounting. See AAA
 - authorization
 - description **16-2**
 - user login **16-4**
 - auto mode
 - configuring **32-10**
 - auto port mode
 - description **32-4**
 - autosensing speed **32-10**
-
- B**
 - BB_credits
 - bit errors
 - reasons **32-11**
 - bit error thresholds
 - configuring **32-11**
 - description **32-11**
 - blocking state, STP **8-12**
 - BPDU guard
 - See STP BPDU guard
 - bridge ID
 - See STP bridge ID
 - broadcast storms
 - see traffic-storm control
 - Brocade
 - native interop mode **43-9**
 - buffer-to-buffer credits. See BB_credits
 - build fabric frames
 - description **33-3**
-
- C**
 - Call Home
 - description **26-1, 27-1**
 - message format options **26-2**
 - call home
 - smart call home feature **26-4**
 - Call Home destination profiles
 - attributes **26-8**
 - Call Home messages
 - configuring levels **26-4**
 - format options **26-2**
 - call home notifications
 - full-txt format for syslog **26-19**
 - XML format for syslog **26-19**
 - CDP
 - configuring **5-6**

Send feedback to nx5000-docfeedback@cisco.com

CFS
 configuring for NTP **3-17**

Cisco
 vendor ID **16-11, 17-3**

cisco-av-pair
 specifying AAA user parameters **16-11, 16-12**

CIST regional root
 See MSTP

CIST root
 See MSTP

community ports **7-3**

community VLANs **7-2, 7-3**

company IDs
 FC ID allocations **43-7**

configuring LACP **11-10**

configuring NPV **34-6**

consoles
 configuring AAA login authentication methods **16-7**

Contiguous Domain ID Assignments
 About **33-13**

D

daylight saving time
 adjusting for **3-14**

dead time intervals
 configuring for FSPF **40-7**
 description **40-7**

debounce timer **5-4**
 configuring **5-7**

default settings
 AAA **16-13**
 RBAC **22-10**
 rollback **23-4**

default users
 description **3-9**

default VSANs
 description **37-8**

default zones

configuring access permissions **38-10**
 configuring policies **38-8**
 description **38-9**
 interoperability **43-10**
 policies **38-10**

destination IDs
 exchange based **36-3**
 flow based **36-3**
 in-order delivery **40-10**
 path selection **37-10**

device alias databases
 committing changes **39-6**
 disabling distribution **39-7**
 discarding changes **39-6**
 distribution to fabric **39-5**
 enabling distribution **39-7**
 locking the fabric **39-6**
 merging **39-8**
 overriding fabric locks **39-7**

device aliases
 comparison with zones (table) **39-2**
 creating **39-3**
 creating (procedure) **39-6**
 default settings **39-10**
 description **39-1**
 displaying information **39-9**
 displaying zone set information **39-9**
 enhanced mode **39-4**
 features **39-1**
 import legacy zone aliases **39-8**
 modifying databases **39-2**
 requirements **39-2**
 using **39-8**
 zone alias conversion **39-8**

device IDs
 call home format **26-16**

DHCHAP
 AAA authentication **44-9**

Send feedback to nx5000-docfeedback@cisco.com

- authentication modes **44-4**
 - compatibility with other NX-OS features **44-3**
 - configuring **44-3**
 - configuring AAA authentication **44-9**
 - default settings **44-11**
 - description **44-2**
 - displaying security information **44-9**
 - enabling **44-4**
 - group settings **44-6**
 - hash algorithms **44-5**
 - passwords for local switches **44-6**
 - passwords for remote devices **44-7**
 - sample configuration **44-9**
 - timeout values **44-8**
 - See also FC-SP **44-1**
 - diagnostics
 - configuring **24-3**
 - default settings **24-4**
 - expansion modules **24-3**
 - health monitoring **24-2**
 - runtime **24-2**
 - Diffie-Hellman Challenge Handshake Authentication Protocol. See DHCHAP
 - documentation
 - additional publications **1-ii**
 - related documents **1-ii**
 - domain IDs
 - allowed lists **33-9**
 - assignment failures **32-7**
 - configuring allowed lists **33-10**
 - configuring CFS distribution **33-10, 33-13**
 - configuring fcalias members **38-10**
 - contiguous assignments **33-13**
 - description **33-7**
 - distributing **33-1**
 - enabling contiguous assignments **33-13**
 - interoperability **43-10**
 - preferred **33-9**
 - static **33-9**
 - domain manager
 - fast restart feature **33-3**
 - isolation **32-7**
 - drop latency time
 - configuring **40-13**
 - configuring for FSPF in-order delivery **40-14**
 - displaying information **40-14**
-
- E**
 - EFMD
 - displaying statistics **46-7**
 - fabric binding **46-1**
 - fabric binding initiation **46-3**
 - EISLs
 - port channel links **36-1**
 - e-mail notifications
 - Call Home **26-1**
 - enhanced zones
 - advantages over basic zones **38-18**
 - changing from basic zones **38-19**
 - configuring default full database distribution **38-23**
 - configuring default policies **38-22**
 - configuring default switch-wide zone policies **38-23**
 - default settings **38-24**
 - description **38-18**
 - displaying information **38-23**
 - enabling **38-20**
 - merging databases **38-21**
 - modifying database **38-20**
 - E port mode
 - classes of service **32-3**
 - description **32-3**
 - E ports
 - configuring **32-9**
 - fabric binding checking **46-2**
 - FCS support **47-1**
 - FSPF topologies **40-1**
 - isolation **32-7**

Send feedback to nx5000-docfeedback@cisco.com

- recovering from link isolations **38-14**
- trunking configuration **35-3**
- ethanalyzer **50-3**
- examples
 - AAA configurations **16-13**
- Exchange Fabric Membership Data. See EFMD
- exchange IDs
 - in-order delivery **40-10**
 - load balancing **50-5**
 - path selection **37-10**
- exchange link parameter. See ELP
- executing a session **23-3**
- expansion port mode. See E port mode
- extended range VLANs
 - See VLANs

F

- fabric binding
 - activation **46-4**
 - checking for E ports **46-2**
 - checking for TE ports **46-2**
 - clearing statistics **46-6**
 - compatibility with DHCHAP **44-3**
 - copying to config database **46-5**
 - copying to configuration file (procedure) **46-6**
 - creating config database (procedure) **46-6**
 - default settings **46-7**
 - deleting databases **46-6**
 - deleting from config database (procedure) **46-6**
 - description **46-1**
 - disabling **46-3**
 - EFMD **46-1**
 - enabling **46-3**
 - enforcement **46-2**
 - forceful activation **46-5**
 - forceful deactivation **46-5**
 - initiation process **46-3**
 - licensing requirements **46-1**
 - port security comparison **46-1**
 - saving to config database **46-5**
 - sWWN lists **46-4**
 - verifying status **46-3**
 - viewing active databases (procedure) **46-6**
 - viewing EFMD statistics (procedure) **46-6**
 - viewing violations (procedure) **46-6**
- Fabric Configuration Servers. See FCSs
- Fabric-Device Management Interface. See FDMI
- fabric login. See FLOGI
- fabric port mode. See F port mode
- fabric pWWNs
 - zone membership **38-2**
- fabric reconfiguration
 - fcdomain phase **33-1**
- fabrics
 - See also build fabric frames
- fabrics. See RCFs;build fabric frames **33-3**
- fabric security
 - authentication **44-1**
 - default settings **44-11**
- Fabric Shortest Path First. See FSPF
- fabric WWNs. See fWWNs
- fault tolerant fabrics
 - example (figure) **40-2**
- fcaliases
 - adding members **38-11**
 - cloning **38-16**
 - configuring for zones **38-10**
 - creating **38-11**
 - renaming **38-16**
 - using **39-8**
- fcdomains
 - autoreconfigured merged fabrics **33-6**
 - configuring CFS distribution **33-10, 33-13**
 - default settings **33-20**
 - description **33-1**
 - disabling **33-5**
 - displaying information **33-18, 33-19**

Send feedback to nx5000-docfeedback@cisco.com

- domain IDs [33-7](#)
- domain manager fast restart [33-3](#)
- displaying statistics [33-20](#)
- enabling [33-5](#)
- enabling autoreconfiguration [33-6](#)
- incoming RCFs [33-5](#)
- initiation [33-5](#)
- overlap isolation [32-7](#)
- restarts [33-3](#)
- switch priorities [33-4](#)
- FC IDs
 - allocating [33-1, 43-6](#)
 - allocating default company ID lists [43-7](#)
 - allocation for HBAs [43-6](#)
 - configuring fcalias members [38-10](#)
 - description [33-14](#)
 - persistent [33-14](#)
- fcping
 - default settings [50-16](#)
 - invoking [50-7](#)
 - verifying switch connectivity [50-7](#)
- FC-SP
 - authentication [44-1](#)
 - enabling [44-4](#)
 - enabling on ISLs [44-9](#)
 - See also DHCHAP [44-1](#)
- FCSSs
 - characteristics [47-2](#)
 - configuring names [47-2](#)
 - creating platform using Device Manager [47-4](#)
 - default settings [47-4](#)
 - description [47-1](#)
 - displaying fabric ports using Device Manager [47-4](#)
 - displaying information [47-3](#)
- fc timers
 - displaying configured values [43-4](#)
 - distribution [43-3](#)
- fctrace
 - default settings [50-16](#)
- invoking [50-5](#)
- FDMI
 - description [41-4](#)
 - displaying database information [41-4](#)
- Fibre Channel
 - sWWNs for fabric binding [46-4](#)
 - timeout values [43-1](#)
 - TOVs [43-2](#)
- Fibre Channel domains. See fcdomains
- Fibre Channel interfaces
 - administrative states [32-5](#)
 - BB_credits [32-6](#)
 - configuring [32-8](#)
 - configuring auto port mode [32-10](#)
 - configuring bit error thresholds [32-11](#)
 - configuring descriptions [32-9](#)
 - configuring frame encapsulation [32-11](#)
 - configuring port modes [32-9](#)
 - configuring speeds [32-10](#)
 - default settings [32-17](#)
 - deleting from port channels [36-11](#)
 - disabling [32-9](#)
 - displaying information [32-15](#)
 - displaying VSAN membership [37-7](#)
 - enabling [32-9](#)
 - operational states [32-5](#)
 - reason codes [32-5](#)
 - states [32-4](#)
 - See also interfaces [32-4](#)
- Fibre Channel Security Protocol. See FC-SP
- field descriptions
 - AAA [16-1](#)
 - TACACS+ [18-14](#)
- FLOGI
 - description [41-1](#)
 - displaying details [41-1](#)
- flow statistics
 - clearing [40-15](#)
 - counting [40-15](#)

Send feedback to nx5000-docfeedback@cisco.com

- description **40-15**
- displaying **40-16**
- forward-delay time
 - MSTP **9-21**
- F port mode
 - classes of service **32-4**
 - description **32-3**
- F ports
 - configuring **32-9**
 - description **32-3**
 - See also Fx ports
- frame encapsulation
 - configuring **32-11**
- FSCN
 - displaying databases **42-3**
- FSPF
 - clearing counters **40-9**
 - clearing VSAN counters **40-5**
 - computing link cost **40-6**
 - configuring globally **40-3**
 - configuring Hello time intervals **40-6**
 - configuring link cost **40-6**
 - configuring on a VSAN **40-4**
 - configuring on interfaces **40-5**
 - dead time intervals **40-7**
 - default settings **40-16**
 - description **40-1**
 - disabling **40-5**
 - disabling on interfaces **40-8**
 - disabling routing protocols **40-5**
 - displaying database information **40-16**
 - displaying global information **40-16**
 - enabling **40-5**
 - fault tolerant fabrics **40-2**
 - in-order delivery **40-10**
 - interoperability **43-11**
 - link state record defaults **40-3**
 - reconvergence times **40-2**
 - redundant links **40-2**
 - resetting configuration **40-4**
 - resetting to defaults **40-4**
 - retransmitting intervals **40-7**
 - routing services **40-1**
 - topology examples **40-2**
 - FSPF routes
 - configuring **40-9**
 - description **40-9**
 - full zone sets
 - considerations **38-4**
 - enabling distribution **38-13**
 - fWWNs
 - configuring fcalias members **38-10**
 - Fx ports
 - VSAN membership **37-4**

G

- GOLD diagnostics
 - configuring **24-3**
 - expansion modules **24-3**
 - health monitoring **24-2**
 - runtime **24-2**
 - graces period alerts
 - licenses **4-8**
-

H

- hard zoning
 - description **38-12**
- HBA ports
 - configuring area FCIDs **33-16**
- HBAs
 - FC ID allocations **43-6**
- health monitoring diagnostics
 - information **24-2**
- hello time
 - MSTP **9-21**

Send feedback to nx5000-docfeedback@cisco.com

- Hello time intervals
 - configuring for FSPF **40-6**
 - description **40-6**
- host ports
 - kinds of **7-3**

- I**
- IDs
 - Cisco vendor ID **16-11, 17-3**
 - serial IDs **26-16**
- IEEE 802.1w
 - See RSTP
- indirect link failures
 - recovering **48-1**
- in-order delivery
 - configuring drop latency time **40-13**
 - displaying status **40-13**
 - enabling for VSANs **40-12**
 - enabling globally **40-12**
 - guidelines **40-12**
 - reordering network frames **40-11**
 - reordering port channel frames **40-11**
- interfaces
 - 1-Gigabit speed
 - configuring **5-5**
 - adding to port channels **36-9, 36-10**
 - assigning to VSANs **37-7**
 - CDP
 - configuring **5-6**
 - configuring descriptions **32-9**
 - configuring fcalias members **38-11**
 - configuring receive data field size **32-11**
 - debounce timer
 - configuring **5-7**
 - deleting from port channels **36-11**
 - displaying information **32-15**
 - displaying SFP information **32-16**
 - forced addition to port channels **36-11**
- isolated states **36-10**
- SFP types **32-15**
- suspended states **36-10**
- UDLD
 - configuring **5-4**
 - defined **5-2**
 - VSAN membership **37-6**
- interface speed **5-4**
- interface statistics
 - description **32-15**
- interoperability
 - configuring interop mode 1 **43-10**
 - description **43-9**
 - verifying status **43-12**
 - VSANs **37-11**
- interop modes
 - configuring mode 1 **43-10**
 - default settings **43-15**
 - description **43-9**
- IOD. See in-order delivery
- ISLs
 - port channel links **36-1**
- isolated port **7-3**
- isolated VLANs **7-2, 7-3**
- isolated VSANs
 - description **37-8**
 - displaying membership **37-8**

- L**
- LACP **11-1, 11-10**
 - system ID **11-5**
- license key files
 - description **4-2**
 - installing key files **4-4**
 - updating **4-4**
- licenses
 - backing up **4-5**
 - claim certificates **4-1**

Send feedback to nx5000-docfeedback@cisco.com

displaying information **4-5**
evaluation **4-2**
grace period alerts **4-8**
grace period expiration **4-8**
grace periods **4-2**
host IDs **4-1**
identifying features in use **4-6**
incremental **4-2**
installation options **4-2**
installing key files **4-4**
installing manually **4-3**
missing **4-2**
node-locked **4-1**
obtaining factory-installed **4-3**
obtaining key files **4-4**
PAK **4-2**
permanent **4-2**
terminology **4-1**
transferring between switches **4-9**
uninstalling **4-6**
updating **4-7**
Link Aggregation Control Protocol **11-1**
link costs
 configuring for FSPF **40-6**
 description **40-6**
Link Failure
 detecting unidirectional **8-14, 9-8**
link failures
 recovering **48-1**
load balancing
 attributes **37-10**
 attributes for VSANs **37-5**
 configuring **37-10**
 description **36-2, 37-10**
 guarantees **37-10**
 port channels **36-1**
logical unit numbers. See LUNs
LUNs
 displaying discovered SCSI targets **42-3**

M

MAC addresses
 configuring secondary **43-6**
management access
 description **3-12**
management interfaces
 displaying information **3-21**
 using force option during shutdown **3-21**
management interfaces. See mgmt0 interfaces
maximum aging time
 MSTP **9-22**
maximum hop count, MSTP **9-22**
McData
 native interop mode **43-9**
merged fabrics
 autoreconfigured **33-6**
mgmt0 interfaces
 configuring **3-20**
 description **3-19**
Microsoft Challenge Handshake Authentication Protocol.
See MSCHAP
MSCHAP
 enabling authentication **16-9**
MST
 CIST regional root **9-5**
 setting to default values **9-14**
MSTP
 boundary ports
 described **9-7**
 CIST, described **9-4**
 CIST regional root **9-5**
 CIST root **9-6**
 configuring
 forward-delay time **9-21**
 hello time **9-21**
 maximum aging time **9-22**
 maximum hop count **9-22**
 MST region **9-13**

Send feedback to nx5000-docfeedback@cisco.com

- port priority [9-18, 9-19](#)
- root switch [9-16](#)
- secondary root switch [9-17](#)
- switch priority [9-20](#)
- CST
 - defined [9-4](#)
 - operations between regions [9-5](#)
 - enabling the mode [9-13](#)
- IEEE 802.1s
 - terminology [9-6](#)
- IST
 - defined [9-4](#)
 - master [9-5](#)
 - operations within a region [9-4](#)
- mapping VLANs to MST instance [9-14](#)
- MST region
 - CIST [9-4](#)
 - configuring [9-13](#)
 - described [9-2](#)
 - hop-count mechanism [9-7](#)
 - IST [9-4](#)
 - supported spanning-tree instances [9-2](#)
- multicast storms
 - see traffic-storm control

- N
- name servers
 - displaying database entries [41-3](#)
 - interoperability [43-11](#)
 - LUN information [42-1](#)
 - proxy feature [41-2](#)
 - registering proxies [41-2](#)
 - rejecting duplicate pWWNs [41-2](#)
- Network Time Protocol. See NTP
- NPIV
 - description [32-13](#)
 - enabling [32-14](#)
- NP links [34-2](#)
- N port identifier virtualization. See NPIV
- N ports
 - FCS support [47-1](#)
 - fctrace [50-5](#)
 - hard zoning [38-12](#)
 - zone enforcement [38-12](#)
 - zone membership [38-2](#)
 - See also Nx ports
- NP-ports [34-1](#)
- NPV, configuring [34-6](#)
- NTP
 - configuration guidelines [3-16](#)
 - configuring [3-15](#)
 - configuring CFS distribution [3-17](#)

- O
- operational states
 - configuring on Fibre Channel interfaces [32-9](#)
 - description [32-5](#)

- P
- passwords
 - administrator [3-8](#)
 - default for administrators [3-10](#)
 - DHCHAP [44-6, 44-7](#)
 - setting administrator default [3-9](#)
 - strong characteristics [22-2](#)
- persistent FC IDs
 - configuring [33-15](#)
 - description [33-14](#)
 - displaying [33-19](#)
 - enabling [33-15](#)
 - purging [33-18](#)
- PLOGI
 - name server [41-3](#)
- Port Channel

Send feedback to nx5000-docfeedback@cisco.com

- STP [11-1](#)
- port channeling [11-1](#)
- port channel modes
 - description [36-7](#)
- PortChannel Protocol
 - converting autocreated groups to manually configured [36-15](#)
- port channel Protocol
 - autocreation [36-14](#)
 - creating channel group [36-13](#)
 - description [36-12](#)
- port channel protocol
 - configuring autocreation [36-15](#)
 - enabling autocreation [36-15](#)
- PortChannels
 - default settings [36-17](#)
 - show tech-support port-channel command [50-14](#)
 - verifying configurations [36-16, 36-17](#)
- port channels
 - adding interfaces [36-9, 36-10](#)
 - administratively down [32-7](#)
 - comparison with trunking [36-2](#)
 - compatibility checks [36-10](#)
 - compatibility with DHCHAP [44-3](#)
 - configuration guidelines [36-6](#)
 - configuring [36-9](#)
 - configuring Fibre Channel routes [40-9](#)
 - deleting [36-8](#)
 - deleting interfaces [36-11](#)
 - description [36-1](#)
 - forcing interface additions [36-11](#)
 - in-order guarantee [40-12](#)
 - interface states [36-10](#)
 - interoperability [43-10](#)
 - link changes [40-11](#)
 - link failures [40-2](#)
 - load balancing [36-2](#)
 - misconfiguration error detection [36-6](#)
- PortFast BPDU filtering
 - See STP PortFast BPDU filtering
- port modes
 - auto [32-4](#)
- port priority
 - MSTP [9-18, 9-19](#)
- ports
 - VSAN membership [37-6](#)
- port security
 - activating [45-5](#)
 - activation [45-2](#)
 - activation rejection [45-6](#)
 - adding authorized pairs [45-11](#)
 - auto-learning [45-2](#)
 - compatibility with DHCHAP [44-3](#)
 - configuration guidelines [45-3](#)
 - configuring CFS distribution [45-12](#)
 - configuring manually without auto-learning [45-9](#)
 - deactivating [45-5](#)
 - default settings [45-19](#)
 - deleting entries from database (procedure) [45-12](#)
 - disabling [45-5](#)
 - displaying configuration [45-18](#)
 - displaying settings (procedure) [45-7](#)
 - displaying statistics (procedure) [45-7](#)
 - displaying violations (procedure) [45-7](#)
 - enabling [45-5](#)
 - enforcement mechanisms [45-2](#)
 - fabric binding comparison [46-1](#)
 - forcing activation [45-6](#)
 - license requirement [45-1](#)
 - preventing unauthorized accesses [45-1](#)
 - WWN identification [45-10](#)
 - port security auto-learning
 - authorization examples [45-8](#)
 - description [45-2](#)
 - device authorization [45-8](#)
 - disabling [45-8](#)
 - distributing configuration [45-13](#)
 - enabling [45-7](#)

Send feedback to nx5000-docfeedback@cisco.com

- guidelines for configuring with CFS **45-3**
 - guidelines for configuring without CFS **45-4**
 - port security databases
 - cleaning up **45-18**
 - copying **45-17**
 - copying active to config (procedure) **45-7**
 - deleting **45-18**
 - displaying configuration **45-19**
 - interactions **45-15**
 - manual configuration guidelines **45-4**
 - merge guidelines **45-14**
 - reactivating **45-6**
 - scenarios **45-15**
 - port speeds
 - configuring **32-10**
 - port tracking
 - default settings **48-7**
 - description **48-1**
 - displaying information **48-6**
 - enabling **48-3**
 - guidelines **48-2**
 - monitoring ports in a VSAN **48-5**
 - multiple ports **48-4**
 - shutting down ports forcefully **48-5**
 - port world wide names. See pWWNs
 - preshared keys
 - TACACS+ **18-3**
 - primary VLANs **7-2**
 - principal switches
 - assigning domain ID **33-9**
 - configuring **33-10**
 - private VLANs
 - community VLANs **7-2, 7-3**
 - end station access to **7-5**
 - isolated VLANs **7-2, 7-3**
 - ports
 - community **7-3**
 - isolated **7-3**
 - promiscuous **7-3**
 - primary VLANs **7-2**
 - secondary VLANs **7-2**
 - promiscuous ports **7-3**
 - proxies
 - registering for name servers **41-2**
 - pWWNs
 - configuring fcalias members **38-10**
 - rejecting duplicates **41-2**
 - zone membership **38-2**
-
- R**
 - RADIUS
 - configuring global preshared keys **17-6**
 - configuring servers **17-4 to 17-13**
 - configuring timeout intervals **17-9**
 - configuring transmission retry counts **17-9**
 - default settings **17-15**
 - description **17-1 to 17-4**
 - example configurations **17-15**
 - network environments **17-1**
 - operation **17-2**
 - prerequisites **17-4**
 - specifying server at login **17-9**
 - verifying configuration **17-14**
 - VSAAs **17-3**
 - RADIUS server groups
 - configuring **17-8**
 - RADIUS servers
 - configuring accounting attributes **17-11**
 - configuring authentication attributes **17-11**
 - configuring dead-time intervals **17-13**
 - configuring hosts **17-5**
 - configuring periodic monitoring **17-12**
 - configuring preshared keys **17-7**
 - configuring timeout interval **17-10**
 - configuring transmission retry count **17-10**
 - deleting hosts **17-13**
 - displaying statistics **17-14**

Send feedback to nx5000-docfeedback@cisco.com

- example configurations **17-15**
- manually monitoring **17-13**
- monitoring **17-2**
- verifying configuration **17-14**
- Rapid Spanning Tree Protocol
 - See RSTP
- RBAC
 - default settings **22-10**
- RCFs
 - description **33-3**
 - incoming **33-5**
 - rejecting incoming **33-6**
- read-only zones
 - default settings **38-24**
- reason codes
 - description **32-5**
- reconfigure fabric frames. See RCFs
- reduced MAC address **8-3**
- redundancy
 - VSANs **37-4**
- redundant physical links
 - example (figure) **40-2**
- Registered State Change Notifications. See RSCNs
- reserved-range VLANs
 - See VLANs
- retransmitting intervals
 - configuring for FSPF **40-8**
 - description **40-7**
- roles
 - authentication **22-1**
- rollback
 - checkpoint copy **23-1**
 - creating a checkpoint copy **23-1**
 - default settings **23-4**
 - deleting a checkpoint file **23-1**
 - description **23-1**
 - example configuration **23-1**
 - guidelines **23-1**
 - high availability **23-1**
 - implementing a rollback **23-1**
 - limitations **23-1**
 - reverting to checkpoint file **23-1**
 - verifying configuration **23-4**
 - root guard
 - See STP root guard
 - root switch
 - MSTP **9-16**
 - route costs
 - computing **40-6**
 - RSCNs
 - clearing statistics **41-6**
 - default settings **41-10**
 - description **41-4**
 - displaying information **41-5**
 - multiple port IDs **41-5**
 - suppressing domain format SW-RSCNs **41-6**
 - RSCN timers
 - configuration distribution using CFS **41-7**
 - configuring **41-6**
 - displaying configuration **41-7**
 - RSTP
 - active topology **8-10**
 - BPDU
 - processing **8-14**
 - designated port, defined **8-10**
 - designated switch, defined **8-10**
 - proposal-agreement handshake process **8-7**
 - rapid convergence **8-7**
 - point-to-point links **8-7**
 - root ports **8-7**
 - root port, defined **8-10**
 - See also MSTP
 - runtime checks
 - static routes **40-9**
 - runtime diagnostics
 - information **24-2**

Send feedback to nx5000-docfeedback@cisco.com

S

scalability

 VSANs [37-4](#)

SCSI

 displaying LUN discovery results [42-3](#)

SCSI LUNs

 customized discovery [42-2](#) discovering targets [42-1](#) displaying information [42-2](#) starting discoveries [42-1](#)

SD port mode

 description [32-4](#) interface modes [32-4](#)

SD ports

 configuring [32-9](#)

secondary MAC addresses

 configuring [43-6](#)secondary VLANs [7-2](#)

serial IDs

 description [26-16](#)

server groups. See AAA server groups

server IDs

 description [26-17](#)session manager [23-3](#) committing a session [23-3](#) configuring ACLs [23-2](#) configuring an ACL session (example) [23-3](#) creating a session [23-2](#) description [23-1](#) discarding a session [23-3](#) guidelines [23-1](#) limitations [23-1](#) saving a session [23-3](#) verifying configuration [23-4](#) verifying the session [23-3](#)

SFPs

 displaying transmitter types [32-16](#) transmitter types [32-15](#)

small computer system interface. See SCSI

smart call home

 description [26-4](#) registration requirements [26-5](#) Transport Gateway (TG) aggregation point [26-5](#)

SMARTnet

 smart call home registration [26-5](#)

SNMP

 access groups [27-4](#) assigning contact [27-11](#) assigning location [27-11](#) configuring LinkUp/LinkDown notifications [27-10](#), [27-11](#) group-based access [27-4](#) server contact name [26-5](#) user synchronization with CLI [27-4](#) Version 3 security features [27-2](#)

SNMP (Simple Network Management Protocol)

versions

 security models and levels [27-2](#)

SNMPv3

 assigning multiple roles [27-6](#) security features [27-2](#) specifying AAA parameters [16-11](#) specifying parameters for AAA servers [16-12](#)

soft zoning

 description [38-12](#)

See also zoning

source IDs

 call home event format [26-16](#) exchange based [36-3](#) flow based [36-3](#) in-order delivery [40-10](#) path selection [37-10](#)

SPAN

 egress sources [49-1](#) sources for monitoring [49-1](#)

SPAN destination port mode. See SD port mode

SPAN sources

Send feedback to nx5000-docfeedback@cisco.com

- egress **49-1**
- ingress **49-1**
- SPF
 - computational hold times **40-3**
- SSH
 - generating server key-pairs **19-1**
- static routes
 - runtime checks **40-9**
- statistics
 - TACACS+ **18-13**
- storage devices
 - access control **38-1**
- STP
 - edge ports **8-7, 10-2**
 - network ports **10-2**
 - normal ports **10-2**
 - Port Channel **11-1**
 - PortFast **8-7, 10-2**
 - port types **10-2**
 - understanding
 - Blocking State **8-12**
 - disabled state **8-13**
 - forwarding state **8-12**
 - learning state **8-12**
 - root bridge election **8-5**
 - STP bridge ID **8-3**
 - STP root guard **10-5**
 - summer time
 - adjusting for **3-14**
 - Switched Port Analyzer. See SPAN
 - switch ports
 - configuring attribute default values **32-13**
 - switch priorities
 - configuring **33-4**
 - default **33-4**
 - description **33-4**
 - switch priority
 - MSTP **9-20**
 - sWWNs
- configuring for fabric binding **46-4**
- T**
- TACACS+
 - advantages over RADIUS **18-2**
 - configuring **18-4, 18-13**
 - configuring global preshared keys **18-6**
 - configuring global timeout interval **18-9**
 - description **18-1**
 - disabling **18-13**
 - displaying statistics **18-13**
 - enabling **18-5**
 - example configurations **18-14**
 - field descriptions **18-14**
 - global preshared keys **18-3**
 - limitations **18-4**
 - prerequisites **18-3**
 - preshared key **18-3**
 - specifying TACACS+ servers at login **18-9**
 - user login operation **18-2**
 - verifying configuration **18-14**
- TACACS+ server
 - configuring dead-time interval **18-12**
- TACACS+ servers
 - configuration process **18-4**
 - configuring hosts **18-5, 18-13**
 - configuring periodic monitoring **18-11**
 - configuring preshared keys **18-7**
 - configuring server groups **17-15, 18-8, 18-14**
 - configuring TCP ports **18-10**
 - configuring timeout interval **18-10**
 - displaying statistics **18-13**
 - field descriptions **18-14**
 - manually monitoring **18-13**
 - monitoring **18-3**
 - verifying configuration **18-14**
- TCP ports
- TACACS+ servers **18-10**

Send feedback to nx5000-docfeedback@cisco.com

- TE port mode
 - classes of service **32-4**
 - description **32-4**
 - TE ports
 - fabric binding checking **46-2**
 - FCS support **47-1, 47-2**
 - fctrace **50-6**
 - FSPF topologies **40-1**
 - interoperability **43-10**
 - recovering from link isolations **38-14**
 - trunking restrictions **35-1**
 - timeout values. See TOVs
 - TOVs
 - configuring across all VSANs **43-2**
 - configuring for a VSAN **43-2**
 - default settings **43-15**
 - interoperability **43-10**
 - ranges **43-1**
 - tracked ports
 - binding operationally **48-3**
 - traffic isolation
 - VSANs **37-4**
 - trap notifications **27-2**
 - troubleshooting
 - collecting output for technical support **50-8**
 - fcping **50-6**
 - fctrace **50-5**
 - show tech-support command **50-8**
 - verifying switch connectivity **50-7**
 - trunk-allowed VSAN lists
 - description **35-4**
 - trunking
 - comparison with port channels **36-2**
 - configuration guidelines **35-1**
 - configuring modes **35-3**
 - default settings **35-7**
 - description **35-1**
 - displaying information **35-6**
 - interoperability **43-10**
 - link state **35-3**
 - merging traffic **35-2**
 - restrictions **35-1**
 - trunking E port mode. See TE port mode
 - trunking ports
 - associated with VSANs **37-7**
 - trunking protocol
 - default settings **35-7**
 - default state **35-2**
 - description **35-2**
 - detecting port isolation **35-2**
 - trunk mode
 - administrative default **32-14**
 - configuring **35-3, 35-4**
 - default settings **35-7**
 - trunk ports
 - displaying information **35-7**
-
- U**
 - UDLD
 - aggressive mode **5-3**
 - configuring **5-4**
 - defined **5-2**
 - nonaggressive mode **5-3**
 - unicast storms
 - see traffic-storm control
 - Unidirectional Link Detection. See UDLD.
 - unique area FC IDs
 - configuring **33-16**
 - description **33-16**
 - user accounts
 - password characteristics **22-2**
 - user login
 - authentication process **16-4**
 - authorization process **16-4**
 - user logins
 - configuring AAA login authentication methods **16-8**
 - user roles

Send feedback to nx5000-docfeedback@cisco.com

- specifying on AAA servers **16-11, 16-12**
- users
 - description **22-1**

- V**
 - vendor-specific attributes. See VSAs
 - Virtual Fibre Channel interfaces
 - default settings **32-17**
 - VLANs
 - extended range **6-2**
 - reserved range **6-2**
 - VTP domain **6-3**
 - VSAN IDs
 - allowed list **35-7**
 - description **37-5**
 - multiplexing traffic **32-4**
 - range **37-4**
 - VSAN membership **37-4**
 - VSANs
 - advantages **37-3**
 - allowed-active **35-1**
 - cache contents **33-20**
 - comparison with zones (table) **37-4**
 - compatibility with DHCHAP **44-3**
 - configuring **37-6**
 - configuring allowed-active lists **35-6**
 - configuring FSPF **40-3**
 - configuring trunk-allowed lists **35-4, 35-6**
 - default settings **37-11**
 - default VSANs **37-8**
 - deleting **37-9**
 - description **37-1**
 - displaying configuration **37-11**
 - displaying membership **37-7**
 - displaying usage **37-11**
 - domain ID automatic reconfiguration **33-6**
 - FC IDs **37-1**
 - FCS support **47-1**
- features **37-1**
- flow statistics **40-14**
- FSPF **40-4**
- FSPF connectivity **40-1**
- interop mode **43-10**
- isolated **37-8**
- load balancing **37-10**
- load balancing attributes **37-5**
- mismatches **32-7**
- multiple zones **38-5**
- names **37-5**
- name server **41-2**
- operational states **37-8**
- port membership **37-6**
- port tracking **48-5**
- states **37-5**
- TE port mode **32-4**
- timer configuration **43-2**
- TOVs **43-2**
- traffic isolation **37-3**
- trunk-allowed **35-1**
- trunking ports **37-7**
- VSAs
 - format **16-12**
 - protocol options **16-12, 17-4**
 - support description **16-11**
- VTP
 - domains
 - VLANs **6-3**

- W**
 - world wide names. See WWNs
 - WWNs
 - configuring **43-5**
 - displaying information **43-5**
 - link initialization **43-6**
 - port security **45-10**
 - secondary MAC addresses **43-6**

Send feedback to nx5000-docfeedback@cisco.com

suspended connections [32-7](#)

Z

zone aliases

conversion to device aliases [39-8](#)

importing [39-8](#)

zone attribute groups

cloning [38-16](#)

zone databases

migrating a non-MDS database [38-17](#)

release locks [38-21](#)

zone members

adding to zones [38-8](#)

converting to pWWN members [38-11](#)

displaying information [38-9](#)

zones

access control [38-9](#)

adding to zone sets [38-11](#)

adding zone members [38-8](#)

analyzing [38-24](#)

backing up (procedure) [38-16](#)

changing from enhanced zones [38-20](#)

cloning [38-16](#)

compacting for downgrading [38-23](#)

comparison with device aliases (table) [39-2](#)

comparison with VSANs (table) [37-4](#)

configuring [38-11](#)

configuring aliases [38-10](#)

configuring fcaliases [38-10](#)

default policies [38-2](#)

default settings [38-24](#)

displaying information [38-17](#)

editing full zone databases [38-8](#)

enforcing restrictions [38-12](#)

exporting databases [38-14](#)

features [38-1, 38-4](#)

importing databases [38-14](#)

membership using pWWNs [37-4](#)

merge failures [32-7](#)

renaming [38-16](#)

restoring (procedure) [38-16](#)

show tech-support zone command [50-12](#)

viewing information [38-18](#)

See also default zones

See also enhanced zones

See also hard zoning;soft zoning [38-12](#)

See also zoning;zone sets [38-2](#)

zone server databases

clearing [38-17](#)

zone sets

activating [38-9](#)

adding member zones [38-11](#)

analyzing [38-24](#)

cloning [38-16](#)

configuring [38-8](#)

considerations [38-4](#)

copying [38-15](#)

creating [38-8, 38-11](#)

default settings [38-24](#)

displaying information [38-17](#)

distributing configuration [38-13](#)

enabling distribution [38-13](#)

exporting [38-15](#)

exporting databases [38-14](#)

features [38-1](#)

importing [38-15](#)

importing databases [38-14](#)

one-time distribution [38-13](#)

recovering from link isolations [38-14](#)

renaming [38-16](#)

viewing information [38-18](#)

See also active zone sets

See also active zone sets;full zone sets [38-5](#)

See also zones;zoning [38-2](#)

zoning

description [38-1](#)

example [38-3](#)

Send feedback to nx5000-docfeedback@cisco.com

implementation [38-4](#)

See also zones;zone sets [38-1](#)

Send feedback to nx5000-docfeedback@cisco.com