



A

- access control list (ACL) [3-10, 3-26](#)
- aggressive VAD [3-8](#)
- arbitration algorithm [2-14](#)
- Assured Forwarding [3-20](#)
- assured forwarding 31 (AF31) [3-9](#)
- Asynchronous Transfer Mode (ATM) [5-3](#)
- Asynchronous Transfer Mode Peak Cell Rate (ATM PCR) [3-4](#)
- ATM and Frame Relay Service Inter-Working (SIW) [5-3](#)
- audience, for this document [vii](#)
- audio quality [3-2](#)

B

- bandwidth
 - codec affect on [3-4](#)
 - consumption [3-5](#)
 - for unicast connection trunk [5-21](#)
 - issues [3-3](#)
 - leased lines [3-19](#)
 - modifying consumption [3-6](#)
 - multicast over GRE [5-12](#)
 - over-provisioning [3-11](#)
 - planning [3-3](#)
 - PMC consumption of [3-6](#)
 - point-to-point lines [3-19](#)
 - provisioning [3-2](#)
 - usage [3-5](#)
 - voice payload [3-7](#)
- bearer channel [2-9](#)
- bidirectional PIM [3-2, 3-3, 3-16](#)

bridging channels

See also mixing

- broadcast queue [3-13](#)
- buffering [3-11](#)
- burst [3-4, 3-11](#)

C

- call flow [2-24](#)
- call leg [4-1, 4-4](#)
- Carrier Operated Relay (COR) [3-7](#)
- Carrier Operated Squelch (COR) [3-7](#)
- Cisco CallManager Express [2-27, 2-28](#)
- Cisco Hoot 'n' Holler
 - channel mixing [2-13](#)
 - use with LMR [2-27](#)
- Cisco IPICS
 - benefits [1-1](#)
 - codec [3-4](#)
 - components
 - Cisco IPICS server [1-3](#)
 - Cisco Unified IP Phone gateway [1-4](#)
 - LMR gateway [1-4](#)
 - networking components [1-4](#)
 - overview [1-2](#)
 - PMC [1-3](#)
 - RMS [1-4, 2-1](#)
 - deployment models [5-1](#)
 - markets [1-1](#)
 - multiple site model [5-2](#)
 - overview [1-1](#)
 - RMS configuration for mixing [2-15](#)
 - single site model [5-1](#)

- voice streams supported [2-9](#)
- Cisco IPICS server [1-3](#)
- Cisco IP Interoperability and Collaboration System
 - See Cisco IPICS
- Cisco Multicast Manager (CMM) [3-27](#)
- Cisco Security Agent (CSA) [3-25](#)
- Cisco Unified CallManager [2-27](#)
- Cisco Unified IP Phone
 - Cisco CallManager Express configuration for [2-28](#)
 - Cisco Unified CallManager configuration for [2-27](#)
 - configuring for Cisco IPICS [2-27](#)
 - overview [1-4](#)
 - services [2-27](#)
- Class-Based Weighted Fair Queuing (CBWFQ) [3-10](#)
- codec
 - bandwidth use [3-4, 3-5](#)
 - choosing [3-4](#)
 - considerations [3-4](#)
 - delay [3-4](#)
 - G.711 [3-4](#)
 - G.729a [3-4](#)
 - types in Cisco IPICS [3-4](#)
 - voice quality [3-4](#)
- Committed Information Rate (CIR) [3-4, 3-11, 3-12](#)
- compressed RTP (cRTP) [3-5](#)
- connection trunk [5-13](#)
- cRTP [3-6](#)
- Customer Edge Router (CE) [5-4](#)

D

- Data MDT [5-5, 5-9](#)
- Data Multicast Distribution Tree (MDT) [5-4](#)
- Default-MDT [5-4, 5-5](#)
- delay [3-9, 3-11](#)
- dense mode (SM) [3-2](#)
- destination pattern [4-3](#)
- dial peer
 - associated with RMS [2-11](#)

- call leg [4-1, 4-4](#)
- configuration example [2-23](#)
- destination pattern [4-3](#)
- inbound [4-2](#)
- inbound call leg [4-4](#)
- matching inbound call leg [4-4](#)
- matching outbound call leg [4-4](#)
- outbound [4-2](#)
- outbound call leg [4-4](#)
- overview [4-1](#)
- POTS [4-2](#)
- session target [4-3](#)
- VoATM (Voice over ATM) [4-2](#)
- VoFR (Voice over Frame Relay) [4-2](#)
- voice-network [4-2](#)
- Voice over IP (VoIP) [4-2](#)
- digital signal processor (DSP) [3-7, 3-8](#)
- discard eligible (DE) [3-11, 3-20](#)
- DS0
 - allocation [2-2](#)
 - channel optimization [2-9](#)
 - loopback channels [2-2](#)
 - remote location requirements [2-8](#)
 - resource allocation [2-8, 2-22](#)
 - resource consumption [2-6, 2-7, 2-20](#)
 - resources [2-19](#)
 - resources not required [2-19](#)
 - use in mixing channels [2-11](#)
- DSCP per-hop behaviors (Fibs) [3-20](#)
- DSP
 - channel optimization [2-9](#)
 - signal detection [3-8](#)
- dspfarm [2-9](#)
- duplicate packets [2-19](#)

E

- E1 interface [2-10](#)
- ear and mouth (E&M)

interface 2-27
 port 3-13

egress policing 3-20

egress shaping 3-20

endpoints
 communication between 2-6, 2-10
 duplicate packets 2-19

expedited forwarding (EF) 3-9

F

firewall 3-26

following 2-3

Frame Relay
 broadcast queue 3-13
 Committed Information Rate (CIR) in 3-12
 connection with E&M port 3-13
 in WAN 5-3
 IP RTP Priority 3-10
 LLQ 3-10
 QoS 3-11

Frame Relay Traffic Shaping (FRTS) 3-12

FRF.12 fragmentation and reassembly technique 3-19

G

G.711 3-4, 5-2

G.729a 3-4

GRE tunnel 5-11

H

High-Level Data Link Control (HDLC) 3-19

hootie
 See Cisco Hoot 'n' Holler

Internet Group Management Protocol (IGMP) 2-16

interoperability and collaboration 1-2

IOS
 arbitration algorithm 2-14
 queuing techniques 3-9

IP precedence 3-9

IP RTP Priority 3-9, 3-10

IPSec VPN 5-13

J

jitter 3-2, 3-9, 3-11, 3-12

L

land mobile radio
 See LMR

LEAF 5-4

leased line 5-3

Link Fragmentation and Interleaving (LFI) 3-19

LMR
 channel 2-15
 communication with endpoints 2-15
 endpoints in 2-8
 gateway 2-27
 use with Cisco Hoot 'n' Holler 2-27

loopback 2-1, 2-2, 2-10

loopback interface 3-16

Low-Latency Queuing (LLQ) 3-9, 3-10, 3-12

M

M1:U12:M2
 connection trunk 5-16
 description 5-13
 unicast connection trunk 3-6, 5-18

- with multicast singularities [5-22](#)
- markets, for Cisco IPICS [1-1](#)
- mixing
 - arbitration algorithm [2-14](#)
 - audio [2-16](#)
 - channels in VTG [2-10](#)
 - channels using Cisco Hoot 'n' Holler [2-13](#)
 - DSP function [3-8](#)
 - example [2-14](#)
 - unicast streams [2-22](#)
 - voice streams [2-16, 3-8](#)
- MPLS
 - in multiple site model [5-2](#)
 - VPN [5-3](#)
 - with multicast VPN [5-3](#)
- multicast [2-22, 3-6, 5-2](#)
 - address [2-8](#)
 - for VTG communication [2-10](#)
 - bandwidth [5-12](#)
 - bidirectional PIM [3-16](#)
 - call flow to unicast [2-26](#)
 - endpoints, communication between [2-6](#)
 - GRE tunnel [5-24](#)
 - island
 - overview [5-10](#)
 - topology [5-10](#)
 - M1:U12:M2 connection trunk [5-24](#)
 - output stream [2-13](#)
 - over GRE [5-11](#)
 - singularity
 - GRE tunnel [5-22](#)
 - M1:U12:M2 connection trunk [5-22](#)
 - overview [5-21](#)
- multicast address
 - guidelines for using [3-24](#)
- multicast address pool [2-2, 3-25](#)
- multicast domain [5-2, 5-4, 5-5](#)
- Multicast Virtual Route Forwarding (MVRF) [5-4](#)
- multicast VPN (MVPN) [5-4](#)

- provider network configuration for [5-5](#)
- provider network verification [5-7](#)
- routing [5-5](#)
- Multilink Point-to-Point Protocol (MLPPP) [3-19](#)
- multiple site model
 - connectivity options [5-3](#)
 - overview [5-2](#)
 - topology [5-3](#)
- Multiprotocol Label Switching
 - See* MPLS

N

- network
 - management [3-26](#)
 - security in [3-25](#)
- networking components, overview [1-4](#)

O

- over-detection [3-7](#)
- over-provisioning [3-11](#)

P

- packet
 - buffering [3-11](#)
 - delay [3-9](#)
 - discard-eligible (DE) [3-11](#)
 - drop [3-11](#)
 - errors [3-2](#)
 - loss [3-2, 3-9, 3-12](#)
- packet rate [3-13](#)
- Permanent Virtual Circuit (PVC) [3-3](#)
- PIM-SSM [5-4](#)
- Plain Old Telephone Service (POTS), for unicast connection [2-24](#)
- PMC
 - bandwidth consumption [3-6](#)

overview 1-3
 remote location 2-22, 3-2, 3-21
 remote user 2-22
 point-to-point connection 3-19
 Point-to-Point Protocol (PPP) 3-19
 policing 3-20
 Protocol Independent Multicast (PIM)
 bidirectional 3-2, 3-3
 dense mode (DM) 3-2
 overview 3-2
 sparse mode (SM) 3-2
 Provider Edge Router (PE) 5-4, 5-5
 Provider Router (P) 5-4
 proxy channel 5-15
 Push-to-Talk Management Center
 See PMC

Q

QoS

at WAN edge 3-20
 factors affecting 3-9
 in enterprise 3-21
 in Frame Relay network 3-11
 in LAN 3-20
 in multiple site model 5-3
 overview 3-8, 3-9
 policing 3-20
 queuing 3-21
 recommendations for networks 3-9
 trust boundary 3-21
 WAN, use in 3-1
 with point-to-point connections 3-19
 Quality of Service
 See QoS
 queuing
 overview 3-21
 techniques 3-9, 3-12
 queuing techniques 3-9

R

RADIUS 3-26
 Real-time Transport Protocol (RTP) 3-5, 3-6
 remote location 2-2, 2-8, 2-22, 3-2, 3-21
 remote PMC user 2-22
 rendezvous point (RP) 3-2, 3-16
 Reverse Path Forwarding (RPF) 3-3
 RMS
 bridging 2-13
 configuration example 2-3
 dial peers associated with 2-11
 DS0 2-2, 2-6, 2-8
 DS0 resources 2-19, 2-20
 function 2-1
 function in Cisco IPICS 2-6
 installation options 2-2
 in WAN that is not multicast enabled 3-6
 mixing 2-13, 2-15, 2-16
 overview 1-4
 resource allocation 2-8
 resource consumption 2-6, 2-8
 voice port configuration 2-14
 voice ports associated with 2-11
 router media service
 See RMS
 RTP, header compression 3-6

S

Secure Socket Layer (SSL) 3-25
 security
 access control list (ACL) 3-26
 Cisco Security Agent (CSA) 3-25
 firewall 3-26
 for Cisco IPICS 3-25
 RADIUS 3-26
 recommendations 3-26
 Secure Socket Layer (SSL) 3-25

spanning tree (STP) attack mitigation [3-26](#)
 TACACS+ [3-26](#)
 serialization [3-9](#)
 service access point (SAP) broadcast [3-13](#)
 session target [4-3](#)
 shared tree
 bidirectional [3-2](#)
 forwarding traffic [3-3](#)
 in PIM SIM [3-2](#)
 unidirectional [3-2](#)
 single site model
 benefits [5-2](#)
 best practices [5-2](#)
 design characteristics [5-1](#)
 overview [5-1](#)
 topology [5-2](#)
 SIP
 connection to RMS using [2-22](#)
 in remote location [3-2](#)
 signaling flow [2-25](#)
 unicast call, set up [2-24](#)
 spanning tree (STP) attack mitigation [3-26](#)
 sparse mode (SM) [3-2](#)
 Sustained Cell Rate [3-4](#)

T

T1 interface [2-10](#)
 TACACS+ [3-26](#)
 topology
 MPLS with multicast VPN [5-4](#)
 multicast island [5-10](#)
 multiple site model [5-3](#)
 single site model [5-2](#)
 trust boundary [3-21](#)

U

UDP port [3-10](#)
 under-detection [3-7](#)
 unicast
 call flow to multicast [2-26](#)
 connection set up [2-25](#)
 connection trunk [5-18](#)
 in WAN that is not multicast enabled [3-6](#)
 POTS use for connection [2-24](#)
 stream mixing [2-22](#)

V

virtual interface (VIF) [2-14](#)
 Virtual Private Network (VPN) [5-3](#)
 virtual talk group
 See VTG
 voice activation detection (VAD)
 aggressive [3-8](#)
 conventional [3-7](#)
 enabling [3-8](#)
 overview [3-7](#)
 Voice and Video Enabled IP Security Protocol (IPSec) [5-3](#)
 voice packet [3-7](#)
 voice payload [3-7](#)
 voice port
 associating IP address with [2-14](#)
 configuration example [2-23](#)
 voice quality [3-4, 3-7, 3-9, 3-12](#)
 voice stream mixing
 See mixing
 voice streams, supported in Cisco IPICS [2-9](#)
 VoIP bearer traffic [3-21](#)
 VoIP traffic, transmission rate [3-5](#)
 VPN [5-4](#)
 VTG [2-8](#)
 about [2-10](#)

communication between channels [2-10](#)
creation [2-10](#)
members [2-10](#)
mixing channels in [2-14](#)
mixing of channels [2-10](#)
multicast address [2-10](#)
multicast address requirements [2-8](#)
participants speaking simultaneously [2-14](#)
restricting access [2-21](#)
RMS resource consumption [2-8](#)

W

Weighted-Fair Queuing (WFQ) [3-10](#)

