



INDEX

Numerics

3-level hierarchical policies

 parent policies [10](#)

802.1P headers, in nested hierarchical policies [8](#)

8K policy maps [3](#)

A

aa5snap [16](#)

AAA

 user profiles [5, 14](#)

AAL5 CPCS padding [2](#)

access list command [10](#)

ACL [4, 10, 12, 13](#)

activating traffic engineering

 on interfaces [23](#)

 on routers [21](#)

adding

 ATM bundle members [24](#)

 ATM PVCs to bundles [23](#)

 Frame Relay

 bundle members directly [45](#)

 Frame Relay bundle members directly [46](#)

 Frame Relay bundle members using map classes [49](#)

AF, *See* assured forwarding.

aggregate drop profiles [16](#)

assured forwarding, DSCP code point [7](#)

ATM

 atm pxf queuing command [8](#)

 atm pxf queuing mode [13, 14, 3, 5, 31, 8, 25](#)

 attaching policies [5](#)

 attaching policies containing the set cos command [26](#)

cell loss priority

 marking [14](#)

 matching [14](#)

 setting CLP bit [3, 29](#)

comparing committed rate data for policing and shaping [5](#)

configuring VBR-nrt VC oversubscription [11](#)

interface QoS inheritance [12](#)

line cards

 maximum VCs supported [5](#)

 VC scaling and hierarchical shaping [7](#)

oversubscription factor [15, 4](#)

queuing modes [9](#)

queuing outbound traffic [7](#)

service categories

 atm pxf queuing mode [13](#)

 no atm pxf queuing mode [13](#)

traffic classes

 in atm pxf queuing mode [8](#)

 in no atm pxf queuing mode [9](#)

VC oversubscription

 allowable oversubscription [4](#)

 ATM line cards [5](#)

See also oversubscription.

virtual circuits

 unshaped [16](#)

 unspecified bit rate [5, 6](#)

ATM CLP

 in random-detect command [31](#)

 WRED [11](#)

ATM overhead accounting

 configuration examples [9](#)

 description [2](#)

- verification examples [12](#)
- atm oversubscribe command [6](#)
- atm over-subscription-factor command [5, 31, 7, 15, 6, 11](#)
- atm pxf queuing command [14, 8, 7](#)
- atm vc-per-vp command [14](#)
- ATM VC queue depth
 - for flow control [39](#)
- AToM
 - set ATM CLP bit [13](#)
 - set FR DE bit [14](#)
- attaching
 - MPLS QoS policies to interfaces [8](#)
 - VC classes to ATM bundles [23](#)
 - VC classes to bundle members [28](#)
- average cell rate, specifying for constant bit rate PVCs [8](#)
- average queue size
 - controlling queue length [20](#)
 - modifying method of calculation [8](#)

B

- bandwidth
 - allocating PVC bandwidth share [2](#)
 - allocating unused bandwidth [3](#)
 - assigning to DLCIs and PVCs [2](#)
 - avoiding bandwidth starvation [25, 2](#)
 - bandwidth remaining command [7](#)
 - bandwidth remaining percent command [10, 14, 37, 47, 26, 46](#)
 - committed rate data for policing and shaping [5](#)
 - comparing bandwidth and priority [4, 7](#)
 - converting specified bandwidth [2, 4, 10](#)
 - distributing between queues [10](#)
 - excess bandwidth [4](#)
 - Frame Relay networks [2, 10](#)
 - kilobits per second [10, 7, 9, 11, 13, 16, 14, 37, 47, 26, 46](#)
 - limiting, advantage of shaping and policing [11](#)
 - maximum percentage [2, 4, 10](#)
 - maximum queues supported [9](#)

- minimum guaranteed queue buffers [1, 4, 10, 3](#)
- minimum percentage [10, 7, 9, 11, 13, 16, 14, 37, 47, 26, 46](#)
- overheads in ATM networks [2, 10](#)
- overriding default queue limit [6](#)
- recalculation after bandwidth changes [26](#)
- reservation [2](#)
- restrictions [9](#)
- specifying bandwidth with the priority command [9, 3](#)
- starvation [3](#)
- total bandwidth [4, 10](#)
- unused bandwidth [4](#)
- verifying and monitoring bandwidth [12](#)
- bandwidth command [5, 6, 10, 11, 16, 34](#)
 - interfaces supporting [2, 7](#)
 - non-supporting interfaces [3](#)
- bandwidth percent command [4](#)
- bandwidth remaining command [7, 3](#)
- bandwidth-remaining command [6](#)
- bandwidth remaining percent command [10, 3, 7](#)
- BBA group
 - attaching to interfaces [28](#)
 - bba-group command [27](#)
 - configuration example [27](#)
 - configuring PPPoE [27](#)
- Bc
 - committed burst [21](#)
 - specifying [12, 13, 18, 52](#)
 - See also* committed burst.
- Be
 - calculating [22](#)
 - metering [22](#)
 - specifying [12, 13](#)
 - See also* excess burst.
- BECN [9](#)
- best effort, BE (DSCP 0) [6](#)
- bits [14](#)
- bottom-level policies
 - nesting child policies [13](#)
 - using set and police commands [9](#)

- BRAS-DSLAM encapsulation types [3](#)
- bump command [5](#)
- bump command (Frame Relay VC-bundle-member) [34](#)
- bump explicit command [6](#)
- bump implicit command [6](#)
- bumping
 - circuit [17](#)
 - not accepting bumped traffic, configuring [28](#)
 - traffic in bundles [3, 16](#)
- bumping PVCs [16](#)
- bundle command [6, 9](#)
- bundles [16](#)
 - adding
 - ATM PVC members [23](#)
 - bundle members [24](#)
 - Frame Relay members directly [45, 46](#)
 - Frame Relay members using map classes [49](#)
 - attaching
 - VC classes [23, 28](#)
 - configuration examples [30](#)
 - creating
 - ATM bundles [18, 21](#)
 - Frame Relay bundles [38, 43](#)
 - Frame Relay configuration examples [50](#)
 - management of [4, 15](#)
 - mapping for PVC bundles [42](#)
 - mapping MPLS EXP to bundle members [32](#)
 - monitoring bundles [53](#)
 - protection rules [3](#)
 - PVC [1](#)
 - PVC selection [32](#)
 - restrictions for bundles [17](#)
 - system limits for bundles [2](#)
 - traffic bumping [3](#)
 - verifying bundles [29](#)
- burst-excess [7](#)
- burst-normal [7](#)

C

- CAC, *See* call admission check.
- calculating
 - bandwidth in kilobits per second [4, 10](#)
 - bandwidth percentage [4, 10](#)
 - committed burst [22](#)
 - excess burst [22](#)
 - policing rate [25](#)
- call admission check [3](#)
- CBR, *See* constant bit rate.
- cbr command [13, 8](#)
- CBS, *See* committed burst.
- CBWFQ [4, 7](#)
 - service policy inheritance [5](#)
- CDVT [12, 27](#)
- CEF [20](#)
- cell delay variation tolerance [12, 27](#)
- cell loss priority
 - in random-detect command [31](#)
 - WRED [11](#)
- cell loss priority, setting the CLP bit [9, 11, 14](#)
- child policies
 - bandwidth percent command [4](#)
 - configuration guidelines [13](#)
 - creating in three-level hierarchical policies [16](#)
 - description of [4](#)
 - hierarchical input policing policies [10](#)
 - nested hierarchical policies [7](#)
 - three-level hierarchical policies [8](#)
 - using set and police commands [9](#)
- CIR, *See* committed information rate.
- circuit bumping [17](#)
- class
 - class-default [9, 12](#)
 - deleting from policy map [17](#)
 - maximum non-class-default classes [9](#)
 - traffic class [4, 16](#)
- class-based traffic shaping [3](#)

- class-based weighted fair queuing, *See* CBWFQ.
- class-bundle command [7](#)
- class command [18, 5, 9, 10, 21](#)
- class-default class [18, 3, 5](#)
 - description of [11](#)
 - minimum bandwidth guarantee [6](#)
- classification
 - defining match criteria [5](#)
- classification byte counts [11](#)
- classifying packets
 - by DSCP [9](#)
 - by group ID [9](#)
 - by IP precedence level [9](#)
 - creating class maps [1, 11, 12](#)
 - defining match criteria [5](#)
 - IP packets using class maps [6](#)
 - restrictions and limitations [11](#)
 - verifying traffic criteria [13](#)
- class-map command [3, 12](#)
- class-map match command [10](#)
- class maps
 - classifying traffic [11](#)
 - creating [12](#)
 - defining [8](#)
 - description of [3, 1](#)
 - example configuration [8](#)
 - for per session rate limiting [3, 4](#)
 - Frame Relay [1](#)
 - match statements [5, 7](#)
 - maximum number supported [2](#)
 - system limits [2](#)
- class of service
 - for Layer 2 to Layer 3 mapping [11](#)
 - for prioritizing packets [11](#)
 - IEEE 802.1p standard [10](#)
 - marking [10](#)
 - recommended values [21](#)
- class policies
 - configuring in a policy map [9](#)
 - configuring using tail drop [11](#)
 - configuring using WRED packet drop [12](#)
- class queues
 - allocating queue IDs [6](#)
 - maximum number [2](#)
 - scaling limits [2](#)
- class selector code points [6, 7](#)
- class-vc command [8](#)
- CLI, *See* modular QoS CLI for implementing QoS.
- CLP, *See* ATM cell loss priority.
- command line interface, *See* modular QoS CLI for implementing QoS.
- commands
 - access list [10](#)
 - atm oversubscribe [6](#)
 - atm over-subscription-factor [31, 15, 6, 11](#)
 - atm pxf queuing [14, 8](#)
 - atm vc-per-vp [14](#)
 - bandwidth [6, 10, 34](#)
 - bandwidth percent [4](#)
 - bandwidth remaining [7, 3](#)
 - bandwidth-remaining [6](#)
 - bandwidth remaining percent [10, 3](#)
 - bba-group [27](#)
 - bump [5](#)
 - bump (Frame Relay VC-bundle-member) [34](#)
 - bump explicit [6](#)
 - bump implicit [6](#)
 - bundle [6, 9](#)
 - cbr [13, 8](#)
 - class [18, 9, 10, 21](#)
 - class-bundle [7](#)
 - class-map [3, 12](#)
 - class-map match [9, 10](#)
 - class-vc [8](#)
 - dbas enable [12](#)
 - dscp (Frame Relay VC-bundle-member) [35](#)
 - encapsulation dot1q [19](#)
 - encapsulation dot1q [22](#)

- encapsulation frame-relay 16
- exp other 37
- frame-relay class 19, 16, 45
- frame-relay interface-dlci 17, 16
- frame-relay interface-queue 2, 3
- frame-relay ip rtp priority 5
- frame-relay map-class 16
- frame-relay traffic rate 6
- frame-relay traffic-shape 7
- frame-relay vc-bundle 38
- interface multilink 5
- interface virtual-template 10, 11
- ip rsvp bandwidth 26
- map-class frame-relay 12, 19, 53, 4
- match 1, 5
- match access-group 10
- match-all 5
- match-any 5
- match cos 6
- match discard-class 6
- match fr-de 6
- match input-interface 6
- match ip dscp 7
- match ip precedence 7
- match ip rtp 7
- match mpls-experimental 16
- match mpls-experimental-imposition 8
- match mpls experimental topmost 8, 4
- match-not 6
- match qos-group 8
- mpls experimental 9
- mpls experimental other 9
- mpls ip encapsulate explicit-null 4
- no atm pxf queuing 14, 9, 6
- oam-bundle 10
- oam retry 11
- police 5, 6, 9
- police percent 11, 35
- policy-map 3, 9, 21
- ppp multilink 6
- ppp multilink fragmentation 8
- ppp multilink fragment disable 9
- ppp multilink interleave 8, 9, 26
- precedence 11
- precedence (Frame Relay VC-bundle-member) 39
- precedence other 39
- priority 5, 6, 10
- propagate-cos 3
- protect 12, 13
- protect (Frame Relay VC-bundle-member) 40
- protocol pppoe group 28
- pvc 14
- pvc (Frame Relay VC-bundle) 41
- pvc-bundle 8, 9, 13
- pvc-in-range 12
- qos match statistics 4
- queue-depth 16, 22, 24, 38
- queue-limit 5, 6, 4
- random-detect 5, 6
- random-detect dscp 8
- random-detect exponential-weight-constant 8
- random-detect precedence 9
- service-policy 3, 10, 5
- set 5
- set atm-clp 5, 6, 9, 14
- set cos 5, 6, 12
- set discard-class 16
- set fr-de 19
- set ip dscp 5, 6, 9
- set ip precedence 5, 6, 9, 5
- set mpls experimental 5, 6, 11
- set mpls experimental imposition 15, 4
- set mpls experimental topmost 16
- set qos-group 5, 6, 9, 13
- shape 5, 6, 10, 4
- show atm class-links 41
- show atm interface 41
- show caller 16

- show class-map [13, 16](#)
- show controllers [41](#)
- show ha pxf cpu queue summary [6](#)
- show hardware pxf [34, 33](#)
- show interface [32, 23, 32](#)
- show interfaces virtual-access [32](#)
- show policy-map [12, 18, 28, 16](#)
- show policy-map class [12, 18, 28](#)
- show policy-map interface [8, 33, 27](#)
- show policy-map map [19](#)
- show pppoe session all [33](#)
- show pppoe session packets [33](#)
- show pxf cpu queue [33](#)
- show pxf cpu queue interface [32](#)
- show pxf cpu queue summary [33](#)
- show pxf cpu schedule [33](#)
- show pxf interface [33](#)
- show vlans [42](#)
- sub-pool [26](#)
- ubr [14, 8](#)
- ubr+ [8, 9](#)
- vbr-nrt [15, 8](#)
- vc-class [29](#)
- vc-class atm [9, 11](#)
- virtual-template [27](#)
- weight [22, 24](#)
- committed burst
 - burst size [6, 9, 21, 8](#)
 - calculating [22](#)
- committed information rate [6, 9, 12](#)
- committed rate, policing data [6, 23](#)
- communicating directly with RADIUS, no proxy [32](#)
- community list [3](#)
- configuring
 - ATM bundle members, VC class [26](#)
 - ATM cell loss priority marking [29](#)
 - bumping rules, Frame Relay members [34](#)
 - class of service marking [26](#)
 - differentiated services code point marking [24](#)
 - discard-class marking [33](#)
 - Frame Relay traffic shaping [5, 6](#)
 - IP precedence marking [22](#)
 - MPLS experimental marking [31](#)
 - percent-based policing [11, 26](#)
 - precedence levels for bundle members, Frame Relay [39](#)
 - protected bundle members, Frame Relay [40](#)
 - QoS [5](#)
 - QoS group marking [28](#)
 - queue size [4](#)
 - random early detection [20](#)
 - RED, *See* configuring random early detection.<configuring
 - zzzz>
 - WRED based on ATM CLP [31](#)
 - WRED based on discard class [29](#)
 - WRED based on DSCP [26](#)
 - WRED based on IP precedence [28](#)
- conforming traffic
 - conform-action [7, 6, 10, 20](#)
 - metering and conforming token bucket [21](#)
 - packet sizes [7](#)
 - specifying multiple conforming actions [26](#)
 - token buckets, single-rate policer [18](#)
- congestion
 - controlling
 - tail drop [8](#)
 - using precedence marking [4](#)
 - using random early detection [8, 9](#)
 - using weighted random early detection [11](#)
 - controlling using random early detection [34](#)
 - management of [4](#)
 - queue limit [2](#)
 - restrictions for controlling [21](#)
- constant bit rate [13, 8](#)
- controlling, average queue length [10](#)
- creating
 - ATM bundles [18, 21](#)

- class maps [12](#)
- Frame Relay bundles [38, 41, 43](#)
- map classes for Frame Relay [1](#)
- policy maps [18](#)
- CS1 through CS7 [6](#)

D

- data, policing rate [23](#)
- data-link connection identifier
 - allocating PVC bandwidth share [2](#)
 - assigning [19](#)
 - description of [17, 16](#)
 - VoIP packet classification [4](#)
 - IP RTP Priority [5](#)
 - See also* DLCI.
- DBS, *See* dynamic bandwidth selection.
- dbns enable command [12](#)
- DE bit [6](#)
- default class
 - bandwidth-remaining command [6](#)
- default traffic class [11](#)
- delay, managing [7](#)
- differentiated services
 - assured forwarding
 - assured forwarding, class drop probability [7](#)
 - assured forwarding classes [7](#)
 - best effort, DSCP 0 [6](#)
 - class selector code points [6, 7](#)
 - compliance with IETF standards [6](#)
 - DiffServ suggested DSCP values [8](#)
 - DSCP [6](#)
 - expedited forwarding, per-hop behavior [7](#)
 - matching criteria [7](#)
 - per-hop behavior [6](#)
 - recommended values [21](#)
 - reserved keywords [7](#)
 - RFCs defining DSCP values [8](#)
 - setting DSCP bits [12](#)

- weighted random early detection based on DSCP [9](#)
- differentiated services code point
 - assured forwarding
 - binary values [8](#)
 - bits [6](#)
 - code point values [7](#)
 - DSCP
 - names [8](#)
 - values [8](#)
 - expedited forwarding
 - RFCs, defining DSCPs [8](#)
- discard-class
 - marking traffic [16, 33](#)
 - setting [11](#)
- discard eligibility bit [6](#)
- displaying, statistics and configuration information for policing [41](#)
- DLCI
 - assigning [16](#)
 - associating map classes to [16](#)
- DotP marking, in nested hierarchical policies [8](#)
- dropping packets
 - based on CLP [31](#)
 - drop policing action [11, 3](#)
 - drop probability, assured forwarding classes [7](#)
 - drop rate in random-detect command [8](#)
 - how RED determines drop probability [10](#)
 - interfaces not supporting drop policies [21](#)
 - interfaces supporting drop policies [21](#)
 - random early detection [9](#)
 - verifying packet dropping [32](#)
 - weighted random early detection [9, 11](#)
- drop profiles
 - for WRED [16](#)
- drop rate, random-detect command [9](#)
- DS3/E3 line card, maximum virtual circuits supported [8](#)
- DSCP, *See* differentiated services.
- DSCP-based mapping for PVC bundles [42](#)
- dscp command (Frame Relay VC-bundle-member) [35](#)

DSLAM-CPE encapsulation types [3](#)

dynamic bandwidth selection

accounting record [7](#)

affect on sessions [6](#)

bandwidth updates [8](#)

CBR PVCs [9](#)

configuring

individual PVC in a PVC range [12](#)

PVC ranges [11](#)

PVCs [10](#)

VC classes [9](#)

debug commands [17](#)

enabling [9, 11](#)

NAS QoS management [6](#)

PCR and SCR parameters [5, 13](#)

protocols supported [8](#)

RADIUS attributes [13](#)

restrictions [3](#)

service category

changes to, restrictions [8](#)

transitions [7](#)

SVCs [8](#)

UBR unshaped transitions [8](#)

policing policies [6](#)

shaped rate and frame headers [6](#)

verification examples [13](#)

exceeding actions

police command [7, 6, 10, 20](#)

specifying multiple actions [26](#)

exceeding packets [7](#)

exceeding token bucket [18, 22](#)

excess bandwidth

allocating unused bandwidth [3](#)

comparing bandwidth and priority [4](#)

excess burst

calculation of [22](#)

default size [22](#)

police command [6, 22](#)

size [22](#)

specifying [12, 13](#)

EXP bit [4](#)

exp command, Frame Relay bundle member [36](#)

expedited forwarding

expedited forwarding, per-hop behavior [7](#)

experimental field value, MPLS QoS [1](#)

exponential-weight-constant

average queue size [20](#)

Frame Relay [3](#)

random-detect command [8](#)

exp other command [37](#)

E

EBS, *See* excess burst size.

EF, *See* expedited forwarding.

encapsulation

subscriber line [4](#)

encapsulation dot.lq command [19](#)

encapsulation dot1.q command [22](#)

encapsulation frame-relay command [16](#)

Ethernet

comparing committed rate data for policing and shaping [5](#)

interface QoS inheritance [12](#)

Ethernet overhead accounting [3](#)

configuration example [10, 11](#)

F

fair queues

creating at three levels [15](#)

creating at two levels [13](#)

Fast Ethernet port [21, 31](#)

fe0/0/0 management port [21, 31](#)

feedbacks, parallel express forwarding [17](#)

flow control

on Layer 2 queues [39](#)

forcing, PVC bundles down [3](#)

fragmentation [1](#)

Frame Relay

attaching, QoS policies using map classes [16](#)

comparing committed rate data for policing and shaping [5](#)

configuring PVC oversubscription [11, 12](#)

creating map classes [1](#)

DE bit [6](#)

drop policy [3](#)

encapsulation types [43](#)

exponential-weight-constant [3](#)

IP RTP [4, 5](#)

IP RTP priority (VoIP) [5](#)

oversubscription

map classes [15](#)

PVCs [7](#)

restrictions [9](#)

physical interface QoS inheritance [12](#)

priority queues [4](#)

QoS policies restrictions [13](#)

queuing outbound traffic [7](#)

traffic shaping [8, 5, 6](#)

weighted fair queuing [2, 4](#)

frame-relay class command [16, 19, 16, 45](#)

frame-relay interface-dlci command [17, 19, 16](#)

frame-relay interface-queue commands [2, 3](#)

frame-relay ip rtp priority command [5](#)

frame-relay map-class command [16](#)

frame-relay traffic rate command [6](#)

frame-relay traffic-shape command [7](#)

frame-relay vc-bundle command [38](#)

FRF.12 [3](#)

See also LFI.

FRTS [8](#)

FRTS, *See* Frame Relay traffic shaping.

G

global pool tunnels [19](#)

differentiated service [26](#)

in DS-TE [20](#)

global synchronization, maximizing [13](#)

green token bucket [18](#)

guaranteed minimum bandwidth [10](#)

H

hierarchical input policing

child policies [10](#)

configuring [19](#)

description of [6, 10](#)

restrictions for [11](#)

See also, hierarchical policies.

hierarchical policies

attaching [21](#)

bandwidth percent command in child policies [4](#)

benefits of [3](#)

child policies [4, 7, 8, 10](#)

configuration examples [22](#)

configuring overhead accounting [6](#)

configuring percent-based policing [34](#)

description of [2](#)

guidelines for configuring [13](#)

hierarchical input policing [6, 10](#)

interfaces not supporting hierarchical policies [12](#)

interfaces supporting hierarchical policies [12](#)

nested hierarchical policies [6, 7](#)

oversubscription [11, 10](#)

parent policies [4, 7, 8, 10](#)

three-level hierarchical policies [6, 8](#)

types of [6](#)

verification examples [29](#)

verifying [27](#)

hierarchical shaping [4, 5, 6](#)

configuration examples [21](#)

maximum line card virtual circuits [8](#)

overview [4](#)

restrictions [8](#)

shaped UBR PVCs [5](#)
 VC scaling [7](#)
 high watermark [22, 24, 25, 38](#)
 hwm [24, 38](#)

See also high watermark.

IEEE 802.1p, for inbound and outbound packets [10](#)

IEEE 802.1Q, frame headers [10](#)

inbound interfaces, hierarchical policies [12](#)

inheritance [10](#)

ATM QoS [2](#)

Frame Relay QoS [12](#)

LAC QoS [30](#)

interface multilink command [5](#)

interfaces

ATM, queuing outbound traffic [7](#)

attaching

ATM QoS policies [2, 5, 7, 8](#)

Frame Relay QoS policies [11, 14, 15, 16, 17, 19](#)

LAC QoS [30](#)

policy maps [12, 32](#)

QoS policies, service-policy command [3](#)

virtual access interface QoS policies [23](#)

VLAN QoS policies [21, 22, 23, 31](#)

configuring QoS [5](#)

Frame Relay, queuing outbound traffic [7](#)

interfaces not supporting

bandwidth command [3](#)

hierarchical policies [12](#)

marking [20](#)

packet drop policies [21](#)

policing [18](#)

priority queuing [4](#)

queue-limit [21](#)

random-detect [21](#)

shaping [13](#)

interfaces supporting

bandwidth command [2, 7](#)

hierarchical policies [12](#)

marking [20](#)

packet drop policies [21](#)

policing [17](#)

priority queuing [4](#)

queue-limit [21](#)

random-detect [21](#)

traffic shaping [13](#)

oversubscribing [5, 31, 2, 45](#)

See also oversubscribing.

packet input match statement [6](#)

QoS inheritance [12](#)

supporting the attachment of QoS policies [1](#)

virtual LAN, queuing outbound traffic [7](#)

interleaving [1](#)

internal marking

discard-class [2](#)

qos-group [2](#)

set qos-group [13](#)

Internet Engineering Task Force, differentiated services RFCs [6](#)

Internet Protocol

DSCP value [7](#)

VoIP [4](#)

IP differentiated services, setting the DSCP bits [9](#)

IP precedence

precedence levels 6 and 7 [16](#)

recommended values [21](#)

setting the precedence level [12](#)

values [7, 4](#)

weighted random early detection,
precedence-based [4, 5, 9, 11](#)

IP Real-Time Protocol [4](#)

ip rsvp bandwidth command [26](#)

IP RTP [4, 5](#)

IP RTP priority for VoIP (Frame Relay) [5](#)

IP sessions

configuration examples for MQC [23](#)

- configuring MQC [21](#)
- interface support [19](#)
- MQC support [18](#)
- policy map actions [19](#)
- restrictions [20](#)
- IPv4 packets [5](#)

J

- jitter, managing [7](#)

K

- kilobits per second
 - bandwidth [10](#)
 - priority queues [10](#)

L

- label-controlled ATM subinterface, QoS inheritance [12](#)
- label imposition, MPLS [15](#)
- label switching router [5](#)
- LAC
 - attaching QoS policies [31](#)
 - QoS inheritance [30](#)
- Layer 2, applying QoS policies to tunnel packets [32](#)
- Layer 2 access concentrator, attaching QoS policies [30](#)
- LC-ATM, QoS inheritance [12](#)
- LFI
 - FRF.12 fragmentation [3](#)
 - MLP over Frame Relay [3](#)
 - MLP over serial [2](#)
 - multi-VC MLP over ATM [2](#)
 - overview [1](#)
 - single-VC MLP over ATM [2](#)
- limiting, number of packets in queues [10](#)
- links, assigning bandwidth to DLCIs and PVCs [2](#)
- LNS

- per-session shaping [45](#)
- locally originated traffic, subject to QoS policies [16](#)
- low-latency priority queuing, *See* priority queuing.
- low watermark [22, 24, 25, 38](#)
- LSR [5](#)
- lwm [24, 38](#)
 - See also* low watermark.

M

- management information base, QoS MIBs [4](#)
- management port [21, 31](#)
- managing PVC bundles [4](#)
- map classes
 - attaching
 - Frame Relay QoS policies [16](#)
 - oversubscribing Frame Relay PVCs [16](#)
- map-class frame-relay command [12, 19, 53, 4](#)
- mapping MPLS EXP to bundle members [32](#)
- marking
 - actions [2](#)
 - ATM cell loss priority [14](#)
 - class of service [2, 10, 15](#)
 - configuring
 - ATM cell loss priority [29](#)
 - class of service [26](#)
 - differentiated services code point [24](#)
 - discard-class [33](#)
 - IP precedence [22](#)
 - MPLS experimental [31](#)
 - QoS group [28](#)
 - description of [2](#)
 - design guidelines for marking [21](#)
 - discard-class [2, 16, 15](#)
 - DSCP marking [2, 15](#)
 - interfaces not supporting marking [20](#)
 - interfaces supporting marking [20](#)
 - IP precedence marking [2, 15](#)
 - MPLS experimental marking [14](#)

- policing and marking traffic [18](#)
 - QoS group marking [2, 13, 15](#)
 - recommended values for marking [21](#)
 - restrictions for traffic marking [20](#)
 - set atm-clp command [2, 15](#)
 - set mpls experimental imposition command [2, 15](#)
 - set qos-group command [2, 15](#)
 - verifying traffic marking [37](#)
 - See also* traffic marking.
- match access-group command [12, 10](#)
- match-all command [5](#)
- match-any command [5](#)
- match command [1, 5, 9](#)
- match cos command [6](#)
- match discard-class command [6](#)
- match fr-de command [6](#)
- match input-interface command [6](#)
- match ip dscp command [7](#)
- match ip precedence command [7](#)
- match ip rtp command [7](#)
- match mpls-experimental command [16](#)
- match mpls-experimental-imposition command [8](#)
- match mpls experimental topmost command [8, 4](#)
- match-not command [6](#)
- match qos-group command [8](#)
- match statements in class maps [2, 5, 7, 11](#)
- maximum burst size [15](#)
- maximum threshold [8](#)
 - default values [39](#)
 - description of [19](#)
 - guidelines for changing [39](#)
 - in the random-detect command [9](#)
 - recommended setting for random early detection [11](#)
- MBS, *See* maximum burst size.
- metering, *See* policing.
- MIB, *See* management information base.
- minimum threshold [8](#)
 - default values [39](#)
 - description of [19](#)
- guidelines for changing [39](#)
 - in the random-detect command [9](#)
 - recommended setting for random early detection [11](#)
- MLP [2](#)
- modes for queuing
 - no atm pxf queuing [4, 6, 7](#)
 - pxf queuing [4, 7](#)
- modular QoS CLI
 - class map [3, 4](#)
 - implementing QoS [2, 34, 50, 29](#)
 - policy map [3, 4](#)
 - service-policy [3, 4](#)
- monitoring
 - bursts [23](#)
 - policing [41](#)
 - QoS policies [32](#)
- MPLS DiffServ tunneling modes
 - CE routers [16](#)
 - MPLS experimental field [14](#)
- MPLS experimental [14](#)
 - bits [4](#)
 - configuring marking [8, 12, 31](#)
- mpls experimental command [9](#)
- mpls experimental other command [9](#)
- MPLS EXP field
 - See also* MPLS experimental.
- MPLS EXP field, setting using policy maps [7](#)
- mpls ip encapsulate explicit-null command [4](#)
- MPLS QoS [1](#)
 - experimental field value [1](#)
 - services supported [2](#)
 - tunnel modes [3](#)
 - pipe mode [10](#)
 - short pipe mode [9](#)
- MQC, *See* modular QoS CLI.
- MQC support for IP sessions [18](#)
- multilink PPP bundling, priority queuing [2](#)
- multiple queues, guidelines for configuring QoS [13](#)
- multi-VC MLP [2](#)

N

NAS [6](#)

NCP, *See* Network Control Protocol.

nested hierarchical policies

creating [13](#)

description of [6](#)

nested policy maps

percent-based bandwidth [26](#)

percent-based policing [11](#)

parent policies [7](#)

queuing actions [21, 31](#)

restrictions for [7](#)

See also, hierarchical policies.

nested hierarchical policies, *See also* hierarchical policies.

network access server [6](#)

Network Control Protocol [6](#)

network-forwarding policy [20](#)

no atm pxf queuing command [14, 9](#)

no atm pxf queuing mode [4, 13, 3, 9, 25, 6, 7](#)

nonreal-time variable bit rate [13](#)

See also variable bit rate.

no policy-map command [18](#)

normal burst, specifying [12, 13, 18, 52](#)

O

oam-bundle command [10](#)

oam retry command [11](#)

OC-12 line card, maximum virtual circuits [8](#)

OC-3 line card, maximum virtual circuits [8](#)

outbound interfaces, hierarchical policies [12](#)

out of resource message [22](#)

overhead accounting

AAL5 [2](#)

ATM [2](#)

bandwidth command [7](#)

calculation [4](#)

child priority queues [3](#)

classification byte counts [11](#)

configuration commands [4, 6](#)

configuration examples [9, 10, 11](#)

configuration requirements for hierarchical policies [5](#)

configuring [6](#)

Ethernet [3](#)

Ethernet frame headers [6](#)

examples of verifying ATM accounting [12](#)

examples of verifying Ethernet accounting [13](#)

feature history [2](#)

features [1](#)

hierarchical policies [5](#)

interfaces supported [6](#)

policing and Ethernet accounting [6](#)

PRE requirements [2](#)

queuing byte counts [11](#)

restrictions [6](#)

shape command [8](#)

show policy-map interface command [6](#)

subscriber line encapsulation [4](#)

traffic shaping overhead accounting for ATM [3](#)

user-defined offset [3, 7, 8](#)

verifying [11](#)

oversubscription

ATM line cards [5](#)

ATM oversubscription factor [4](#)

atm over-subscription-factor command [15, 5](#)

ATM port and bandwidth sharing [53](#)

ATM VC [3](#)

benefits of [2](#)

configuration examples [38](#)

configuring [10](#)

configuring for VLANs [17](#)

configuring on VBR-nrt virtual circuits [11](#)

disabling on ATM interfaces [7](#)

Frame Relay PVCs [7, 11, 12, 15](#)

hierarchical policies [11, 10](#)

interface [2, 45](#)

restrictions

Frame Relay PVC oversubscription 9

interface oversubscription 3

VLAN oversubscription 9

session level 53

UBR virtual circuits 4

VBR-nrt virtual circuits 3

verifying 41

VLAN 9

oversubscription factor 15

P

packet buffers, queue limit 4

packet drops

verifying 32

packets

classifying 1

conforming or exceeding, determining 23

conforming packets 7

defining traffic classes 1

drop policy

Frame Relay 3

random early detection 20

exceeding packets 7

green packets 7

IPv4 packets 5

matching packets 5

queue limit 3

red packets 7

specifying QoS

IP packets 1

MPLS packets 1

violating packets 7

VoIP classification 4

yellow packets 7

PAK_Priority 16

parallel express forwarding

feedbacks 17

QoS performance 17

shaping VCs 5

parent policies

description of 4

hierarchical input policing policies 10

in nested hierarchical policies 7

service-policy command 4

shape command 4

three-level hierarchical policies 8, 18

PCR

See peak cell rate.

peak cell rate

constant bit rate PVCs 13

dynamic bandwidth selection 13

multiple sessions 5

unshaped and shaped unspecified bit rate PVCs 13

variable bit rate PVCs 15

percentage-based shaping 8

percent-based

bandwidth, configuring 10

policing, configuring 26, 32, 34, 35

priority, configuring 10

per-class mode 4

per-hop behavior 6, 7

per-match mode 4

per session

rate limiting 3, 9, 12

service policy 5, 11, 13

per-session shaping on ATM interfaces

configuration examples 50

configuring 46

description of 45

verifying 50

per user multiservice rate limiting 4, 10, 13

per VRF AAA 32

PHB, *See* per-hop behavior.

pipe tunneling mode 3, 10

police actions

set-cos-transmit 15

- set-frde-transmit [14](#)
- police command [5, 6, 7, 6, 9](#)
- police percent command [11, 32, 35](#)
- policer, *See* policing.
- policies
 - attaching
 - ATM QoS policies [2, 5](#)
 - Frame Relay QoS policies [11, 15, 17, 19](#)
 - LAC QoS [30, 31](#)
 - QoS policies, service-policy command [3](#)
 - VLAN QoS policies [21, 22, 23](#)
 - creating Frame Relay QoS policies [14](#)
 - Frame Relay QoS restrictions [13](#)
 - queuing actions [21, 31](#)
- policing [3](#)
 - actions [3](#)
 - bits per second-based policing [28](#)
 - class-based policing [2](#)
 - committed burst [6, 9, 8](#)
 - committed information rate [6, 9, 20](#)
 - conform-action [6, 10, 20](#)
 - conforming packets [7](#)
 - effects of shaping [13](#)
 - exceed-action [6, 10, 20](#)
 - exceeding packets [7](#)
 - excess burst [6, 22](#)
 - green packets [7](#)
 - inbound traffic at two levels [19](#)
 - interfaces not supporting policing [18](#)
 - interfaces supporting policing [17](#)
 - marking and policing traffic [18](#)
 - metering using token buckets [18](#)
 - nested policies [11](#)
 - percent-based policing [11, 34](#)
 - policing actions
 - drop [11, 3](#)
 - set-clp-transmit [11, 3](#)
 - set-cos-transmit [3](#)
 - set-discard-class-transmit [11, 3](#)
 - set-dscp-transmit [12, 3](#)
 - set-dscp-tunnel-transmit [3](#)
 - set-frde-transmit [4](#)
 - set-mpls-exp-imposition-transmit [12, 4](#)
 - set-mpls-exp-transmit [12, 4](#)
 - set-prec-transmit [12, 4](#)
 - set-prec-tunnel-transmit [4](#)
 - set-qos-transmit [4](#)
 - policing rate data [23](#)
 - policing traffic, percent-based [11, 26](#)
 - rate granularity [25](#)
 - red packets [7](#)
 - restrictions and limitations for policing [26](#)
 - set-qos-transmit policing action [12](#)
 - single-rate color marker [4](#)
 - specifying multiple actions [26](#)
 - three-color marker [4, 5, 33](#)
 - token bucket algorithm [2](#)
 - traffic policing overview [2](#)
 - transmit policing action [4](#)
 - two-color marker [4](#)
 - verifying and monitoring [41](#)
 - violate-action [6, 12](#)
 - violating packets [7](#)
 - yellow packets [7](#)
- policy actions
 - input [5](#)
 - output [6](#)
 - prior to Release 12.0(17)SL [6, 7](#)
 - Release 12.0(17)SL [8](#)
 - Release 12.0(17)SL and later [10](#)
 - Release 12.0(20)ST and later [10](#)
 - Release 12.0(22)S and later [11](#)
- policy map
 - attaching to interfaces [2, 12, 32, 4](#)
 - class bandwidth allocation [10, 16](#)
 - class queue limit [17](#)
 - configuration example [25, 29, 30, 12, 14](#)
 - creating policy maps [3, 18](#)

- defining QoS actions [2, 19](#)
- definition of [3](#)
- deleting classes from policy maps [17](#)
- deleting policy maps [18](#)
- description of [1, 2](#)
- input actions [5](#)
- maximum number supported [2](#)
- maximum priority queues [9](#)
- modifying a class policy [2, 4](#)
- output actions [6](#)
- per session rate limiting [3](#)
- per user multiservice rate limiting [4](#)
- policy actions [7](#)
- policy-map command [3, 9, 10, 21](#)
- qos match statistics [4](#)
- restrictions for policy maps [2](#)
- system limits, policy maps [2, 4](#)
- verifying configuration [12, 20](#)
- policy-map command [3, 18, 5](#)
- policy maps
 - 8k [3](#)
- policy-map-type service command [20](#)
- PPP
 - applying rate limiting
 - PPPoA, PPPoE, and RBE sessions [6](#)
 - tunneled sessions [6](#)
 - ppp multilink command [6](#)
 - ppp multilink fragmentation command [8](#)
 - ppp multilink fragment disable command [9](#)
 - ppp multilink interleave command [8, 9, 26](#)
- PPPoE
 - displaying status of active tunnels [33](#)
 - sessions [28](#)
- precedence-based mapping for PVC bundles [42](#)
- precedence command [11](#)
- precedence command (Frame Relay VC-bundle-member) [39](#)
- precedence field [42](#)
- precedence levels [9](#)
- precedence other command [39](#)
- PRI field, *See* priority field.
- priority
 - class, minimum guaranteed bandwidth percentage [3](#)
 - comparing priority and bandwidth [7](#)
 - data, recommended marking values [21](#)
 - field [10](#)
 - priority command [5, 6, 10](#)
 - priority queuing, *See* priority queuing.
 - queue [8](#)
- priority queuing
 - bandwidth command [5](#)
 - bandwidth starvation of other queues [25](#)
 - configuring [6](#)
 - description of [1](#)
 - Frame Relay [4](#)
 - guaranteed minimum bandwidth [2](#)
 - interfaces not supporting [4](#)
 - interfaces supporting priority queuing [4](#)
 - multilink PPP bundling [2](#)
 - police command [25](#)
 - random-detect command [5](#)
 - restrictions for priority queues [5](#)
 - strict priority queuing [2](#)
 - verifying priority queues [11](#)
- propagate-cos command [3](#)
- protect command [12, 13](#)
- protect command (Frame Relay VC-bundle-member) [40](#)
- protocol pppoe group command [28](#)
- pvc-bundle command [8, 9, 13](#)
- PVC bundles [1](#)
 - adding
 - ATM PVC members [23](#)
 - bundle members [24](#)
 - Frame Relay bundle members [45](#)
 - Frame Relay bundle members directly [46](#)
 - Frame Relay members using map classes [49](#)
 - ATM members [23](#)
 - attaching

- VC classes [23, 28](#)
 - bumping PVCs [16](#)
 - configuration examples [30](#)
 - creating
 - ATM bundles [18](#)
 - Frame Relay bundles [21, 38, 43](#)
 - Frame Relay configuration examples [50](#)
 - management of [4, 15](#)
 - mapping
 - for PVC bundles [42](#)
 - MPLS EXP to bundle members [32](#)
 - monitoring bundles [53](#)
 - protection rules [3](#)
 - PVC selection [32](#)
 - restrictions for bundles [17](#)
 - system limits for bundles [2](#)
 - traffic bumping [3](#)
 - verifying bundles [29](#)
 - pvc command [14](#)
 - pvc command (Frame Relay VC-bundle) [41](#)
 - pvc-in-range command [12](#)
 - PVCs, attaching ATM policies [8](#)
 - PXF [17](#)
 - PXF and shaping [5](#)
 - pxf queuing mode [7](#)
-
- ## Q
- QID, *See* queue IDs.
 - QoS
 - applying service policies [3](#)
 - ATM attaching QoS policies [6](#)
 - ATM inheritance [2](#)
 - atm pxf queuing mode [3, 5, 31](#)
 - attaching
 - ATM QoS policies [7](#)
 - Frame Relay QoS policies [11, 14, 16, 17, 19](#)
 - QoS policies [1](#)
 - virtual access interface QoS policies [23](#)
 - VLAN QoS policies [21, 22, 23](#)
 - attaching ATM QoS policies [8](#)
 - benefits of QoS [2](#)
 - class map [3, 4](#)
 - CLI migration from PRE2 to PRE3 [3](#)
 - configuring per session service policy [11](#)
 - configuring QoS [5](#)
 - creating Frame Relay policy [14](#)
 - defining QoS actions [2](#)
 - DSLAM model configurations [6](#)
 - features [6](#)
 - for subscribers [1, 2](#)
 - Frame Relay
 - inheritance [12](#)
 - traffic shaping [5, 6](#)
 - input and output policy-map actions [4, 6, 7, 8](#)
 - LAC inheritance [30](#)
 - management information base for QoS [4](#)
 - Model D.2 [7](#)
 - Model F [7](#)
 - modular command line interface for implementing QoS [2, 34, 50, 29](#)
 - no atm pxf queuing mode [3](#)
 - objectives of bandwidth and priority commands [7](#)
 - order of execution for QoS features [4](#)
 - per session
 - rate limiting [3](#)
 - service policy [5](#)
 - policing traffic [11, 26](#)
 - policy map [3, 4](#)
 - defining QoS actions [2](#)
 - definition of [3](#)
 - QoS actions [4](#)
 - precedence [6](#)
 - QoS features and changes [11](#)
 - QoS group
 - identifier, setting [28](#)
 - maximum number [13](#)
 - policing action, setting [12](#)

- QoS implementation guidelines 4
- QoS inheritance 12
- QoS policy propagation through the Border Gateway Protocol 13
- QoS restrictions and limitations 2
- queuing actions 21, 31
- random early detection (RED) 20
- scalability 4
- service policies
 - components 5
 - creating 5
 - definition of 3
 - per session rate limiting 3
 - per user multiservice rate limiting 4
 - specifying QoS, IP and MPLS packets 1
 - traffic subject to QoS 16
 - types of QoS actions 4
- qos match statistics command 4
- QoS models
 - configure sessions 8
 - configure subinterfaces 8
 - D.2 6
 - D.2 configuration example 9, 10
 - D.2 configuration tasks 8
 - D.2 key components 7
 - F 6
 - F configuration example 10
 - F configuration tasks 9
 - F key components 7
 - generic requirements 6
- QoS service
 - business 6
 - residential 6
- QPPB, *See* QoS policy propagation through the Border Gateway Protocol.
- quality of service, *See* QoS.
- queue depth 16, 38
- queue-depth command 16, 22, 24, 38
- queue IDs
 - allocating 6
 - determining available queues 6
 - out of resource message 6
 - reserving
- queue limit
 - aggregate sum restrictions 22
 - as a power of 2 5
 - changing 22
 - combining with random detection 22
 - configuring 4
 - default behavior 5, 25
 - description of 2
 - overriding default 6
 - packet buffers 4
 - restrictions 21
- queue-limit command 5, 6, 4, 10, 11, 17
- queues
 - allocating queue IDs 6
 - changing size of 22
 - maximum number 2
 - priority 4
 - scaling limits 2
- queue size
 - calculating the average size 18, 20
 - configuring 24
 - controlling using queue-limit 20
 - exponential-weight-constant 18, 20
 - modifying method of calculation 8
- queue weight 2
- queuing byte counts 11
- queuing modes
 - atm pxf queuing 3, 5, 31, 8, 25
 - changing 5, 31
 - no atm pxf queuing 3, 9, 25
 - specifying 14
- queuing outbound traffic
 - ATM interfaces 7
 - Frame Relay interfaces 7
 - VLANs 7

R

RADIUS

- AAA user profiles [5, 14](#)
- configuring RADIUS on the router [11](#)
- server [5](#)
- random-detect command [13](#)
 - drop rate [8](#)
 - input policy map action [5](#)
 - maximum threshold [8](#)
 - minimum threshold [8](#)
 - output policy map action [6](#)
 - usage guidelines [18](#)
- random-detect discard-class command [18](#)
- random-detect dscp command [8, 18](#)
- random-detect exponential-weight-constant command [8](#)
- random-detect ip precedence command [18](#)
- random-detect precedence command [9](#)
- random early detection
 - combining with queue limit [10](#)
 - combining with tail drop [8](#)
 - description of [9, 34](#)
 - determining drop probability [10](#)
 - enabling [3](#)
 - queue limit [20](#)
 - recommended threshold settings [11](#)
 - restrictions for RED [23](#)
- rate, committed rate data [6](#)
- rate limiting
 - per session rate limiting [3, 10](#)
 - per user multiservice [4, 10](#)
 - PPPoA, PPPoE and RBE sessions [6](#)
 - PPP tunneled sessions [6](#)
- RBE, applying service-policies to sessions [10](#)
- Real-Time Protocol [4](#)
- RED, *See* random early detection.
- red packets [7](#)
- response time, improving [7](#)
- restrictions and limitations

- ATM PVC selection [17](#)
- Frame Relay QoS policies [13](#)
- LAC QoS policies [31](#)
- policy maps [2](#)
- VLAN QoS policies [21](#)

RFC 1490 [16](#)

RFC 791 [4](#)

RTP [4](#)

S

- SAR [5, 7, 39, 22, 24, 25](#)
 - determining VC weights [21](#)
- scalability, qos match statistics command [4](#)
- SCR, *See* sustained cell rate.
- segmentation and reassembly [5](#)
- serialization delay [2](#)
- service categories
 - atm pxf queuing mode [13](#)
 - no atm pxf queuing mode [13](#)
- service policies
 - applying [1](#)
 - attaching to interfaces [15](#)
 - components [5](#)
 - creating [5, 2](#)
 - defining input and output policies [12](#)
 - definition of [3](#)
- service-policy command [3, 5, 10, 11](#)
- service profile [52](#)
- session categories
 - IP session support [18](#)
- session level, oversubscription [53](#)
- session queuing
 - configuring on ATM VCs [54](#)
 - configuring on RADIUS [60](#)
 - configuring on virtual templates [54](#)
 - examples of configuring on ATM VCs [61](#)
 - interfaces supported [52](#)
 - prerequisites for ATM VCs [53](#)

- restrictions on ATM VCs 53
- verifying on ATM VCs 62
- session traffic queues 52
- set ATM CLP bit 13
- set atm-clp command 5, 6, 9, 14
- set-clp-transmit policing action 11, 3
- set command 5
- set cos command 5, 6, 12
- set-cos-transmit policing action 3, 15
- set discard-class command 16
- set-discard-class-transmit policing action 11, 3
- set-dscp-transmit policing action 12, 3
- set-dscp-tunnel-transmit policing action 3
- set Frame Relay DE bit 14
- set fr-de command 19
- set-frde-transmit policing action 4
- set ip dscp command 5, 6, 9
- set ip precedence command 5, 6, 9, 5
- set mpls experimental command 5, 6, 11
- set mpls experimental imposition command 15, 4
- set mpls experimental topmost command 16
- set-mpls-exp-imposition-transmit policing action 12, 4
- set-mpls-exp-transmit policing action 12, 4
- set-prec-transmit policing action 12, 4
- set-prec-tunnel-transmit policing action 4
- set qos-group command 5, 6, 9, 13, 7
- set-qos-transmit policing action 12, 4
- setting
 - class queue size 24
 - MPLS EXP field 7
- shape command 5, 6, 10, 4
- shaped UBR PVCs 13, 14, 5
- shaping
 - percentage 8
- shaping traffic
 - atm pxf queuing and shaping 8
 - bandwidth 10
 - class-based 3, 14
 - comparing shaping and policing 11
 - Frame Relay 8
 - hierarchical shaping 4, 15
 - interfaces not supporting shaping 13
 - overview 2
 - shaping classes 14
 - VC level 5, 15
 - verifying traffic shaping 17
- short pipe tunneling mode 3, 9
- show atm class-links command 41
- show atm interface command 41
- show atm vp command 19
- show caller command 16
- show class-map command 13, 16
- show controllers atm command 20
- show controllers command 41
- show ha pxf cpu queue summary 6
- show hardware pxf command 34, 33
- show interface command 32, 23, 32
- show interfaces virtual-access command 32
- show policy-map 18, 28
- show policy-map class command 12, 18, 28
- show policy-map command 19, 12, 18, 20, 28, 16
- show policy-map interface command 8, 33, 27
 - overhead accounting 11
 - overhead accounting restrictions 6
- show pppoe session all command 33
- show pppoe session packets command 33
- show pxf cpu queue atm command 19
- show pxf cpu queue command 33
- show pxf cpu queue interface command 32
- show pxf cpu queue summary command 33
- show pxf cpu schedule command 33
- show pxf interface command 33
- show pxf statistics qos policy-map interface command 20, 21
- show pxf statistics qos policy-map session command 21
- show queue command 20
- show vlans command 42
- simultaneous policy maps

- attaching to ATM VCs [9, 12](#)
- attaching to Ethernet interface [7](#)
- attaching to PPPoA sessions [8](#)
- attaching to PPPoE sessions [6, 10](#)
- attributes 37 and 39 [4](#)
- configuration examples [14](#)
- configuring [5](#)
- displaying statistics for LAC sessions [22](#)
- interface-level policy [2](#)
- on interface and PPP session [1](#)
- QoS actions [2](#)
- restrictions [4](#)
- session-level policy [2](#)
- verifying [18](#)
- single-rate color marker [4](#)
- slope, determining [10](#)
- SMS [5](#)
- specifying QoS [1](#)
- statements, match [2, 5, 11](#)
- statistics
 - collecting priority queuing information [11](#)
 - displaying
 - bandwidth information [12](#)
 - marking information [37](#)
 - policing information [41](#)
 - displaying drop information [32](#)
- strict QoS guarantees [25](#)
- subinterfaces, attaching
 - QoS policies [21](#)
 - VLAN QoS policies [31](#)
- sub-pool command [26](#)
- sub-pool tunnels [19](#)
 - differentiated services-traffic engineering [19](#)
 - strict QoS guarantees [25](#)
- subscriber management server [5](#)
- sustained cell rate [15, 13](#)
- system limits
 - class maps [2](#)
 - link fragmentation and interleaving [4](#)

- policy maps [2, 4](#)

T

- tag control information field [10](#)
- tag interface [5, 6](#)
- tail drop [8, 3](#)
- TCP/IP traffic, weighted random early detection [13](#)
- three-color marker, example configuration [33](#)
- three-color policer [44, 7](#)
- three-level hierarchical policies
 - child policies [8](#)
 - creating [15](#)
 - description of [6, 8](#)
 - parent policies [8](#)
 - restrictions for [9](#)
 - See also* hierarchical policies.
- thresholds
 - guidelines for changing [39](#)
 - maximum and minimum [19](#)
 - RED recommended settings [11](#)
 - WRED default drop thresholds [19](#)
- token bucket [2, 18, 21](#)
- ToS, *See* type of service field.
- traffic
 - classes [11, 16](#)
 - congestion [3](#)
 - drop policies
 - Frame Relay [3](#)
 - random early detection [20](#)
 - weighted random early detection [8](#)
 - marking
 - 802.1p [10](#)
 - actions [2](#)
 - ATM cell loss priority [14, 29](#)
 - class of service [10, 26](#)
 - description of [2, 15](#)
 - design guidelines for marking [21](#)
 - discard-class [16, 33](#)

- internal [2](#)
 - IP precedence [22](#)
 - Layer 2 marking [2](#)
 - Layer 2 to Layer 3 mapping [3](#)
 - Layer 3 marking [2](#)
 - MPLS experimental [31](#)
 - QoS group [28](#)
 - recommended values for marking [21](#)
 - restrictions for marking [20](#)
 - set ip dscp and set ip precedence commands for a packet [10](#)
 - verifying marking [37](#)
 - weighted random early detection marking [3](#)
 - MPLS experimental marking [14](#)
 - policing [11, 26](#)
 - QoS group marking [13](#)
 - shaping, Frame Relay [6](#)
 - traffic bumping [3](#)
 - traffic engineering
 - activating
 - interfaces [23](#)
 - routers [21](#)
 - configuration examples
 - midpoint routers [30](#)
 - tail-end routers [31](#)
 - tunnel head routers [28](#)
 - verifying configurations [26](#)
 - traffic marking
 - class of service [11](#)
 - configuring differentiated services code point [24](#)
 - interfaces not supporting marking [20](#)
 - interfaces supporting marking [20](#)
 - IP precedence values [4](#)
 - MPLS marking [15](#)
 - multiple priority levels [3](#)
 - QoS group [13](#)
 - traffic shaping
 - atm pxf queuing and shaping [8](#)
 - bandwidth [10](#)
 - class-based [3, 14](#)
 - comparing
 - shaping and policing [11](#)
 - shaping mechanisms [10](#)
 - Frame Relay [8, 5, 6](#)
 - hierarchical shaping [4, 15](#)
 - interfaces not supporting shaping [13](#)
 - interfaces supporting shaping [13](#)
 - overview [2](#)
 - shaping classes [14](#)
 - VC level [15](#)
 - verifying traffic shaping [17](#)
 - transmit policing action [4](#)
 - tunneling mode
 - MPLS QoS [3](#)
 - pipe [3, 10](#)
 - short pipe [3, 9](#)
 - uniform [3](#)
 - tunnel interfaces, configuring attributes [24](#)
 - tunnel packets, applying QoS policies [32](#)
 - tunnels
 - global pool [20](#)
 - sub-pool [19](#)
 - type of service field
 - description of [4](#)
 - DSCP bits [6](#)
-
- ## U
- ubr+ command [8, 9](#)
 - UBR, *See* unspecified bit rate.
 - ubr command [14, 8](#)
 - uniform tunneling mode [3](#)
 - unshaped UBR [13](#)
 - unspecified bit rate [13, 14, 8, 9](#)
 - user-defined offset
 - for overhead accounting [3, 8](#)
 - user profile [51](#)

V

VAI [3, 12, 13](#)

variable bit rate

nonreal time VBR [15](#)

nonreal time VBRs [15, 8, 9](#)

real time VBR [15](#)

variable bit rate-nonreal time

configuring in atm pxf queuing mode [8](#)

VBR-nrt, *See* variable bit rate-nonreal time.

vbr-nrt command [15, 8, 9](#)

VC class, adding bundle members [26](#)

vc-class atm command [9, 11](#)

vc-class command [29](#)

VCI [10](#)

VC scaling, active ATM VCs [7](#)

VC weights, determining [20](#)

verifying

Frame Relay PVC selection [52](#)

hierarchical policies [27](#)

packet dropping [32](#)

policing [41](#)

priority queuing [11](#)

PVC bundles [29](#)

QoS policies [32](#)

traffic engineering configurations [26](#)

video traffic, recommended marking values [21](#)

violate-action [6, 10, 12](#)

violating packets [7](#)

virtual access interface [5, 6](#)

attaching QoS policies [23](#)

creating [3](#)

See also VAI.

virtual channel identifier [14](#)

virtual circuit

calculating default weight [23](#)

changing the weight of [12, 27](#)

configuring queue depth [38](#)

configuring weight using class maps [29](#)

maximum VCs on ATM line cards [5](#)

supporting low count [8](#)

verifying oversubscription and weighting [41](#)

weighting configuration examples [38](#)

virtual LAN

configuring oversubscription [17](#)

creating VLAN subinterfaces [23](#)

encapsulating [19](#)

interfaces [7](#)

oversubscribing [9, 19](#)

queuing outbound traffic [7](#)

virtual path [22](#)

virtual path identifier [14, 10, 21](#)

virtual path tunnels, maximum VCs on ATM line cards [5](#)

virtual-template command [27, 10, 11](#)

virtual template interface

applying service policies [3, 13](#)

applying to BBA groups [27](#)

attaching policy maps [10, 11](#)

RADIUS server [23](#)

routed bridge encapsulation over ATM [24](#)

virtual access interfaces [23](#)

virtual time management system [2, 10, 22](#)

VLAN, *See* virtual LAN.

voice over Internet Protocol (VoIP) [4](#)

voice traffic, recommended marking values [21](#)

VoIP, *See* voice over Internet Protocol.

VP, *See* virtual path tunnels.

VPI, *See* virtual path identifier.

VP parameters, changing shaping parameters [12, 27](#)

VTMS, *See* virtual time management system.

W

watermarks, high and low [22, 24, 25, 38](#)

weight

calculating default VC weight [23](#)

configuring

for ATM virtual circuits [28, 31](#)

- on range of PVCs [30](#)
 - using class maps [29](#)
- determining VC weights [20, 22](#)
- restrictions for virtual circuit weighting [27](#)
- weight command [22, 24](#)
- weighted fair queuing [7, 2, 4](#)
- weighted random early detection
 - aggregate drop profiles [16](#)
 - based on ATM cell loss priority [11](#)
 - based on ATM CLP [31](#)
 - based on discard class [29](#)
 - based on discard-class [11](#)
 - based on DSCP [11, 26](#)
 - based on IP precedence [9, 11, 28](#)
 - benefits of [12](#)
 - description of
 - drop modes [13, 14](#)
 - drop profiles [14](#)
 - drop profiles on PRE3 [15](#)
 - how WRED works [13](#)
 - queue-limit [20](#)
 - random-detect command usage guidelines [18](#)
 - restrictions for WRED [23](#)
 - supported features [7](#)
 - traffic marking [3](#)
 - verifying packet dropping [32](#)
- WFQ [7](#)
- WRED, *See* weighted random early detection.

Y

- yellow
 - packets [7](#)
 - token bucket [18](#)