



Send documentation comments to mdsfeedback-doc@cisco.com.

CHAPTER 10

M Commands

The commands in this chapter apply to the Cisco MDS 9000 Family of multilayer directors and fabric switches. All commands are shown here in alphabetical order regardless of command mode. Please see the Command Mode section to determine the appropriate mode for each command. For more information, see the *Cisco MDS 9000 Family Configuration Guide*.

- mkdir
- move

[Send documentation comments to mdsfeedback-doc@cisco.com.](mailto:mdsfeedback-doc@cisco.com)

mkdir

To create a new directory in the flash file system, use the **mkdir** command.

mkdir {**bootflash:** | **slot0 :** | **volatile:**} *directory*

Syntax Description		
	bootflash:	Source or destination location for internal bootflash memory
	slot0:	Source or destination location for the CompactFlash memory or PCMCIA card
	<i>directory</i>	Name of the directory to create.

Defaults This command has no default settings.

Command Modes EXEC

Usage Guidelines This command is only valid on Class C Flash file systems.
If you do not specify the directory name in the command line, the switch prompts you for it.

Examples This example creates a directory called test in the slot0 directory.

```
switch# mkdir slot0:test
```

This example creates a directory called test at the current directory level.

```
switch# mkdir test
```

If the current directory is slot0:mydir, this command creates a directory called slot0:mydir/test.

Related Commands	Command	Description
	dir	Displays a list of files on a file system
	rmdir	Removes an existing directory in the flash file system.

Send documentation comments to mdsfeedback-doc@cisco.com.

move

To remove a file from the source directory and place it in the destination directory, use the **move** command.

move {**bootflash:** | **slot0 :** | **volatile:**} *directory* {**bootflash:** | **slot0 :** | **volatile:**} *directory*

Syntax Description

bootflash:	Source or destination location for internal bootflash memory
slot0:	Source or destination location for the CompactFlash memory or PCMCIA card
<i>directory</i>	Name of the directory to move, or to create.

Defaults

This command has no default settings.

Command Modes

EXEC

Usage Guidelines

If you do not specify the directory name in the command line, the switch prompts you for it.

Examples

This example moves the file called samplefile from the slot0 directory to the mystorage directory.

```
switch# move slot0:samplefile slot0:mystorage/samplefile
```

This example moves a file from the current directory level.

```
switch# move samplefile mystorage/samplefile
```

If the current directory is slot0:mydir, this command moves slot0:mydir/samplefile to slot0:mydir/mystorage/samplefile.

Related Commands

Command	Description
dir	Displays a list of files on a file system
mkdir	Creates a new directory in the flash file system
rmdir	Removes an existing directory in the flash file system.

Send documentation comments to mdsfeedback-doc@cisco.com.